

```
SYS-TEST-IAP225# sh running-config
version 6.4.2.0-4.1.1
virtual-controller-country IN
virtual-controller-key
c253286701715b21ce9e20ec91673293596d51df18dacdf36d
name SYS-TEST-ARUBA225
virtual-controller-ip 10.105.171.120
terminal-access
clock timezone Chennai 05 30
rf-band all

allow-new-aps
allowed-ap 84:d4:7e:c6:88:4a

routing-profile
route 0.0.0.0 0.0.0.0 10.105.171.10

arm
wide-bands 5ghz
80mhz-support
min-tx-power 18
max-tx-power 127
band-steering-mode prefer-5ghz
air-time-fairness-mode fair-access
client-aware
scanning

syslog-level warn ap-debug
syslog-level warn network
syslog-level warn security
syslog-level warn system
syslog-level warn user
syslog-level warn user-debug
syslog-level warn wireless

extended-ssid

user test ffdd0de6edd0355cb310df6d118ef026bcfcc49d8c590e34 portal

mgmt-user admin d800464e4e1a7332b7935b23da7aa4e5

wlan access-rule default_wired_port_profile
index 0
rule any any match any any any permit

wlan access-rule wired-instant
index 1
rule masterip 0.0.0.0 match tcp 80 80 permit
rule masterip 0.0.0.0 match tcp 4343 4343 permit
rule any any match udp 67 68 permit
rule any any match udp 53 53 permit

wlan access-rule Auba_mab
index 2
```

```
captive-portal external profile ise223_mab
rule 10.105.171.223 255.255.255.255 match tcp 1 20000 permit
rule any any match any any any permit

wlan access-rule Aruba_dot1x
index 3
captive-portal external profile ise223
rule any any match any any any permit
rule 10.105.171.223 255.255.255.255 match tcp 1 20000 permit

wlan ssid-profile Auba_mab
enable
index 0
type employee
ssid Auba_mab
opmode opensystem
max-authentication-failures 0
vlan 105
auth-server ISE223_MAB
rf-band all
captive-portal disable
mac-authentication
dtim-period 1
inactivity-timeout 1000
broadcast-filter arp
radius-accounting
dmo-channel-utilization-threshold 90
local-probe-req-thresh 0
max-clients-threshold 64

wlan ssid-profile Aruba_dot1x
enable
index 1
type employee
ssid Aruba_dot1x
opmode wpa2-aes
max-authentication-failures 0
vlan 105
auth-server ise223
rf-band all
captive-portal disable
dtim-period 1
inactivity-timeout 1000
broadcast-filter arp
radius-accounting
dmo-channel-utilization-threshold 90
local-probe-req-thresh 0
max-clients-threshold 64
dot11k

auth-survivability cache-time-out 24

wlan auth-server ise145
ip 10.105.171.145
port 1812
acctport 1813
key 1d44facfc63ada5b30d30e60ecbe47b9b2663aa5edbec874
nas-ip 10.105.171.120
rfc3576
```

```
cppm-rfc3576-port 5999

wlan auth-server isel29
ip 10.126.107.129
port 1812
acctport 1813
key b5b77ba85c768c2e1b29af4fb9b9a8635f0b1b3c316f1aea

wlan auth-server ise223
ip 10.105.171.223
port 1812
acctport 1813
key bb425233efd3f12508e5538491a5b73105304b20f1c24454
nas-ip 10.105.171.120
rfc3576
cppm-rfc3576-port 5999

wlan auth-server ISE223_MAB
ip 10.105.171.223
port 1812
acctport 1813
key 50550542f575f31a0db96dba4b13ef00b33d5fd77076a619
nas-ip 10.105.171.119
rfc3576
cppm-rfc3576-port 5999

wlan auth-server ISE205
ip 10.105.171.205
port 1812
acctport 1813
key fcd1e9b5c1406400530241db32d9d025b94fd1001e07cb0e
rfc3576
cppm-rfc3576-port 5999

wlan external-captive-portal
server localhost
port 80
url "/"
auth-text "Authenticated"
auto-whitelist-disable
https

wlan external-captive-portal ise223
server 10.105.171.223
port 8443
url "/portal/g?p=gZP9Rrqqy8Meqcj4jomvGZKAZr"
auth-text ""
auto-whitelist-disable
https

wlan external-captive-portal ise223_mab
server 10.105.171.223
port 8443
url "/portal/g?p=eMjakL5dpZL9jFOKQNXNbXykoO"
auth-text ""
auto-whitelist-disable
https

wlan external-captive-portal ISE205
server 10.105.171.205
port 5999
```

```
url "/"
auth-text ""
auto-whitelist-disable
https
```

```
blacklist-time 3600
auth-failure-blacklist-time 3600
```

```
ids
wireless-containment none
```

```
wired-port-profile wired-instant
switchport-mode access
allowed-vlan all
native-vlan guest
no shutdown
access-rule-name wired-instant
speed auto
duplex auto
no poe
type guest
captive-portal disable
no dot1x
inactivity-timeout 1000
```

```
wired-port-profile default_wired_port_profile
switchport-mode trunk
allowed-vlan all
native-vlan 1
shutdown
access-rule-name default_wired_port_profile
speed auto
duplex full
no poe
type employee
captive-portal disable
no dot1x
inactivity-timeout 1000
```

```
enet0-port-profile default_wired_port_profile
```

```
uplink
preemption
enforce none
failover-internet-pkt-lost-cnt 10
failover-internet-pkt-send-freq 30
failover-vpn-timeout 180
```

```
airgroup
disable
```

```
airgroupservice airplay
disable
description AirPlay
```

```
airgroupservice airprint
disable
```

description AirPrint

SYS-TEST-IAP225#