

elevate-0500-UC540 : Cisco Configuration Assistant

System Window Help

Home

Configure

- Ports
- Switching
- Routing
- Telephony
 - System
 - Ports and Trunks
 - Users/Extensions
 - Users and Phones
 - Voicemail
 - Single Number Reach
 - System Speed Dial
 - Local Directory
 - Phone Groups
 - Voice Features
 - Call Handling
 - Dial Plan
 - Site Management
 - Phone Customization
- Wireless
- Security
- Device Properties
- Save Configuration...

Applications

Monitor

Troubleshoot

Maintenance

Partner Connection

Users and Phones

Devices

Hostname: elevate-0500-UC540

User Extensions Floating Extensions Extension Mobility Analog Extensions

Extension	Call Forward All	First Name	Last Name	User ID	Voicemail
310					<input type="checkbox"/>
303					<input type="checkbox"/>
312					<input type="checkbox"/>
301					<input type="checkbox"/>
305					<input type="checkbox"/>
300					<input type="checkbox"/>
306					<input type="checkbox"/>
311					<input type="checkbox"/>
307					<input type="checkbox"/>
309					<input type="checkbox"/>
304					<input type="checkbox"/>
308					<input type="checkbox"/>

Add/Edit Floating Extension

Extension Settings

Number:

Call Forward All:

PSTN Number: No DID mapped

☐ Enable Voicemail

If voicemail is enabled, default password for phone access to voicemail is 1234.

User Information

These fields are only required for mailbox creation or AA dial-by-name service; otherwise, they can be left blank.

First Name:

Last Name:

User ID:

Password:

Clear User Fields

OK Cancel Help

Total Rows: 12

Add... Edit Delete...

OK Refresh Help

