



# Vonage Business Solutions Support

[SEARCH SUPPORT](#)

## SonicWALL Firewall Configuration

The SonicWALL firewall requires a few small adjustments to ensure the best quality of service. Although different versions of the Sonicwall operating system may have these settings in different places, the following steps will ensure your device will function properly.

### The VoIP Tab

1. Navigate to the router's web interface. This is usually <http://192.168.1.1>.
2. The default login credentials are:
  - **Username:** admin
  - **Password:** admin
3. Go to the **VoIP** tab (or Firewall tab, depending on the device's web interface) and then **VoIP**.
4. Near the top of the page, make sure **Enable Consistent NAT** is checked.
5. Further down on the page, make sure **Enable SIP Transformations** is unchecked.
6. Save your changes.

### Plans

[Unlimited Extensions](#)[Metered Extensions](#)[Virtual Extensions](#)[New Business Startup](#)[Phones and Routers](#)[International Long Distance](#)

## Features

[The Basics](#)

[Teleworking and Mobility](#)

[Productivity](#)

[Training and Compliance](#)

[Big Business Presence](#)

[Desktop & Plugins](#)

## Resources

[Customer Success Stories](#)

[Education Center](#)

[White Papers](#)

[Webinars](#)

[FAQs](#)

[Blog](#)

## About Us

[Press](#)

[Vonage Patents](#)

[Careers](#)

[Referrals](#)

[Login to Partner Portal](#)

[Contact Us](#)

---

[Facebook](#)

[LinkedIn](#)

[Twitter](#)

[YouTube](#)

[Google Plus](#)

[RSS](#)

---

© 2006-2015 Vonage Business Solutions | All Rights Reserved  
[Patents](#) | [Privacy Policy](#) | [Terms of Service](#)