

Phone Adapter with 2 Ports for Voice-Over-IP

PAP2

Voice

Info System SIP Provisioning Regional Line 1 Line 2 User 1 User 2

Advanced View (switch to basic view)

User Login

Call Progress Tones

Dial Tone:	350@-19,440@-19;20(*0/1+2)
Second Dial Tone:	420@-19,520@-19;10(*0/1+2)
Outside Dial Tone:	420@-16;10(*0/1)
Prompt Tone:	520@-19,620@-19;10(*0/1+2)
Busy Tone:	480@-19,620@-19;10(.5/.5/1+2)
Reorder Tone:	480@-19,620@-19;10(.125/.125/1+2)
Off Hook Warning Tone:	480@-10,620@0;10(.125/.125/1+2)
Ring Back Tone:	440@-19,480@-19;*(2/4/1+2)
Confirm Tone:	600@-16;1(.25/.25/1)
SIT1 Tone:	985@-16,1428@-16,1777@-16;20(.380/0/1,.380/0/2,.
SIT2 Tone:	914@-16,1371@-16,1777@-16;20(.274/0/1,.274/0/2,.
SIT3 Tone:	914@-16,1371@-16,1777@-16;20(.380/0/1,.380/0/2,.
SIT4 Tone:	985@-16,1371@-16,1777@-16;20(.380/0/1,.274/0/2,.
MWI Dial Tone:	350@-19,440@-19;2(.1/.1/1+2);10(*0/1+2)
Cfwd Dial Tone:	350@-19,440@-19;2(.2/.2/1+2);10(*0/1+2)
DND Dial Tone:	350@-19,440@-19;2(.2/.2/2);10(*0/1+2)
Holding Tone:	600@-19;*(.1/.1/1,.1/.1/1,.1/9.5/1)
Conference Tone:	350@-19;20(.1/.1/1,.1/9.7/1)
Secure Call Indication Tone:	397@-19,507@-19;15(0/2/0,.2/.1/1,.1/2.1/2)
Feature Invocation Tone:	350@-16;*(.1/.1/1)

Distinctive Ring Patterns

Ring1 Cadence:	60(2/4)	Ring2 Cadence:	60(.8/4,.8/4)
Ring3 Cadence:	60(.4/2,.4/2,.8/4)	Ring4 Cadence:	60(.3/2,1/2,.3/4)
Ring5 Cadence:	1(.5/.5)	Ring6 Cadence:	60(.2/4,.2/4,.2/4)
Ring7 Cadence:	60(.4/2,.4/2,.4/4)	Ring8 Cadence:	60(0.25/9.75)

Distinctive Call Waiting Tone Patterns

CWT1 Cadence:	30(.3/9.7)	CWT2 Cadence:	30(.1/1,.1/9.7)
CWT3 Cadence:	30(.1/1,.1/1,.1/9.	CWT4 Cadence:	30(.1/1,.3/1,.1/9.3)
CWT5 Cadence:	1(.5/.5)	CWT6 Cadence:	30(.1/1,.3/2,.3/9.1)
CWT7 Cadence:	30(.3/1,.3/1,.1/9.1)	CWT8 Cadence:	2.3(.3/2)

Distinctive Ring/CWT Pattern Names

Ring1 Name:	Bellcore-r1	Ring2 Name:	Bellcore-r2
Ring3 Name:	Bellcore-r3	Ring4 Name:	Bellcore-r4
Ring5 Name:	Bellcore-r5	Ring6 Name:	Bellcore-r6
Ring7 Name:	Bellcore-r7	Ring8 Name:	Bellcore-r8

Ring and Call Waiting Tone Spec

Ring Waveform:	Sinusoid	Ring Frequency:	20
Ring Voltage:	90	CWT Frequency:	440@-10
Synchronized Ring:	no		

Control Timer Values (sec)

Hook Flash Timer Min:	.1	Hook Flash Timer Max:	.9
Callee On Hook Delay:	0	Reorder Delay:	15
Call Back Expires:	1800	Call Back Retry Intvl:	30

Call Back Delay:	.5	VMWI Refresh Intvl:	0
Interdigit Long Timer:	10	Interdigit Short Timer:	3
CPC Delay:	10	CPC Duration:	0.5

**Vertical Service
Activation Codes**

Call Return Code:	*69	Blind Transfer Code:	*98
Call Back Act Code:	*66	Call Back Deact Code:	*86
Cfwd All Act Code:	*72	Cfwd All Deact Code:	*73
Cfwd Busy Act Code:	*90	Cfwd Busy Deact Code:	*91
Cfwd No Ans Act Code:	*92	Cfwd No Ans Deact Code:	*93
Cfwd Last Act Code:	*63	Cfwd Last Deact Code:	*83
Block Last Act Code:	*60	Block Last Deact Code:	*80
Accept Last Act Code:	*64	Accept Last Deact Code:	*84
CW Act Code:	*56	CW Deact Code:	*57
CW Per Call Act Code:	*71	CW Per Call Deact Code:	*70
Block CID Act Code:	*67	Block CID Deact Code:	*68
Block CID Per Call Act Code:	*81	Block CID Per Call Deact Code:	*82
Block ANC Act Code:	*77	Block ANC Deact Code:	*87
DND Act Code:	*78	DND Deact Code:	*79
CID Act Code:	*65	CID Deact Code:	*85
CWCID Act Code:	*25	CWCID Deact Code:	*45
Dist Ring Act Code:	*26	Dist Ring Deact Code:	*46
Speed Dial Act Code:	*74	Secure All Call Act Code:	*16
Secure No Call Act Code:	*17	Secure One Call Act Code:	*18
Secure One Call Deact Code:	*19	Conference Act Code:	
Attn-Xfer Act Code:		Modem Line Toggle Code:	*99
Media Loopback Code:	*03		
Referral Services Codes:			
Feature Dial Services Codes:			

**Vertical Service
Announcement Codes**

Service Annc Base Number:	
Service Annc Extension Codes:	

**Outbound Call Codec
Selection Codes**

Prefer G711u Code:	*017110	Force G711u Code:	*027110
Prefer G711a Code:	*017111	Force G711a Code:	*027111
Prefer G723 Code:	*01723	Force G723 Code:	*02723
Prefer G726r16 Code:	*0172616	Force G726r16 Code:	*0272616
Prefer G726r24 Code:	*0172624	Force G726r24 Code:	*0272624
Prefer G726r32 Code:	*0172632	Force G726r32 Code:	*0272632
Prefer G726r40 Code:	*0172640	Force G726r40 Code:	*0272640
Prefer G729a Code:	*01729	Force G729a Code:	*02729

Miscellaneous

Set Local Date (mm/dd):		Set Local Time (HH/mm):	
Time Zone:	GMT-05:00	FXS Port Impedance:	600
Daylight Saving Time Rule:	start=3/8/7/2:00;end=11/1/7/2:00;save=1		
FXS Port Input Gain:	-3	FXS Port Output Gain:	-3
DTMF Playback Level:	-16	DTMF Playback Length:	.1
Detect ABCD:	yes	Playback ABCD:	yes
Caller ID Method:	Bellcore(N.Amer,China)	FXS Port Power Limit:	3

Caller ID FSK
Standard:
More Echo
Suppression:

bell 202
no

Feature Invocation
Method: Default

Save Settings

Cancel Settings

