

SPA112 Configuration Utility

May 28, 2016 18:26

Information	Line 1
System	
SIP	General
Provisioning	Line Enable:
Regional	Streaming Audio Server (SAS)
Line 1	SAS Enable: SAS DLG Refresh Intvl:
User 1	SAS Inbound RTP Sink:
Line 2	NAT Settings
User 2	NAT Mapping Enable: NAT Keep Alive Enable:
	NAT Keep Alive Msg: NAT Keep Alive Dest:
	Network Settings
	SIP ToS/DiffServ Value: SIP CoS Value: [0-7]
	RTP ToS/DiffServ Value: RTP CoS Value: [0-7]
	Network Jitter Level: Jitter Buffer Adjustment:
	SIP Settings
	SIP Transport: SIP Port:
	SIP 100REL Enable: EXT SIP Port:
	Auth Resync-Reboot: SIP Proxy-Require:
	SIP Remote-Party-ID: SIP GUID:
	SIP Debug Option: RTP Log Intvl:
	Restrict Source IP: Referor Bye Delay:
	Refer Target Bye Delay: Referee Bye Delay:
	Refer-To Target Contact: Sticky 183:
	Auth INVITE: Reply 182 On Call Waiting:
	Use Anonymous With RPID: Use Local Addr In FROM:
	Call Feature Settings
	Blind Attn-Xfer Enable: MOH Server:
	Xfer When Hangup Conf: Conference Bridge URL:
	Conference Bridge Ports: Enable IP Dialing:
	Emergency Number: Mailbox ID:
	Feature Key Sync:
	Proxy and Registration
	Proxy:
	Outbound Proxy:
	Use Outbound Proxy: Use OB Proxy In Dialog:

Register:	Make Call Without Reg:
Register Expires:	Ans Call Without Reg:
Use DNS SRV:	DNS SRV Auto Prefix:
Proxy Fallback Intvl:	Proxy Redundancy Method:
Mailbox Subscribe URL:	Mailbox Subscribe Expires:
Subscriber Information	
Display Name:	User ID:
Password:	Use Auth ID:
Auth ID:	Resident Online Number:
SIP URI:	
Supplementary Service Subscription	
Call Waiting Serv:	Block CID Serv:
Block ANC Serv:	Dist Ring Serv:
Cfwd All Serv:	Cfwd Busy Serv:
Cfwd No Ans Serv:	Cfwd Sel Serv:
Cfwd Last Serv:	Block Last Serv:
Accept Last Serv:	DND Serv:
CID Serv:	CWCID Serv:
Call Return Serv:	Call Redial Serv:
Call Back Serv:	Three Way Call Serv:
Three Way Conf Serv:	Attn Transfer Serv:
Unattn Transfer Serv:	MWI Serv:
VMWI Serv:	Speed Dial Serv:
Secure Call Serv:	Referral Serv:
Feature Dial Serv:	Service Announcement Serv:
Reuse CID Number As Name:	CONFCID Serv:
Audio Configuration	
Preferred Codec:	Second Preferred Codec:
Third Preferred Codec:	Use Pref Codec Only:
Use Remote Pref Codec:	Codec Negotiation:
G729a Enable:	Silence Supp Enable:
G726-32 Enable:	Silence Threshold:
FAX V21 Detect Enable:	Echo Canc Enable:
FAX CNG Detect Enable:	FAX Passthru Codec:
FAX Codec Symmetric:	DTMF Process INFO:
FAX Passthru Method:	DTMF Process AVT:
FAX Process NSE:	DTMF Tx Method:
FAX Disable ECAN:	DTMF Tx Mode:
DTMF Tx Strict Hold Off Time:	FAX Enable T38:

Hook Flash Tx Method:

FAX T38 Redundancy:

FAX T38 ECM Enable:

FAX Tone Detect Mode:

Symmetric RTP:

FAX T38 Return to Voice:

Modem Line:

RTP to Proxy in Remote Hold:

Dial Plan

Dial Plan:

FXS Port Polarity Configuration

Idle Polarity:

Caller Conn Polarity:

Callee Conn Polarity:

Inserted from <<http://192.168.1.198/admin/voice/>>