

Call Progress Tones

Dial Tone:	425@-12;10(.6/1/1,.2/.2/1)
Second Dial Tone:	420@-19,520@-19;10(*0/1+2)
Outside Dial Tone:	425@-12;10(.6/1/1,.2/.2/1)
Prompt Tone:	520@-19,620@-19;10(*0/1+2)
Busy Tone:	425@-20;10(.5/.5/1)
Reorder Tone:	425@-12;10(.25/.25/1)
Off Hook Warning Tone:	425@-12;10(.25/.25/1)
Ring Back Tone:	425@-20;*(1/4)
Confirm Tone:	600@-16;1(.25/.25/1)
SIT1 Tone:	985@-16,1428@-16,1777@-16;20(.380/0/1,.380/0/2,.380/0/3,0/4/0)
SIT2 Tone:	914@-16,1371@-16,1777@-16;20(.274/0/1,.274/0/2,.380/0/3,0/4/0)
SIT3 Tone:	914@-16,1371@-16,1777@-16;20(.380/0/1,.380/0/2,.380/0/3,0/4/0)
SIT4 Tone:	985@-16,1371@-16,1777@-16;20(.380/0/1,.274/0/2,.380/0/3,0/4/0)
MWI Dial Tone:	350@-19,440@-19;2(.1/.1/1+2);10(*0/1+2)
Cfwd Dial Tone:	350@-19,440@-19;2(.2/.2/1+2);10(*0/1+2)
Holding Tone:	600@-19;*(.1/.1/1,.1/.1/1,.1/9.5/1)
Conference Tone:	350@-19;20(.1/.1/1,.1/9.7/1)
Secure Call Indication Tone:	397@-19,507@-19;15(0/2/0,.2/.1/1,.1/2.1/2)
VoIP PIN Tone:	600@-10;*(0/1/1,.1/.1/1,.1/.1/1,.1/.5/1)
PSTN PIN Tone:	600@-10;*(0/.7/1,.2/.1/1,.2/.1/1,.2/.5/1)
Feature Invocation Tone:	350@-16;*(.1/.1/1)

Distinctive Ring Patterns

Ring1 Cadence:	90(1/4)	Ring2 Cadence:	60(.8/.4,.8/4)
Ring3 Cadence:	60(.4/.2,.4/.2,.8/4)	Ring4 Cadence:	60(.3/.2,1/.2,.3/4)
Ring5 Cadence:	1(.5/.5)	Ring6 Cadence:	60(.2/.4,.2/.4,.2/4)
Ring7 Cadence:	60(.4/.2,.4/.2,.4/4)	Ring8 Cadence:	60(0.25/9.75)

Distinctive Call Waiting Tone Patterns

CWT1 Cadence:	60(.1/3)	CWT2 Cadence:	30(.1/.1,.1/9.7)
CWT3 Cadence:	30(.1/.1,.1/.1,.1/9.7)	CWT4 Cadence:	30(.1/.1,.3/.1,.1/9.3)
CWT5 Cadence:	1(.5/.5)	CWT6 Cadence:	30(.1/.1,.3/.2,.3/9.1)
CWT7 Cadence:	30(.3/.1,.3/.1,.1/9.1)	CWT8 Cadence:	2.3(.3/2)

Distinctive Ring/CWT Pattern Names

Ring1 Name:	Bellcore-r1	Ring2 Name:	Bellcore-r2
Ring3 Name:	Bellcore-r3	Ring4 Name:	Bellcore-r4
Ring5 Name:	Bellcore-r5	Ring6 Name:	Bellcore-r6
Ring7 Name:	Bellcore-r7	Ring8 Name:	Bellcore-r8

Ring and Call Waiting Tone Spec

Ring Waveform:	Sinusoid ▼	Ring Frequency:	25
Ring Voltage:	70	CWT Frequency:	425@-10

Control Timer Values (sec)

Hook Flash Timer Min:	.06	Hook Flash Timer Max:	.2
Callee On Hook Delay:	0	Reorder Delay:	0
Call Back Expires:	1800	Call Back Retry Intvl:	30
Call Back Delay:	.5	VMWI Refresh Intvl:	0
Interdigit Long Timer:	10	Interdigit Short Timer:	3
CPC Delay:	2	CPC Duration:	0

Vertical Service Activation Codes

Call Return Code:	*69	Call Redial Code:	*07
Blind Transfer Code:	*98	Call Back Act Code:	*66
Call Back Deact Code:	*86	Call Back Busy Act Code:	*05
Cfwd All Act Code:	*72	Cfwd All Deact Code:	*73
Cfwd Busy Act Code:	*90	Cfwd Busy Deact Code:	*91
Cfwd No Ans Act Code:	*92	Cfwd No Ans Deact Code:	*93
Cfwd Last Act Code:	*63	Cfwd Last Deact Code:	*83
Block Last Act Code:	*60	Block Last Deact Code:	*80
Accept Last Act Code:	*64	Accept Last Deact Code:	*84
CW Act Code:	*56	CW Deact Code:	*57
CW Per Call Act Code:	*71	CW Per Call Deact Code:	*70
Block CID Act Code:	*67	Block CID Deact Code:	*68
Block CID Per Call Act Code:	*81	Block CID Per Call Deact Code:	*82
Block ANC Act Code:	*77	Block ANC Deact Code:	*87
DND Act Code:	*78	DND Deact Code:	*79
CID Act Code:	*65	CID Deact Code:	*85
CWCID Act Code:	*25	CWCID Deact Code:	*45
Dist Ring Act Code:	*26	Dist Ring Deact Code:	*46
Speed Dial Act Code:	*74	Secure All Call Act Code:	*16
Secure No Call Act Code:	*17	Secure One Call Act Code:	*18
Secure One Call Deact Code:	*19	Conference Act Code:	
Attn-Xfer Act Code:		Modem Line Toggle Code:	*99
FAX Line Toggle Code:	#99		

Referral Services Codes:

Feature Dial Services Codes:

Vertical Service Announcement Codes

Service Annc Base Number:

Service Annc Extension Codes:

Outbound Call Codec Selection Codes

Prefer G711u Code:	*017110	Force G711u Code:	*027110
Prefer G711a Code:	*017111	Force G711a Code:	*027111
Prefer G723 Code:	*01723	Force G723 Code:	*02723
Prefer G726r16 Code:	*0172616	Force G726r16 Code:	*0272616
Prefer G726r24 Code:	*0172624	Force G726r24 Code:	*0272624
Prefer G726r32 Code:	*0172632	Force G726r32 Code:	*0272632
Prefer G726r40 Code:	*0172640	Force G726r40 Code:	*0272640
Prefer G729a Code:	*01729	Force G729a Code:	*02729

Miscellaneous

Set Local Date (mm/dd):

Set Local Time (HH/mm):

Time Zone:

GMT+02:00 ▼

FXS Port Impedance:

600

Daylight Saving Time Rule:

start=4/1/7;end=10/-1/7;save=1

FXS Port Input Gain:

-3

FXS Port Output Gain:

-3

DTMF Playback Level:

-16

DTMF Playback Length:

.1

Detect ABCD:

yes ▼

Playback ABCD:

yes ▼

Caller ID Method:

ETSI FSK

Caller ID FSK Standard:

bell 202 ▼

Feature Invocation Method:

Default ▼

More Echo Suppression:

no ▼

Undo All Changes

Submit All Changes

[User Login](#) | [basic](#) | advanced