

Router

Voice

Info | System | **SIP** | Provisioning | Regional | Line 1 | PSTN Line | User 1 | PSTN User | [ser Login](#) | [basic](#) | [advanced](#)

SIP Parameters

Max Forward:	70	Max Redirection:	5
Max Auth:	2	SIP User Agent Name:	\$VERSION
SIP Server Name:	\$VERSION	SIP Reg User Agent Name:	
SIP Accept Language:		DTMF Relay MIME Type:	application/dtmf-relay
Hook Flash MIME Type:	application/hook-flash	Remove Last Reg:	no ▼
Use Compact Header:	no ▼	Escape Display Name:	no ▼
RFC 2543 Call Hold:	yes ▼	Mark All AVT Packets:	yes ▼

SIP Timer Values (sec)

SIP T1:	.5	SIP T2:	4
SIP T4:	5	SIP Timer B:	32
SIP Timer F:	32	SIP Timer H:	32
SIP Timer D:	32	SIP Timer J:	32
INVITE Expires:	240	ReINVITE Expires:	30
Reg Min Expires:	1	Reg Max Expires:	7200
Reg Retry Intvl:	30	Reg Retry Long Intvl:	1200

Response Status Code Handling

SIT1 RSC:		SIT2 RSC:	
SIT3 RSC:		SIT4 RSC:	
Try Backup RSC:		Retry Reg RSC:	

RTP Parameters

RTP Port Min:	16384	RTP Port Max:	16482
RTP Packet Size:	0.030	Max RTP ICMP Err:	0
RTCP Tx Interval:	0	No UDP Checksum:	no ▼
Stats In BYE:	no ▼		

SDP Payload Types

NSE Dynamic Payload:	100	AVT Dynamic Payload:	101
INFOREQ Dynamic Payload:		G726r16 Dynamic Payload:	98
G726r24 Dynamic Payload:	97	G726r32 Dynamic Payload:	2
G726r40 Dynamic Payload:	96	G729b Dynamic Payload:	99
NSE Codec Name:	NSE	AVT Codec Name:	telephone-event
G711u Codec Name:	PCMU	G711a Codec Name:	PCMA
G726r16 Codec Name:	G726-16	G726r24 Codec Name:	G726-24
G726r32 Codec Name:	G726-32	G726r40 Codec Name:	G726-40
G729a Codec Name:	G729a	G729b Codec Name:	G729ab
G723 Codec Name:	G723		

NAT Support Parameters

Handle VIA received:	no ▼	Handle VIA rport:	no ▼
Insert VIA received:	no ▼	Insert VIA rport:	no ▼
Substitute VIA Addr:	no ▼	Send Resp To Src Port:	no ▼
STUN Enable:	no ▼	STUN Test Enable:	no ▼
STUN Server:		EXT IP:	
EXT RTP Port Min:		NAT Keep Alive Intvl:	15

Undo All Changes

Submit All Changes

[User Login](#) | [basic](#) | advanced