

Router

Voice

Info | System | SIP | Provisioning | Regional | **Line 1** | PSTN Line | User 1 | PSTN User | [ser Login](#) | [basic](#) | [advanced](#)

Line Enable: yes ▼

Streaming Audio Server (SAS)

SAS Enable: no ▼ SAS DLG Refresh Intvl: 30
SAS Inbound RTP Sink:

NAT Settings

NAT Mapping Enable: no ▼ NAT Keep Alive Enable: no ▼
NAT Keep Alive Msg: \$NOTIFY NAT Keep Alive Dest: \$PROXY

Network Settings

SIP ToS/DiffServ Value: 0x68 SIP CoS Value: 3 [0-7]
RTP ToS/DiffServ Value: 0xb8 RTP CoS Value: 6 [0-7]
Network Jitter Level: high ▼ Jitter Buffer Adjustment: up and down ▼

SIP Settings

SIP Port: 5061 SIP 100REL Enable: no ▼
EXT SIP Port: Auth Resync-Reboot: yes ▼
SIP Proxy-Require: SIP Remote-Party-ID: yes ▼
SIP GUID: no ▼ SIP Debug Option: none ▼
RTP Log Intvl: 0 Restrict Source IP: no ▼
Referor Bye Delay: 4 Refer Target Bye Delay: 0
Referee Bye Delay: 0 Refer-To Target Contact: no ▼
Sticky 183: no ▼

Call Feature Settings

Blind Attn-Xfer Enable: no ▼ MOH Server:
Xfer When Hangup Conf: yes ▼

Proxy and Registration

Proxy:
Outbound Proxy:
Use Outbound Proxy: no ▼ Use OB Proxy In Dialog: yes ▼
Register: yes ▼ Make Call Without Reg: yes ▼
Register Expires: 3600 Ans Call Without Reg: no ▼
Use DNS SRV: no ▼ DNS SRV Auto Prefix: no ▼
Proxy Fallback Intvl: 3600 Proxy Redundancy Method: Normal ▼
Voice Mail Server: Mailbox Subscribe Expires: 2147483647

Subscriber Information

Display Name: User ID: 2160817753948
Password: Use Auth ID: no ▼
Auth ID:
Mini Certificate:

SRTP Private Key:

Supplementary Service Subscription

Call Waiting Serv:	yes ▼	Block CID Serv:	yes ▼
Block ANC Serv:	yes ▼	Dist Ring Serv:	yes ▼
Cfwd All Serv:	yes ▼	Cfwd Busy Serv:	yes ▼
Cfwd No Ans Serv:	yes ▼	Cfwd Sel Serv:	yes ▼
Cfwd Last Serv:	yes ▼	Block Last Serv:	yes ▼
Accept Last Serv:	yes ▼	DND Serv:	yes ▼
CID Serv:	yes ▼	CWCID Serv:	yes ▼
Call Return Serv:	yes ▼	Call Redial Serv:	yes ▼
Call Back Serv:	yes ▼	Three Way Call Serv:	yes ▼
Three Way Conf Serv:	yes ▼	Attn Transfer Serv:	yes ▼
Unattn Transfer Serv:	yes ▼	MWI Serv:	yes ▼
VMWI Serv:	yes ▼	Speed Dial Serv:	yes ▼
Secure Call Serv:	yes ▼	Referral Serv:	yes ▼
Feature Dial Serv:	yes ▼	Service Announcement Serv:	no ▼

Audio Configuration

Preferred Codec:	G711u ▼	Silence Supp Enable:	no ▼
Use Pref Codec Only:	no ▼	Silence Threshold:	medium ▼
G729a Enable:	yes ▼	Echo Canc Enable:	yes ▼
G723 Enable:	yes ▼	Echo Canc Adapt Enable:	yes ▼
G726-16 Enable:	yes ▼	Echo Supp Enable:	yes ▼
G726-24 Enable:	yes ▼	FAX CED Detect Enable:	yes ▼
G726-32 Enable:	yes ▼	FAX CNG Detect Enable:	yes ▼
G726-40 Enable:	yes ▼	FAX Passthru Codec:	G711u ▼
DTMF Process INFO:	yes ▼	FAX Codec Symmetric:	yes ▼
DTMF Process AVT:	yes ▼	FAX Passthru Method:	NSE ▼
DTMF Tx Method:	Auto ▼	FAX Process NSE:	yes ▼
Hook Flash Tx Method:	None ▼	FAX Disable ECAN:	no ▼
Release Unused Codec:	yes ▼	FAX Enable T38:	yes ▼
FAX T38 Redundancy:	1 ▼	FAX Tone Detect Mode:	caller or callee ▼
Symmetric RTP:	yes ▼		

Gateway Accounts

Gateway 1:		GW1 NAT Mapping Enable:	no ▼
GW1 Auth ID:		GW1 Password:	
Gateway 2:		GW2 NAT Mapping Enable:	no ▼
GW2 Auth ID:		GW2 Password:	
Gateway 3:		GW3 NAT Mapping Enable:	no ▼
GW3 Auth ID:		GW3 Password:	
Gateway 4:		GW4 NAT Mapping Enable:	no ▼
GW4 Auth ID:		GW4 Password:	

VoIP Fallback To PSTN

Auto PSTN Fallback: no ▼

Dial Plan

Dial Plan: xx.<:@gw0>

Enable IP Dialing: yes ▼

Emergency Number:

FXS Port Polarity Configuration

Idle Polarity: Forward ▼

Caller Conn Polarity: Forward ▼

Callee Conn Polarity: Forward ▼

Undo All Changes

Submit All Changes

[User Login](#) [basic](#) | [advanced](#)