



Texto original

Sugiere una traducción mejor

```

14 - Cisco Systems - # DEVELOPMENT Model=78xx Version=10-1-1SR1-4
[TZ=GMT-00:00] Wed Apr 11 08:39:22 2012
=====
===== [14]
7145 NOT 08:39:22.823891 dgetfile(5893)- alt-tftp1:::
7146 NOT 08:39:22.838141 dgetfile(5893)- alt-tftp2:::
7147 NOT 08:39:22.838208 dgetfile(5893)- domain:
7148 NOT 08:39:22.838247 dgetfile(5893)- tftpname:
7149 NOT 08:39:22.838283 dgetfile(5893)- ipmode:1
7150 NOT 08:39:22.838317 dgetfile(5893)------
7151 NOT 08:39:22.838354 dgetfile(5893)-parseDhcpInfoIntoTftpList(): no valid load server
7152 NOT 08:39:22.838389 dgetfile(5893)-Set tftpList from tftp_alt
7153 NOT 08:39:22.838423 dgetfile(5893)-tftpList[0] = 10.53.2.36
7154 NOT 08:39:22.838458 dgetfile(5893)-Set tftpList from Final
7155 NOT 08:39:22.838492 dgetfile(5893)-tftpList[0] = 10.53.2.36
7156 NOT 08:39:22.838528 dgetfile(5893)-AUTH.SRVR [GT5893] look up server - 0 - ::ffff:10.53.2.36
7157 NOT 08:39:22.875144 dgetfile(5893)-AUTH.SRVR [GT5893] authentication retval = 10
7158 NOT 08:39:22.875299 dgetfile(5893)-XXTP Secure file requested
7159 NOT 08:39:22.875340 dgetfile(5893)-XXTP Non secure file approved -- SEP547C69D68B99.cnf.xml
7160 NOT 08:39:22.875377 dgetfile(5893)-XXTP start request, server 1 - 10.53.2.36
7161 NOT 08:39:22.885600 GHTTP-LIMIT download will be limited to 2048 KB
7162 NOT 08:39:22.885971 GHTTP-fileServer 10.53.2.36
7163 NOT 08:39:22.886416 GHTTP-getaddrinfo ok family 2 socktype 1 protocol 6
7164 NOT 08:39:22.887419 GHTTP-connect6() failed
7165 NOT 08:39:22.889400 dgetfile(5893)-NO-HTTP with code 102 force=0
7166 NOT 08:39:22.897952 TFTP-pid = 5907
7167 NOT 08:39:22.911680 TFTP-LIMIT download will be limited to 2048 KB
7168 NOT 08:39:22.912105 TFTP-ai_family = 2, sockType = 2, protocol = 17
7169 NOT 08:39:22.912385 TFTP-Requesting SEP547C69D68B99.cnf.xml from 10.53.2.36
7170 NOT 08:39:22.926568 TFTP-Finished: rcvd 8545 bytes
7171 NOT 08:39:22.930452 dgetfile(5893)-XXTP complete - status = 0
7172 NOT 08:39:22.930551 dgetfile(5893)-XXTP actualserver [10.53.2.36]
7173 NOT 08:39:22.946805 dgetfile(5893)-DDGETTFTP.RESULT [_0_ [PASS] No error
]
7174 NOT 08:39:22.948202 downd-SOCKET accept errno=4 "Interrupted system call"
7175 NOT 08:39:22.991274 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - Config handleTftpResponse,
status=0 for file=ram/SEP547C69D68B99.cnf.xml.59066
7176 ERR 08:39:22.991420 JAVA: configmgr MQThread|cip.xml.XmlParser: - The Encoding ASCII is
invalid
7177 WRN 08:39:23.038043 JAVA: configmgr MQThread|cip.xml.XmlParser: - XML Parser Warning: Unknown
element 'uid' in element '/device/networkLocaleInfo' (line=183)
7178 DEB 08:39:23.042148 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - Update common parameters -
STARTS
7179 ERR 08:39:23.042818 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - DirectoryUrl
securedirectoryUrl
7180 DEB 08:39:23.043954 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - No SideCar Module
configured
7181 DEB 08:39:23.045051 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - TZ data Missing
7182 DEB 08:39:23.050514 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - Update common parameters -
ENDS
7183 DEB 08:39:23.051588 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - NO SRST configured
7184 INF 08:39:23.061290 JAVA: configmgr MQThread|cip.xml.XmlSipConfigObject:? - Clearing tvsconfig
information
7185 NOT 08:39:23.061825 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - setConfigTvsProperty IP
mode 0IP Pref 0DSCP 96
7186 NOT 08:39:23.062136 JAVA: configmgr MQThread|cip.sec.TvsProperty:? - TVS IPv4 - 1 :TVS IPv6 -
1 :TVS Port - 1:0TVS IPv4 - 2 :TVS IPv6 - 2 :TVS Port - 2:0TVS IPv4 - 3 :TVS IPv6 - 3 :TVS Port -
3:0IP Address Mode:0IP Preference Mode:0

```

```
7187 NOT 08:39:23.063089 SECUREAPP-processing add tvs file req
7188 NOT 08:39:23.063273 SECUREAPP-Invalid TVS server data passed - v4 Addr:, v6 Addr:, port:
244832
7189 NOT 08:39:23.063372 SECUREAPP-No primary TVS Server found, TVS disabled
7190 NOT 08:39:23.063465 SECUREAPP-clear previous tvs info
7191 NOT 08:39:23.090920 SECUREAPP-add tvs file req done, clnt</tmp/secClnt_pid_2111_34586992>
7192 NOT 08:39:23.113514 SECUREAPP-processing ip mode pref req
7193 NOT 08:39:23.117020 SECUREAPP-ip mode pref req done, clnt</tmp/secClnt_pid_2111_34586993>
7194 NOT 08:39:23.165068 SECUREAPP-processing set tos req
7195 NOT 08:39:23.169514 SECUREAPP-set tos req done, clnt</tmp/secClnt_pid_2111_34586994>
7196 NOT 08:39:23.216082 downd-Enter the case of DD_SET_TEMP_TFTP
7197 NOT 08:39:23.216207 downd-DDFORK - execing [/usr/sbin/dsetftftp][L200][ ]
7198 NOT 08:39:23.234475 dsetftftp-SETTFTP [5916] emcc_mode =0, override =0, tempTftp1= , tempTftp2
= , tempTftp3 = , tempTftp4 =
7199 NOT 08:39:23.234765 dsetftftp-SETTFTP [5916] EMCC Config file doesn't exist
7200 NOT 08:39:23.236148 dsetftftp-dsettempftftp.RESULT [Error description unknown]
7201 NOT 08:39:23.238276 downd-SOCKET accept errno=4 "Interrupted system call"
7202 NOT 08:39:23.238738 SECUREAPP-SEC_GET_EMCC: EMCC mode disabled
7203 NOT 08:39:23.238879 SECUREAPP-SEC_GET_EMCC: EMCC mode disabled
7204 NOT 08:39:23.290341 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - ===not full config or not
emcc mode ,so do vendor config
7205 DEB 08:39:23.290482 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - No Common info configured
7206 DEB 08:39:23.290526 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - No Enterprise info
configured
7207 NOT 08:39:23.292089 SECUREAPP-cert info, req done, clnt</tmp/secClnt_pid_2111_34586996>
7208 DEB 08:39:23.391269 JAVA: --> PropertySetIpAddressingMode: IPv4_ONLY
7209 DEB 08:39:23.391404 JAVA: setsshIPMode 1
7210 DEB 08:39:23.391446 JAVA: setsshIPMode: IPv4_MODE
7211 DEB 08:39:23.391486 JAVA: command: cp -f /tmp/sshd.tmp /usr/local/etc/sshd
7212 NOT 08:39:23.400768 JAVA: upgrade MQThread|UpgradeService: - request =>
IPv4 Load Server: -> , IPv6 Load Server: -> , IPv4 Log Server: -> , ip-addressing-mode:0,
ppid-enabled:true -> true
7213 NOT 08:39:23.412206 JAVA: Seamless Upgrade Thread|UpgradeService: - Got request for
(sip78xx.10-1-1SR1-4.loads) when we are already running (sip78xx.10-1-1SR1-4.loads)
7214 NOT 08:39:23.412554 JAVA: Seamless Upgrade Thread|UpgradeService: - and () when we already
have (). Ignoring this request.
7215 NOT 08:39:23.412908 JAVA: Seamless Upgrade Thread|UpgradeService: - notifyListeners Notifying
2 listeners of status=4
7216 WRN 08:39:23.413679 JAVA: System P7-display MQThread|DisplayTask:? - DispayTask-----
upgradeStatus-----statusChanged-----statusVal=4
7217 NOT 08:39:23.413909 JAVA: Seamless Upgrade Thread|cip.cfg.SipConfig:statusChanged - >>
status=4
7218 NOT 08:39:23.414084 JAVA: Seamless Upgrade Thread|cip.cfg.SipConfig:statusChanged - <<
status=4
7219 NOT 08:39:23.414276 JAVA: Seamless Upgrade Thread|UpgradeService: - notifyListeners << leaving
status=4
7220 DEB 08:39:23.432754 JAVA: send msg to netsd retval: 1
7221 NOT 08:39:23.432860 NETSD-eventThrd(): oversubscribed, interest is not registered
7222 DEB 08:39:24.441316 JAVA: setipmode(): pid = 2111
7223 DEB 08:39:24.441469 JAVA: setipmode(): NETSD_MESSAGE_QUE: key->0x100f1035 mode = 1
7224 DEB 08:39:24.441524 JAVA: setipmode(): msgsnd() rc: 0, size: 8 bytes
7225 DEB 08:39:24.441570 JAVA: <-- PropertySetIpAddressingMode: IPv4_ONLY, rc=0
7226 NOT 08:39:24.441825 NETSD-Set IP mode 1
7227 NOT 08:39:24.441884 NETSD-Requestted IP mode is same as current mode
7228 NOT 08:39:24.552470 SECUREAPP-processing set ssh info req
7229 NOT 08:39:24.562619 SECUREAPP-Enabled SSH mode
7230 NOT 08:39:24.562907 SECUREAPP-set ssh info, req done, clnt</tmp/secClnt_pid_2111_34587000>
7231 ERR 08:39:24.607294 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - informationUrl is
7232 ERR 08:39:24.607480 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - directoriesUrl is
7233 ERR 08:39:24.607537 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - messagesUrl is
7234 ERR 08:39:24.607583 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - servicesUrl is
7235 ERR 08:39:24.607628 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - authenticationUrl is
7236 ERR 08:39:24.607708 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - idleUrl is
7237 ERR 08:39:24.607753 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - messagesUrl is null
7238 ERR 08:39:24.607796 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - servicesUrl of null
7239 ERR 08:39:24.607841 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - info url of null
7240 ERR 08:39:24.607884 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - dir Url of null
7241 ERR 08:39:24.607927 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - idle Url of null
7242 ERR 08:39:24.607970 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - auth Url of null
7243 ERR 08:39:24.608013 JAVA: configmgr MQThread|VendorConfig:? - vendorconfig :
```

setConfigProperties

```
7244 DEB 08:39:24.608055 JAVA: setportcfg(): pid: 2111
7245 DEB 08:39:24.624968 JAVA: setportcfg(): msgsnd() rc: 0 size: 828 bytes
7246 ERR 08:39:24.625827 JAVA: configmgr MQThread|cip.props.NativePropertyStore:? -
device.settings.config.vendorconfig.ipv6logserver IO error.
7247 ERR 08:39:24.626536 JAVA: setespconfig: inetdMsgQue has not been created : No such file or
directory
7248 DEB 08:39:24.627698 JAVA: setportcfg(): pid: 2111
7249 DEB 08:39:24.628113 JAVA: setportcfg(): msgsnd() rc: 0 size: 828 bytes
7250 ERR 08:39:24.628439 JAVA: configmgr MQThread|VendorConfig:? -
About to set WebAccess
7251 INF 08:39:24.629325 JAVA: configmgr MQThread|DisplayTask:? - device.settings.energywise.config
changed
7252 DEB 08:39:24.629622 JAVA: configmgr MQThread - ----- detecting property change for
device.settings.energywise.config
7253 DEB 08:39:24.629884 JAVA: configmgr MQThread - DisplayTask-----propertyChanged-----
PowerOffTime=24:00
7254 DEB 08:39:24.630112 JAVA: configmgr MQThread - DisplayTask-----propertyChanged-----
PowerOnTime=00:00
7255 WRN 08:39:24.630388 JAVA: configmgr MQThread|DisplayTask:? - resetCurrentPowerState():
Energywise is disabled
7256 WRN 08:39:24.630623 JAVA: configmgr MQThread|DisplayTask:? - resetCurrentPowerState():
Energywise null domain
7257 WRN 08:39:24.630847 JAVA: configmgr MQThread|DisplayTask:? - resetCurrentPowerState():
Energywise null secret
7258 DEB 08:39:24.631070 JAVA: configmgr MQThread|DisplayTask:? - resetCurrentPowerState(): Non
EMCC mode
7259 WRN 08:39:24.631398 kernel: [ 756.705398] ##### garp_enabled #####
7260 WRN 08:39:24.631715 JAVA: configmgr MQThread|DisplayTask:? - resetCurrentPowerState(): no
time changed, so needn't reschedule existing timer
7261 INF 08:39:24.644166 JAVA: configmgr MQThread|DisplayTask:? - device.settings.powersave changed
7262 DEB 08:39:24.644490 JAVA: configmgr MQThread - ----- detecting property change for
device.settings.powersave
7263 DEB 08:39:24.644714 JAVA: configmgr MQThread - DisplayTask-----propertyChanged-----
PowerOffTime=24:00
7264 DEB 08:39:24.644889 JAVA: configmgr MQThread - DisplayTask-----propertyChanged-----
PowerOnTime=00:00
7265 DEB 08:39:24.645089 JAVA: configmgr MQThread|DisplayTask:? - isUriTimerSet=false
7266 DEB 08:39:24.645253 JAVA: configmgr MQThread|DisplayTask:? - theDisplayOnTimer
7267 DEB 08:39:24.645930 JAVA: configmgr MQThread|DisplayTask:? - theDisplayOffTimer
7268 INF 08:39:24.646887 JAVA: configmgr MQThread|DisplayTask:? - Created TimeToOnTimer with
interval of: 3600000
7269 INF 08:39:24.647588 JAVA: configmgr MQThread|DisplayTask:? - Created TimeToOffTimer with
interval of: 3600000
7270 DEB 08:39:24.648119 JAVA: configmgr MQThread|DisplayTask:? - isWithinActiveTime=false
7271 DEB 08:39:24.648694 JAVA: configmgr MQThread|DisplayTask:? - IsIdleTimerSet=false
isRunning=false
7272 DEB 08:39:24.648888 JAVA: configmgr MQThread|DisplayTask:? - clearIdleTimer()
7273 DEB 08:39:24.649056 JAVA: configmgr MQThread|DisplayTask:? - isUriTimerSet=false
7274 DEB 08:39:24.649244 JAVA: configmgr MQThread|DisplayTask:? - DisplayOff(): is display
currently off? false
7275 DEB 08:39:24.649408 JAVA: configmgr MQThread|DisplayTask:? - isDisplayOn=true
7276 NOT 08:39:24.650175 PWRMAN-setMode(): LOW
7277 NOT 08:39:24.650609 PWRMAN-eventRcv(): rcv() failed : Connection reset by peer
7278 ERR 08:39:24.651328 JAVA: configmgr MQThread|cip.g3.userio.InputManager:? - lightLamp.. type =
10 value= 1 state= 2 color=0
7279 WRN 08:39:24.651417 kernel: [ 756.727681] Set LCD backlight 0
7280 WRN 08:39:24.651807 JAVA: configmgr MQThread|DisplayTask:? - acceptEWPowSetting(): level 7
7281 NOT 08:39:24.652111 JAVA: --> PropertySetEnergywiseSwitchLevel: 7
7282 NOT 08:39:24.652488 EWCLIENT-event_rcv(): LSOCK_CMD_EVENT: EV_CHANGE_LEVEL: 7
7283 NOT 08:39:24.652551 EWCLIENT-ewcl_eventThrd(): waiting for socket activity
7284 NOT 08:39:24.652921 EWCLIENT-event_rcv(): LSOCK_CMD_EVENT: EV_GET_LEVEL proc:
7285 NOT 08:39:24.652984 EWCLIENT-send_level_reply(): cmd: 0x5 event: 0xc00 status: 0x0 error:
0x0 level: 7 fd: 12
7286 NOT 08:39:24.653026 EWCLIENT-ewcl_eventThrd(): waiting for socket activity
7287 NOT 08:39:24.653247 JAVA: <-- PropertySetEnergywiseSwitchLevel
7288 DEB 08:39:24.653512 JAVA: configmgr MQThread|DisplayTask:? - isFullyRegistered=false
7289 DEB 08:39:24.653703 JAVA: configmgr MQThread|DisplayTask:? - DisplayOn(): is display currently
on? false
7290 DEB 08:39:24.653904 JAVA: configmgr MQThread|DisplayTask:? - isDisplayOn=false
```

```
7291 ERR 08:39:24.654256 JAVA: configmgr MQThread|cip.g3.userio.InputManager:? - lightLamp.. type =
10 value= 1 state= 1 color=0
7292 WRN 08:39:24.654481 JAVA: configmgr MQThread|DisplayTask:? - acceptEWPowSetting(): level 10
7293 NOT 08:39:24.654697 JAVA: --> PropertySetEnergywiseSwitchLevel: 10
7294 NOT 08:39:24.654974 EWCLIENT-event_rcv(): LSOCK_CMD_EVENT: EV_CHANGE_LEVEL: 10
7295 NOT 08:39:24.655034 EWCLIENT-ewcl_eventThrd(): waiting for socket activity
7296 NOT 08:39:24.655372 EWCLIENT-event_rcv(): LSOCK_CMD_EVENT: EV_GET_LEVEL proc:
7297 NOT 08:39:24.655430 EWCLIENT-send_level_reply(): cmd: 0x5 event: 0xc00 status: 0x0 error:
0x0 level: 10 fd: 12
7298 NOT 08:39:24.655473 EWCLIENT-ewcl_eventThrd(): waiting for socket activity
7299 NOT 08:39:24.655642 JAVA: <-- PropertySetEnergywiseSwitchLevel
7300 NOT 08:39:24.656343 PWRMAN-setMode(): NORMAL
7301 NOT 08:39:24.656764 PWRMAN-eventRcv(): rcv() failed : Connection reset by peer
7302 WRN 08:39:24.661497 kernel: [ 756.733918] Set LCD backlight 1
7303 ERR 08:39:24.664587 JAVA: configmgr MQThread|VendorConfig:? - WebAccess true
7304 ERR 08:39:24.664913 JAVA: configmgr MQThread|VendorConfig:? - WebProtocol 0
7305 NOT 08:39:24.665989 JAVA: configmgr MQThread|VendorConfig:? - Setting 80-bit-srtp to false
7306 DEB 08:39:24.675073 JAVA: setportcfg(): pid: 2111
7307 DEB 08:39:24.675495 JAVA: setportcfg(): msgsnd() rc: 0 size: 828 bytes
7308 DEB 08:39:24.675740 JAVA: setportcfg(): pid: 2111
7309 DEB 08:39:24.675964 JAVA: setportcfg(): msgsnd() rc: 0 size: 828 bytes
7310 DEB 08:39:24.676379 JAVA: configmgr MQThread|cip.cfg.SipTargetConfig:? - ===== stonemark
CMCconnection
7311 DEB 08:39:24.676755 JAVA: settcptimeoutmode(): pid: 2111
7312 NOT 08:39:24.677177 NETSD-netsdSetTCPTimeoutMode(): 0
7313 DEB 08:39:24.677351 JAVA: settcptimeoutmode(): msgsnd(): rc: 0 size: 8 bytes
7314 DEB 08:39:24.677574 JAVA: configmgr MQThread|cip.cfg.SipTargetConfig:? - ===== stonemark
Ringvolume
7315 DEB 08:39:24.677845 JAVA: configmgr MQThread|cip.cfg.SipTargetConfig:? - ===== stonemark
HeadsetMonitor
7316 DEB 08:39:24.678089 JAVA: configmgr MQThread|cip.cfg.SipTargetConfig:? - ===== stonemark
EMCCMode
7317 INF 08:39:24.678342 JAVA: configmgr MQThread|VendorConfig:setConfigProperties - current
sshAccess:false,emccMode:false
7318 INF 08:39:24.678535 JAVA: configmgr MQThread|VendorConfig:setConfigProperties - downloaded
sshAccess:1, new sshAccess:false
7319 NOT 08:39:24.719471 JAVA: configmgr MQThread|VendorConfig:? - Setting RTCP to false
7320 NOT 08:39:24.720478 ms-FEATUREMGR.ms_enableFeature ms_enableFeature: [configNumber=4]
[enabled=0]
7321 NOT 08:39:24.720570 ms-FEATUREMGR.ftm_enableFeature ms_CONFIGTYPE_RINGOUTOFBAND unsupported
7322 NOT 08:39:24.721857 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
LocaleManager detect propety changed: device.settings.config.localization.userlocale.charset
7323 NOT 08:39:24.728778 CDP-cdpSetPCVlanAccess(): ENABLE
7324 NOT 08:39:24.733754 JAVA: HTTP JNI| Java_cip_http_NativeHttpTask_updateUserLocaleCharSet:
setting Http Char Set to [Accept-Charset: utf-8,iso-8859-1;q=0.8]
7325 NOT 08:39:24.734128 JAVA: HTTP JNI| Java_cip_http_NativeHttpTask_updateUserLocaleLangCode:
setting Http Language Tag to [Accept-Language: en_US]
7326 DEB 08:39:24.737412 JAVA: setapptos(150): pid: 2111
7327 DEB 08:39:24.737811 JAVA: setapptos(): msgsnd(): rc: 0 size: 8 bytes
7328 NOT 08:39:24.737881 JAVA: HTTP JNI| setTos: call to mg_set_tos
7329 DEB 08:39:24.738637 JAVA: setapptos(150): pid: 2111
7330 DEB 08:39:24.739042 JAVA: setapptos(): msgsnd(): rc: 0 size: 8 bytes
7331 NOT 08:39:24.739186 JAVA: HTTP JNI| setTos: call to mg_set_tos
7332 NOT 08:39:24.753022 SECUREAPP-setting security mode
7333 NOT 08:39:24.756741 SECUREAPP-set sec mode req done, clnt</tmp/secClnt_pid_2111_34587001>
7334 NOT 08:39:24.776168 CDP-cdpSetSwportCfgRemote 7 timer 30
7335 NOT 08:39:24.776347 CDP-cdpSetSwportCfgRemote setting : Type=0 Cfg=7 portval=7
7336 ERR 08:39:24.809756 JAVA: configmgr MQThread|cip.cfg.TimeDateProperty:? - Could not find
timezone: South America Standard/Daylight Time
7337 NOT 08:39:24.810182 JAVA: configmgr MQThread|cip.cfg.TimeDateProperty:? - setTimeZone
tz:Greenwich Standard Time ctz:GMT
7338 NOT 08:39:24.812294 JAVA: *** SetTimezone *** :TZ=GMT-00:00
7339 NOT 08:39:24.812909 JAVA: getenv TZ::GMT-00:00
7340 NOT 08:39:24.819036 JAVA: configmgr MQThread|cip.cfg.SipConfig: - Entering
setProtocolConfigProperties() at 1334133564818 millisecs....<RemoveItLater>
7341 DEB 08:39:24.826378 JAVA: configmgr MQThread|cip.cfg.SipConfig: - currentMwimask=[B@1c341c34
changeMask=[B@37083708
7342 INF 08:39:24.827205 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.config.sipprofile.local.mwistatus
7343 ERR 08:39:24.829975 JAVA: messages MQThread|cip.g3.userio.InputManager:? - lightLamp.. type =
```

```
8 value= 0 state= 1 color=0
7344 NOT 08:39:24.830562 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_setDigestNamePasswd: Name =35693
7345 NOT 08:39:24.882432 CDP-cprSetPortCfg port:0:1 ret:0
7346 NOT 08:39:24.883515 CDP-cdpSetSwportCfgRemote: Value Sent to IOCTL LOCAL[0] 1 1
7347 NOT 08:39:24.883966 NETSD-netsdSignal(): EV_LINK
7348 NOT 08:39:24.885508 PAE: -paeNetsdRcvMsg(2009): LINK change: status: 0x0 : No such file or
directory
7349 NOT 08:39:24.885608 EWCLIENT-event(1982): Ignoring unknown Event from netsd <0x100>
7350 NOT 08:39:24.885661 JAVA: *****HANDLE EVENT*****
7351 NOT 08:39:24.885729 JAVA: Calling handleNetSDEvent
7352 NOT 08:39:24.885772 JAVA: events: 0x100 from netsd
7353 NOT 08:39:24.885815 JAVA: handleEvent module=2 event=0x100-->
7354 DEB 08:39:24.885857 JAVA: getportcfg(): pid: 2111
7355 DEB 08:39:24.885899 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7356 NOT 08:39:24.886103 CDP-cdpSetPcportCfgRemote 7
7357 NOT 08:39:24.887782 CDP-cprSetPortCfg port:1:1 ret:0
7358 NOT 08:39:24.888053 CDP-cdpSetPcportCfgRemote Value Sent to IOCTL LOCAL[0] 1 1
7359 NOT 08:39:24.888338 NETSD-netsdSignal(): EV_LINK
7360 NOT 08:39:24.888705 EWCLIENT-event(1982): Ignoring unknown Event from netsd <0x100>
7361 DEB 08:39:24.889731 JAVA: getportcfg(): msgrcv(): 44 bytes
7362 DEB 08:39:24.889828 JAVA: --> GetPortConfig: port=3
7363 DEB 08:39:24.889875 JAVA: getportcfg(): pid: 2111
7364 DEB 08:39:24.889938 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7365 NOT 08:39:24.948028 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_setDigestNamePasswd: Name =35693
7366 NOT 08:39:24.992126 vleo-TCPIF PCPORT Link Change, but no status change
7367 NOT 08:39:25.066237 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_setDigestNamePasswd: Name =
7368 NOT 08:39:25.091671 JAVA: configmgr MQThread|cip.cfg.SipConfig: - Exiting
setProtocolConfigProperties() at 1334133565091 millisecs....<RemoveItLater>
7369 DEB 08:39:25.102615 JAVA: getportcfg(): msgrcv(): 44 bytes
7370 DEB 08:39:25.102789 JAVA: <-- GetPortConfig: 0
7371 DEB 08:39:25.102840 JAVA: --> GetPortConfig: port=2
7372 DEB 08:39:25.102885 JAVA: getportcfg(): pid: 2111
7373 DEB 08:39:25.102927 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7374 NOT 08:39:25.160985 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - CUCM in config file: #0
XmlCallAgentObject: IPv4-name=[10.102.112.3] IPv6-name=[] port=5060 priority=0
7375 NOT 08:39:25.162013 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - CUCM in config file: #1
XmlCallAgentObject: IPv4-name=[] IPv6-name=[] port=0 priority=32767
7376 NOT 08:39:25.162689 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - CUCM in config file: #2
XmlCallAgentObject: IPv4-name=[] IPv6-name=[] port=0 priority=32767
7377 NOT 08:39:25.163260 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - CUCM in config file: #3
XmlCallAgentObject: IPv4-name=[] IPv6-name=[] port=0 priority=32767
7378 NOT 08:39:25.163825 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - CUCM in config file: #4
XmlCallAgentObject: IPv4-name=[] IPv6-name=[] port=0 priority=32767
7379 DEB 08:39:25.164443 JAVA: configmgr MQThread|cip.sec.CapfProperty:? - CAPF IPv4 :CAPF IPv6
:CAPF Mode :0CAPF Port :3804
7380 NOT 08:39:25.211856 vleo-TCPIF PCPORT Link Change, but no status change
7381 ERR 08:39:25.215789 JAVA: configmgr MQThread|cip.sec.CapfProperty:? - getCapfInfo
ipv4Address=, ipv6Address=
7382 ERR 08:39:25.266547 JAVA: configmgr MQThread|cip.sec.CapfProperty:? - getCapfInfo
ipv4Address=, ipv6Address=
7383 ERR 08:39:25.321222 JAVA: configmgr MQThread|cip.sec.CapfProperty:? - getCapfInfo
ipv4Address=, ipv6Address=
7384 DEB 08:39:25.321370 JAVA: configmgr MQThread|cip.sec.CapfProperty:? - No update of the capf
info needed
7385 NOT 08:39:25.322352 PAE: -paeNetsdRcvMsg(2009): LINK change: status: 0x0 : No such file or
directory
7386 DEB 08:39:25.328427 JAVA: getportcfg(): msgrcv(): 44 bytes
7387 DEB 08:39:25.328564 JAVA: <-- GetPortConfig: 0
7388 DEB 08:39:25.328612 JAVA: --> GetPortConfig: port=11
7389 DEB 08:39:25.328655 JAVA: getportcfg(): pid: 2111
7390 DEB 08:39:25.328698 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7391 NOT 08:39:25.329767 SECUREAPP-SEC_CAPF_N_IN_USE: CAPF not in use, user cancel ignored
7392 ERR 08:39:25.378537 JAVA: configmgr MQThread|cip.sec.CapfProperty:? - Failed to resolve Capf
Ipv4 Address with hostname
7393 ERR 08:39:25.378682 JAVA: configmgr MQThread|cip.sec.CapfProperty:? - Failed to resolve Capf
Ipv6 Address with hostname
7394 DEB 08:39:25.378737 JAVA: configmgr MQThread|cip.sec.CapfProperty:? - CAPF IPv4 :CAPF IPv6
:CAPF Mode :0CAPF Port :3804
7395 ERR 08:39:25.378782 JAVA: configmgr MQThread|cip.sec.CapfProperty:? - No valid CAPF server
7396 NOT 08:39:25.379641 JAVA: System P5-traceManager MQThread|cip.110n.LocalizationManager$1: -
```

```
LocaleManager detect property changed: device.settings.config.localization.userlocale
7397 NOT 08:39:25.379752 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
userLocaleState = 3
7398 INF 08:39:25.379801 JAVA: System P5-traceManager MQThread|cip.l10n.UserLocaleProperty:? -
LocaleChanged: name= version=1.0.0.0-1
7399 INF 08:39:25.380596 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.config.localization.userlocale
7400 INF 08:39:25.380680 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
UserLocaleRdy=false networklocaleRdy=true cmchanged=false
7401 INF 08:39:25.381359 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.config.localization.userlocale
7402 INF 08:39:25.381448 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
UserLocaleRdy=false networklocaleRdy=true cmchanged=false
7403 NOT 08:39:25.383119 downd-Enter the case of DD_SET_TEMP_TFTP
7404 NOT 08:39:25.383229 downd-DDFORK - execing [/usr/sbin/dsetftp][-L200][ ]
7405 INF 08:39:25.384045 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.config.localization.networklocale
7406 INF 08:39:25.384195 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
UserLocaleRdy=false networklocaleRdy=false cmchanged=false
7407 NOT 08:39:25.385162 ms-FEATUREMGR.ms_enableFeature ms_enableFeature: [configNumber=4]
[enabled=0]
7408 NOT 08:39:25.385254 ms-FEATUREMGR.ftm_enableFeature ms_CONFIGTYPE_RINGOUTOFBAND unsupported
7409 INF 08:39:25.391520 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - processConfigNoError:
result=0
7410 INF 08:39:25.420229 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - processConfigNoError:
stored config to flash
7411 NOT 08:39:25.420602 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - Config
processConfigNoError() result code=CONFIG_FILE_NO_CHANGE
7412 NOT 08:39:25.422144 SECUREAPP-setting security mode
7413 NOT 08:39:25.423406 dsetftp-SETTFTP [5939] emcc_mode =0, override =1, tempTftp1= , tempTftp2
= , tempTftp3 = , tempTftp4 =
7414 NOT 08:39:25.433819 dsetftp-SETTFTP [5939] EMCC Config file doesn't exist
7415 NOT 08:39:25.435531 dsetftp-dsettempTftp.RESULT [Error description unknown]
7416 NOT 08:39:25.440157 SECUREAPP-set sec mode req done, clnt</tmp/secClnt_pid_2111_34587011>
7417 NOT 08:39:25.441601 downd-SOCKET accept errno=4 "Interrupted system call"
7418 DEB 08:39:25.444020 JAVA: getportcfg(): msgrcv(): 44 bytes
7419 DEB 08:39:25.444157 JAVA: <-- GetPortConfig: 8
7420 DEB 08:39:25.454072 JAVA: --> GetPortConfig: port=10
7421 DEB 08:39:25.454319 JAVA: getportcfg(): pid: 2111
7422 DEB 08:39:25.454667 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7423 INF 08:39:25.474622 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - committing CM_CHANGED
property, CM_CHANGED before=false
7424 INF 08:39:25.476079 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.config.callmanager.changed
7425 INF 08:39:25.476199 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
UserLocaleRdy=false networklocaleRdy=false cmchanged=true
7426 NOT 08:39:25.484477 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - --->ConfigManager
PropertyChanged: device.config.io.dscp.config
7427 NOT 08:39:25.484995 SECUREAPP-SEC_GET_EMCC: EMCC mode disabled
7428 NOT 08:39:25.485167 SECUREAPP-SEC_GET_EMCC: EMCC mode disabled
7429 DEB 08:39:25.485872 JAVA: setapptos(41): pid: 2111
7430 DEB 08:39:25.486321 JAVA: setapptos(): msgsnd(): rc: 0 size: 8 bytes
7431 NOT 08:39:25.486605 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - <---ConfigManager
PropertyChanged: device.config.io.dscp.config
7432 NOT 08:39:25.486956 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - --->ConfigManager
PropertyChanged: device.settings.network.swportstatus
7433 NOT 08:39:25.487188 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ConfigManager
PropertyChanged: device.settings.network.swportstatus
7434 NOT 08:39:25.487396 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ConfigManager
PropertyChanged: device.settings.network.swportstatus linkState=Link
7435 NOT 08:39:25.487579 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ConfigManager
PropertyChanged: device.settings.network.swportstatus calling linkState.isRPCInvalidConfiguration()
7436 INF 08:39:25.487850 JAVA: configmgr MQThread|cip.setg.PortConfigProperty:? -
PortConfigProperty.isRPCInvalidConfiguration(), SwRemoteConfig=0 swPortStatus=8
7437 NOT 08:39:25.488040 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - <---ConfigManager
PropertyChanged: device.settings.network.swportstatus
7438 INF 08:39:25.528338 JAVA: System P5-traceManager MQThread|cip.l10n.UserLocaleProperty:? -
getFile--(remoteFileName:/sp-sip.jar)
7439 NOT 08:39:25.529906 SECUREAPP-cert info, req done, clnt</tmp/secClnt_pid_2111_34587013>
7440 INF 08:39:25.531412 JAVA: tftp MQThread|cip.tftp.TftpService:? - .... tftpLargeFileRequest...
```

```
7441 NOT 08:39:25.533004 downd-DDFORK - execing [/usr/sbin/dgetfile][-L620][ ]
7442 NOT 08:39:25.533737 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
LocaleManager detect property changed: device.settings.config.localization.userlocale
7443 NOT 08:39:25.534066 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
userLocaleState = 4
7444 NOT 08:39:25.534403 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
LocaleManager detect property changed: device.settings.config.localization.networklocale
7445 NOT 08:39:25.534618 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
networkLocaleState = 3
7446 INF 08:39:25.534836 JAVA: System P5-traceManager MQThread|cip.l10n.NetworkLocaleProperty:? -
LocaleChanged: name= version=1.0.0.0-1
7447 INF 08:39:25.542345 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.config.localization.networklocale
7448 INF 08:39:25.542509 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
UserLocaleRdy=false networklocaleRdy=false cmchanged=true
7449 NOT 08:39:25.543888 downd-Enter the case of DD_SET_TEMP_TFTP
7450 NOT 08:39:25.543999 downd-DDFORK - execing [/usr/sbin/dsettempftp][-L200][ ]
7451 NOT 08:39:25.580392 dsettemp-SETTFTP [5945] emcc_mode =0, override =1, tempTftp1= , tempTftp2
= , tempTftp3 = , tempTftp4 =
7452 NOT 08:39:25.580820 dsettemp-SETTFTP [5945] EMCC Config file doesn't exist
7453 NOT 08:39:25.582287 dsettemp-dsettempTFTP.RESULT [Error description unknown]
7454 NOT 08:39:25.589958 dgetfile(5944)-GETXXTP [GT5944][src=/sp-sip.jar][dest=/tmp/ram/L10N-
886567200][serv=][serv6=][sec=2]
7455 NOT 08:39:25.590359 dgetfile(5944)-EMCC mode is false
7456 NOT 08:39:25.591500 downd-SOCKET accept errno=4 "Interrupted system call"
7457 NOT 08:39:25.591956 SECUREAPP-SEC_GET_EMCC: EMCC mode disabled
7458 NOT 08:39:25.592206 SECUREAPP-SEC_GET_EMCC: EMCC mode disabled
7459 NOT 08:39:25.602048 NETSD-netsdDhcp6Get(): que = /tmp/dhcp6_get_msg_que64
7460 NOT 08:39:25.604463 dgetfile(5944)-----Wired DHCP6 Info of DOWND -----
--
7461 NOT 08:39:25.604600 dgetfile(5944)-dhcp6Info state:0x6 status:0x0 autocfg:0x2 mbit:0
7462 NOT 08:39:25.604646 dgetfile(5944)-                ipv6:: prefixlen:0
7463 NOT 08:39:25.604689 dgetfile(5944)-                dns1::
7464 NOT 08:39:25.604728 dgetfile(5944)-                dns2::
7465 NOT 08:39:25.604767 dgetfile(5944)-                router1::
7466 NOT 08:39:25.604805 dgetfile(5944)-                router2::
7467 NOT 08:39:25.604844 dgetfile(5944)-                tftp1::
7468 NOT 08:39:25.604882 dgetfile(5944)-                tftp2::
7469 NOT 08:39:25.604921 dgetfile(5944)-                alt-tftp1::
7470 NOT 08:39:25.604959 dgetfile(5944)-                alt-tftp2::
7471 NOT 08:39:25.604998 dgetfile(5944)-                domain:
7472 NOT 08:39:25.605036 dgetfile(5944)-                tftpname:
7473 NOT 08:39:25.605074 dgetfile(5944)-                ipmode:1
7474 NOT 08:39:25.605112 dgetfile(5944)-----
7475 NOT 08:39:25.605151 dgetfile(5944)-parseDhcpInfoIntoTftpList(): no valid load server
7476 NOT 08:39:25.605190 dgetfile(5944)-Set tftpList from tftp_alt
7477 NOT 08:39:25.605228 dgetfile(5944)-tftpList[0] = 10.53.2.36
7478 NOT 08:39:25.605266 dgetfile(5944)-Set tftpList from Final
7479 NOT 08:39:25.605322 dgetfile(5944)-tftpList[0] = 10.53.2.36
7480 NOT 08:39:25.605363 dgetfile(5944)-AUTH.SRVR [GT5944] look up server - 0 - ::ffff:10.53.2.36
7481 INF 08:39:25.634001 JAVA: System P5-traceManager MQThread|cip.l10n.NetworkLocaleProperty:? -
getFile--(remoteFileName:/g3-tones.xml)
7482 NOT 08:39:25.634161 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
LocaleManager detect property changed: device.settings.config.localization.networklocale
7483 NOT 08:39:25.634216 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
networkLocaleState = 4
7484 INF 08:39:25.634651 JAVA: tftp MQThread|cip.tftp.TftpService:? - ... tftpLargeFileRequest...
7485 NOT 08:39:25.639067 SECUREAPP-cert info, req done, clnt</tmp/secClnt_pid_2111_34587015>
7486 NOT 08:39:25.658478 dgetfile(5944)-AUTH.SRVR [GT5944] authentication retval = 10
7487 NOT 08:39:25.658620 dgetfile(5944)-XXTP Secure file requested
7488 NOT 08:39:25.658716 dgetfile(5944)-XXTP Non secure file approved -- /sp-sip.jar
7489 NOT 08:39:25.658763 dgetfile(5944)-XXTP start request, server 1 - 10.53.2.36
7490 NOT 08:39:25.667187 GHTTP-LIMIT download will be limited to 8192 KB
7491 NOT 08:39:25.667568 GHTTP-fileServer 10.53.2.36
7492 NOT 08:39:25.712384 GHTTP-getaddrinfo ok family 2 socktype 1 protocol 6
7493 NOT 08:39:25.713605 GHTTP-connect6() failed
7494 NOT 08:39:25.714726 dgetfile(5944)-NO-HTTP with code 102 force=0
7495 DEB 08:39:25.715809 JAVA: getportcfg(): msgrcv(): 44 bytes
7496 DEB 08:39:25.715916 JAVA: <-- GetPortConfig: 9
7497 DEB 08:39:25.715964 JAVA: getportcfg(): pid: 2111
```

```
7498 DEB 08:39:25.716008 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7499 NOT 08:39:25.724719 TFTPd-pid = 5960
7500 NOT 08:39:25.738425 TFTPd-LIMIT download will be limited to 8192 KB
7501 NOT 08:39:25.832420 TFTPd-ai_family = 2, sockType = 2, protocol = 17
7502 NOT 08:39:25.832563 TFTPd-Requesting /sp-sip.jar from 10.53.2.36
7503 DEB 08:39:25.833724 JAVA: getportcfg(): msgrcv(): 44 bytes
7504 DEB 08:39:25.833828 JAVA: getportcfg(): pid: 2111
7505 DEB 08:39:25.833877 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7506 DEB 08:39:25.834430 JAVA: getportcfg(): msgrcv(): 44 bytes
7507 DEB 08:39:25.834506 JAVA: getassetid(): pid: 2111
7508 DEB 08:39:25.834554 JAVA: getassetid(): msgsnd() rc: 0, size: 44 bytes
7509 DEB 08:39:25.835095 JAVA: getassetid(): msgrcv() 44 bytes
7510 NOT 08:39:25.835175 JAVA: --> internalGetIPv4_Invalid: active-interface:0(Wired-LAN)
7511 NOT 08:39:25.835370 NETSD-netsdDhcp6Get(): que = /tmp/dhcp6_get_msg_que64
7512 NOT 08:39:25.837216 TFTPd-Error: (1+1)File not found
7513 NOT 08:39:25.842201 dgetfile(5944)-XXTP complete - status = 2
7514 NOT 08:39:25.842343 dgetfile(5944)-XXTP actualserver [10.53.2.36]
7515 NOT 08:39:25.842391 downd-DDFORK - execing [/usr/sbin/dgetfile][-L620][ ]
7516 NOT 08:39:25.842432 downd-Enter the case of DD_SET_TEMP_TFTP
7517 NOT 08:39:25.842471 downd-DDFORK - execing [/usr/sbin/dsetttftp][-L200][ ]
7518 DEB 08:39:25.881353 JAVA: getportcfg(): pid: 2111
7519 DEB 08:39:25.881507 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7520 DEB 08:39:25.882511 JAVA: getportcfg(): msgrcv(): 44 bytes
7521 NOT 08:39:25.882589 JAVA: internalGetIPv4_Invalid: CDP is BOUND or wlan connected.
7522 NOT 08:39:25.882639 JAVA: internalGetIPv4_Invalid: DHCP is BOUND INADDR_ANY:0,
dhcpInfo.my_ip_addr:0xd90d350a, ntohl(dhcpInfo.my_ip_addr):0xa350dd9
7523 NOT 08:39:25.882683 JAVA: internalGetIPv4_Invalid: DHCP is BOUND
7524 NOT 08:39:25.882726 JAVA: <-- internalGetIPv4_Invalid (1)
7525 NOT 08:39:25.882918 NETSD-netsdDhcp6Get(): que = /tmp/dhcp6_get_msg_que64
7526 DEB 08:39:25.886229 JAVA: -> internalGetIPv6_Invalid, active-interface:0
7527 DEB 08:39:25.886383 JAVA: internalGetIPv6_Invalid: ipmode:IPv4_ONLY(1), ip-auto-config:2,
dhcp6Info.state=0x6 (Enabled), dhcp6Info.status=0, dhcp6Info.managed_by=1(DHCPv6-Server)
7528 DEB 08:39:25.886434 JAVA: internalGetIPv6_Invalid: STATE_DHCP6S_IPV6_STACK_TURNED_OFF
7529 DEB 08:39:25.886500 JAVA: <- internalGetIPv6_Invalid, rc=199
7530 NOT 08:39:25.886551 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - --->ConfigManager
PropertyChanged: device.settings.network.ipstacksstate
7531 NOT 08:39:25.886599 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ConfigManager
IP_STACKS_STATE changed=1,199
7532 NOT 08:39:25.886643 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - IPv4 state=DHCP BOUND
7533 NOT 08:39:25.886686 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - IPv6 state=STACK
TURNED OFF
7534 ERR 08:39:25.886732 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ipv6Valid=false,
prevIpv6Dhcp=true,ipv6Dhcp=true
7535 ERR 08:39:25.886777 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? -
prevIpv6Valid=false,ipv6Valid=false, prevIpv6Dhcp=true,ipv6Dhcp=true
7536 ERR 08:39:25.886822 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ipv4Valid=true,
prevIpv4Dhcp=true,ipv4Dhcp=true
7537 ERR 08:39:25.886900 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? -
prevIpv4Valid=true,ipv4Valid=true, prevIpv4Dhcp=true,ipv4Dhcp=true
7538 NOT 08:39:25.886947 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - <---ConfigManager
PropertyChanged: device.settings.network.ipstacksstate
7539 INF 08:39:25.894661 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.network.ipstacksstate
7540 INF 08:39:25.894828 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
device.settings.network.ipstacksstate=1,199
7541 ERR 08:39:25.894886 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: - addrMode=0
mediaPrefer=0 hostIpAddr=10.53.13.217 hostIpv6Addr= hostMediaIp=10.53.13.217
7542 NOT 08:39:25.894957 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_IP_Update: New:
sig_ip=10.53.13.217,sig_ipv6=, media_ip=10.53.13.217 Current: sig_ip=10.53.13.217,sig_ipv6=
media_ip=10.53.13.217 signaling interface=SEP547C69D68B99, media_interface=SEP547C69D68B99,
vpn_enabled=0
7543 NOT 08:39:25.895006 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_IP_Update: No Signaling IP Changes
Detected
7544 NOT 08:39:25.895053 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_IP_Update: No Media IP Changes
Detected
7545 WRN 08:39:25.896772 JAVA: Thread-0|cip.sipcc.SipEnhancedAlarmInfo:propertyChanged -
name=device.settings.network.ipstacksstate value=1,199
7546 NOT 08:39:25.901516 JAVA: <-- handleEvent
7547 NOT 08:39:25.908776 JAVA: *****HANDLE EVENT*****
7548 NOT 08:39:25.909008 JAVA: Calling handleNetSDEvent
```



```

7549 NOT 08:39:25.909198 JAVA: events: 0x100 from netsd
7550 NOT 08:39:25.909325 JAVA: handleEvent module=2 event=0x100-->
7551 NOT 08:39:25.914123 dgetfile(5944)-DDGETTFTP.RESULT [_2_ File not found
]
7552 NOT 08:39:25.914753 downd-SOCKET accept errno=4 "Interrupted system call"
7553 DEB 08:39:25.915069 JAVA: getportcfg(): pid: 2111
7554 DEB 08:39:25.915345 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7555 DEB 08:39:25.929839 JAVA: getportcfg(): msgrcv(): 44 bytes
7556 DEB 08:39:25.929985 JAVA: --> GetPortConfig: port=3
7557 DEB 08:39:25.930035 JAVA: getportcfg(): pid: 2111
7558 DEB 08:39:25.930081 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7559 DEB 08:39:25.930802 JAVA: getportcfg(): msgrcv(): 44 bytes
7560 DEB 08:39:25.930888 JAVA: <-- GetPortConfig: 0
7561 DEB 08:39:25.930933 JAVA: --> GetPortConfig: port=2
7562 DEB 08:39:25.930974 JAVA: getportcfg(): pid: 2111
7563 DEB 08:39:25.931015 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7564 NOT 08:39:25.937233 dsettfoot-SETTFTP [5966] emcc_mode =0, override =0, tempTftp1= , tempTftp2
= , tempTftp3 = , tempTftp4 =
7565 NOT 08:39:25.938215 dgetfile(5965)-GETXXTP [GT5965][src=/g3-tones.xml][dest=/tmp/ram/L10N-
866527488][serv=][serv6=][sec=2]
7566 NOT 08:39:25.938526 dgetfile(5965)-EMCC mode is false
7567 NOT 08:39:25.938791 dsettfoot-SETTFTP [5966] EMCC Config file doesn't exist
7568 NOT 08:39:25.940582 dsettfoot-dsettemptftp.RESULT [Error description unknown]
7569 NOT 08:39:25.943176 downd-SOCKET accept errno=4 "Interrupted system call"
7570 NOT 08:39:25.943681 SECUREAPP-SEC_GET_EMCC: EMCC mode disabled
7571 NOT 08:39:25.948505 SECUREAPP-SEC_GET_EMCC: EMCC mode disabled
7572 DEB 08:39:25.954557 JAVA: getportcfg(): msgrcv(): 44 bytes
7573 DEB 08:39:25.954728 JAVA: <-- GetPortConfig: 0
7574 DEB 08:39:25.954780 JAVA: --> GetPortConfig: port=11
7575 DEB 08:39:25.954825 JAVA: getportcfg(): pid: 2111
7576 DEB 08:39:25.954869 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7577 NOT 08:39:25.958203 NETSD-netsdDhcp6Get(): que = /tmp/dhcp6_get_msg_que64
7578 NOT 08:39:25.958343 dgetfile(5965)-----Wired DHCP6 Info of DOWND -----
--
7579 NOT 08:39:25.958391 dgetfile(5965)-dhcp6Info state:0x6 status:0x0 autocfg:0x2 mbit:0
7580 NOT 08:39:25.958454 dgetfile(5965)- ipv6:: prefixlen:0
7581 NOT 08:39:25.958497 dgetfile(5965)- dns1::
7582 NOT 08:39:25.958537 dgetfile(5965)- dns2::
7583 NOT 08:39:25.958575 dgetfile(5965)- router1::
7584 NOT 08:39:25.958642 dgetfile(5965)- router2::
7585 NOT 08:39:25.958683 dgetfile(5965)- tftp1::
7586 NOT 08:39:25.958723 dgetfile(5965)- tftp2::
7587 NOT 08:39:25.958762 dgetfile(5965)- alt-tftp1::
7588 NOT 08:39:25.958802 dgetfile(5965)- alt-tftp2::
7589 NOT 08:39:25.958841 dgetfile(5965)- domain:
7590 NOT 08:39:25.958879 dgetfile(5965)- tftpname:
7591 NOT 08:39:25.958918 dgetfile(5965)- ipmode:1
7592 NOT 08:39:25.958957 dgetfile(5965)-----
7593 NOT 08:39:25.958997 dgetfile(5965)-parseDhcpInfoIntoTftpList(): no valid load server
7594 NOT 08:39:25.959036 dgetfile(5965)-Set tftplist from tftp_alt
7595 NOT 08:39:25.959076 dgetfile(5965)-tftplist[0] = 10.53.2.36
7596 NOT 08:39:25.959113 dgetfile(5965)-Set tftplist from Final
7597 NOT 08:39:25.959152 dgetfile(5965)-tftplist[0] = 10.53.2.36
7598 NOT 08:39:25.959191 dgetfile(5965)-AUTH.SRVR [GT5965] look up server - 0 - ::ffff:10.53.2.36
7599 WRN 08:39:25.991779 JAVA: System P5-traceManager MQThread|cip.l10n.UserLocaleProperty:? -
Unable to process LocaleProperty 'device.settings.config.localization.userlocale'
7600 INF 08:39:25.992655 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.config.localization.userlocale
7601 INF 08:39:25.992751 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
UserLocaleRdy=true networklocaleRdy=false cmchanged=true
7602 NOT 08:39:25.994573 JAVA: HTTP JNI| Java_cip_http_NativeHttpTask_updateUserLocaleCharSet:
setting Http Char Set to [Accept-Charset: utf-8,ASCII;q=0.8]
7603 NOT 08:39:25.995132 JAVA: HTTP JNI| Java_cip_http_NativeHttpTask_updateUserLocaleCharSet:
setting Http Char Set to [Accept-Charset: utf-8,ASCII;q=0.8]
7604 NOT 08:39:25.999844 JAVA: HTTP JNI| Java_cip_http_NativeHttpTask_updateUserLocaleLangCode:
setting Http Language Tag to [Accept-Language: en]
7605 NOT 08:39:26.000262 JAVA: HTTP JNI| Java_cip_http_NativeHttpTask_updateUserLocaleLangCode:
setting Http Language Tag to [Accept-Language: en]
7606 NOT 08:39:26.001216 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
LocaleManager detect property changed: device.settings.network.ipstacksstate

```

```
7607 NOT 08:39:26.001612 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1:? -
LocaleMgr, IP stack changed during updating. Have IP stack=true
7608 INF 08:39:26.002242 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.config.localization.userlocale
7609 INF 08:39:26.002331 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
UserLocaleRdy=true networklocaleRdy=false cmchanged=true
7610 NOT 08:39:26.002581 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
LocaleManager detect property changed: device.settings.config.localization.userlocale
7611 NOT 08:39:26.002779 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
userLocaleState = 2
7612 NOT 08:39:26.009995 dgetfile(5965)-AUTH.SRVR [GT5965] authentication retval = 10
7613 NOT 08:39:26.010143 dgetfile(5965)-XXTP Secure file requested
7614 NOT 08:39:26.010190 dgetfile(5965)-XXTP Non secure file approved -- /g3-tones.xml
7615 NOT 08:39:26.010232 dgetfile(5965)-XXTP start request, server 1 - 10.53.2.36
7616 NOT 08:39:26.019454 GHTTP-LIMIT download will be limited to 8192 KB
7617 NOT 08:39:26.020900 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
LocaleManager detect property changed: device.settings.config.localization.userlocale.charset
7618 NOT 08:39:26.021308 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
LocaleManager detect property changed: device.settings.config.localization.userlocale.charset
7619 NOT 08:39:26.021577 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
LocaleManager detect property changed: device.settings.config.localization.userlocale
7620 NOT 08:39:26.022192 SECUREAPP-cert info, req done, clnt</tmp/secClnt_pid_2111_34587017>
7621 NOT 08:39:26.022619 GHTTP-fileServer 10.53.2.36
7622 NOT 08:39:26.062544 GHTTP-getaddrinfo ok family 2 socktype 1 protocol 6
7623 NOT 08:39:26.063774 GHTTP-connect6() failed
7624 NOT 08:39:26.064893 dgetfile(5965)-NO-HTTP with code 102 force=0
7625 DEB 08:39:26.066887 JAVA: getportcfg(): msgrcv(): 44 bytes
7626 DEB 08:39:26.067029 JAVA: <-- GetPortConfig: 8
7627 NOT 08:39:26.080309 TFTPd-pid = 5985
7628 NOT 08:39:26.085785 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - --->ConfigManager
PropertyChanged: device.settings.network.swportstatus
7629 NOT 08:39:26.085933 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ConfigManager
PropertyChanged: device.settings.network.swportstatus
7630 NOT 08:39:26.085986 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ConfigManager
PropertyChanged: device.settings.network.swportstatus linkState=Link
7631 NOT 08:39:26.086037 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ConfigManager
PropertyChanged: device.settings.network.swportstatus calling linkState.isRPCInvalidConfiguration()
7632 INF 08:39:26.086084 JAVA: configmgr MQThread|cip.setg.PortConfigProperty:? -
PortConfigProperty.isRPCInvalidConfiguration(), SwRemoteConfig=0 swPortStatus=8
7633 NOT 08:39:26.086129 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - <---ConfigManager
PropertyChanged: device.settings.network.swportstatus
7634 DEB 08:39:26.086312 JAVA: --> GetPortConfig: port=10
7635 DEB 08:39:26.086471 JAVA: getportcfg(): pid: 2111
7636 DEB 08:39:26.086795 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7637 NOT 08:39:26.100949 TFTPd-LIMIT download will be limited to 8192 KB
7638 NOT 08:39:26.192389 TFTPd-ai_family = 2, sockType = 2, protocol = 17
7639 NOT 08:39:26.192536 TFTPd-Requesting /g3-tones.xml from 10.53.2.36
7640 DEB 08:39:26.193449 JAVA: getportcfg(): msgrcv(): 44 bytes
7641 DEB 08:39:26.193546 JAVA: <-- GetPortConfig: 9
7642 DEB 08:39:26.193596 JAVA: getportcfg(): pid: 2111
7643 DEB 08:39:26.193639 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7644 DEB 08:39:26.194211 JAVA: getportcfg(): msgrcv(): 44 bytes
7645 DEB 08:39:26.194286 JAVA: getportcfg(): pid: 2111
7646 DEB 08:39:26.194331 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7647 DEB 08:39:26.194855 JAVA: getportcfg(): msgrcv(): 44 bytes
7648 DEB 08:39:26.194923 JAVA: getassetid(): pid: 2111
7649 DEB 08:39:26.194968 JAVA: getassetid(): msgsnd() rc: 0, size: 44 bytes
7650 DEB 08:39:26.195425 JAVA: getassetid(): msgrcv() 44 bytes
7651 NOT 08:39:26.195718 JAVA: --> internalGetIPv4_Invalid: active-interface:0(Wired-LAN)
7652 NOT 08:39:26.197545 TFTPd-Error: (1+1)File not found
7653 NOT 08:39:26.197662 NETSD-netsdDhcp6Get(): que = /tmp/dhcp6_get_msg_que64
7654 NOT 08:39:26.201778 dgetfile(5965)-XXTP complete - status = 2
7655 NOT 08:39:26.201918 dgetfile(5965)-XXTP actualserver [10.53.2.36]
7656 NOT 08:39:26.201966 downd-Enter the case of DD_SET_TEMP_TFTP
7657 NOT 08:39:26.202006 downd-DDFORK - execing [/usr/sbin/dsetfttp][-L200][ ]
7658 DEB 08:39:26.231864 JAVA: getportcfg(): pid: 2111
7659 DEB 08:39:26.232011 JAVA: getportcfg(): msgsnd(): rc: 0 size: 44 bytes
7660 DEB 08:39:26.232598 JAVA: getportcfg(): msgrcv(): 44 bytes
7661 NOT 08:39:26.232677 JAVA: internalGetIPv4_Invalid: CDP is BOUND or wlan connected.
7662 NOT 08:39:26.232727 JAVA: internalGetIPv4_Invalid: DHCP is BOUND INADDR_ANY:0,
```

```
dhcpInfo.my_ip_addr:0xd90d350a, ntohl(dhcpInfo.my_ip_addr):0xa350dd9
7663 NOT 08:39:26.232772 JAVA: internalGetIPv4_Invalid: DHCP is BOUND
7664 NOT 08:39:26.232814 JAVA: <-- internalGetIPv4_Invalid (1)
7665 NOT 08:39:26.233002 NETSD-netsdDhcp6Get(): que = /tmp/dhcp6_get_msg_que64
7666 DEB 08:39:26.233621 JAVA: -> internalGetIPv6_Invalid, active-interface:0
7667 DEB 08:39:26.233714 JAVA: internalGetIPv6_Invalid: ipmode:IPv4_ONLY(1), ip-auto-config:2,
dhcp6Info.state=0x6 (Enabled), dhcp6Info.status=0, dhcp6Info.managed_by=1(DHCPv6-Server)
7668 DEB 08:39:26.233765 JAVA: internalGetIPv6_Invalid: STATE_DHCP6S_IPV6_STACK_TURNED_OFF
7669 DEB 08:39:26.233840 JAVA: <- internalGetIPv6_Invalid, rc=199
7670 NOT 08:39:26.236236 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - --->ConfigManager
PropertyChanged: device.settings.network.ipstacksstate
7671 NOT 08:39:26.236364 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ConfigManager
IP_STACKS_STATE changed=1,199
7672 NOT 08:39:26.236413 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - IPv4 state=DHCP BOUND
7673 NOT 08:39:26.236459 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - IPv6 state=STACK
TURNED OFF
7674 ERR 08:39:26.236505 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ipv6Valid=false,
prevIpv6Dhcp=true,ipv6Dhcp=true
7675 ERR 08:39:26.236551 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? -
prevIpv6Valid=false,ipv6Valid=false, prevIpv6Dhcp=true,ipv6Dhcp=true
7676 ERR 08:39:26.236594 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - ipv4Valid=true,
prevIpv4Dhcp=true,ipv4Dhcp=true
7677 ERR 08:39:26.236639 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? -
prevIpv4Valid=true,ipv4Valid=true, prevIpv4Dhcp=true,ipv4Dhcp=true
7678 NOT 08:39:26.236684 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - <---ConfigManager
PropertyChanged: device.settings.network.ipstacksstate
7679 INF 08:39:26.244101 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.network.ipstacksstate
7680 INF 08:39:26.244266 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
device.settings.network.ipstacksstate=1,199
7681 ERR 08:39:26.244319 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: - addrMode=0
mediaPrefer=0 hostIpAddr=10.53.13.217 hostIpv6Addr= hostMediaIp=10.53.13.217
7682 NOT 08:39:26.244373 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_IP_Update: New:
sig_ip=10.53.13.217,sig_ipv6=, media_ip=10.53.13.217 Current: sig_ip=10.53.13.217,sig_ipv6=
media_ip=10.53.13.217 signaling interface=SEP547C69D68B99, media_interface=SEP547C69D68B99,
vpn_enabled=0
7683 NOT 08:39:26.244419 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_IP_Update: No Signaling IP Changes
Detected
7684 NOT 08:39:26.244464 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_IP_Update: No Media IP Changes
Detected
7685 NOT 08:39:26.246732 dgetfile(5965)-DDGETTFTP.RESULT [_2_ File not found
]
7686 NOT 08:39:26.248097 downd-SOCKET accept errno=4 "Interrupted system call"
7687 WRN 08:39:26.248564 JAVA: Thread-0|cip.sipcc.SipEnhancedAlarmInfo:propertyChanged -
name=device.settings.network.ipstacksstate value=1,199
7688 NOT 08:39:26.248788 JAVA: <-- handleEvent
7689 NOT 08:39:26.256324 dsetftp-SETTFTP [5990] emcc_mode =0, override =0, tempTftp1= , tempTftp2
= , tempTftp3 = , tempTftp4 =
7690 NOT 08:39:26.256669 dsetftp-SETTFTP [5990] EMCC Config file doesn't exist
7691 NOT 08:39:26.258072 dsetftp-dsettempTftp.RESULT [Error description unknown]
7692 NOT 08:39:26.260205 downd-SOCKET accept errno=4 "Interrupted system call"
7693 NOT 08:39:26.260693 SECUREAPP-SEC_GET_EMCC: EMCC mode disabled
7694 NOT 08:39:26.260872 SECUREAPP-SEC_GET_EMCC: EMCC mode disabled
7695 WRN 08:39:26.309279 JAVA: System P5-traceManager MQThread|cip.l10n.NetworkLocaleProperty:? -
Unable to process LocaleProperty 'device.settings.config.localization.networklocale'
7696 INF 08:39:26.312820 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.config.localization.networklocale
7697 INF 08:39:26.312962 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
UserLocaleRdy=true networklocaleRdy=true cmchanged=true
7698 ERR 08:39:26.313017 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
InitCallControl
7699 NOT 08:39:26.313064 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener: -
cfgDlndDone(): mgmt_state=9
7700 NOT 08:39:26.313106 downd-DDFORK - execing [/usr/sbin/dgetfile][L620][ ]
7701 NOT 08:39:26.319094 ms-FEATUREMGR.ms_enableFeature ms_enableFeature: [configNumber=4]
[enabled=0]
7702 NOT 08:39:26.319220 ms-FEATUREMGR.ftm_enableFeature ms_CONFIGTYPE_RINGOUTOFBAND unsupported
7703 NOT 08:39:26.320910 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
LocaleManager detect property changed: device.settings.network.ipstacksstate
7704 NOT 08:39:26.321038 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
```

```
LocaleManager detect property changed: device.settings.config.localization.networklocale
7705 NOT 08:39:26.321090 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
networkLocaleState = 2
7706 NOT 08:39:26.324448 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener: -
skDnldDone():mgmtState=9nativeInit=false
7707 ERR 08:39:26.324579 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener: -
initSIPCC, nativeSideInitialized=false
7708 ERR 08:39:26.324633 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: - addrMode=0
mediaPrefer=0 hostIpAddr=10.53.13.217 hostIpv6Addr= hostMediaIp=10.53.13.217
7709 NOT 08:39:26.324687 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_IP_Update: New:
sig_ip=10.53.13.217,sig_ipv6=, media_ip=10.53.13.217 Current: sig_ip=10.53.13.217,sig_ipv6=
media_ip=10.53.13.217 signaling interface=SEP547C69D68B99, media_interface=SEP547C69D68B99,
vpn_enabled=0
7710 NOT 08:39:26.324733 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_IP_Update: No Signaling IP Changes
Detected
7711 NOT 08:39:26.324777 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_IP_Update: No Media IP Changes
Detected
7712 NOT 08:39:26.324819 JAVA: CCAPI_Service_start -
7713 NOT 08:39:26.339857 JAVA: SIPCC-SIP_DEVICE_MGR: registration_processEvent: Event EV_CC_START,
current State MGMT_STATE_WAITING_FOR_CONFIG_FILE
7714 WRN 08:39:26.340016 JAVA: Thread-4|cip.cfg.SipConfig:? - configFetchReq called...
7715 WRN 08:39:26.340069 JAVA: Thread-4|cip.cfg.SipConfig:? - setting config request
property...currently it is =false
7716 WRN 08:39:26.340118 JAVA: configmgr MQThread|cip.cfg.SipConfig:? - generateConfigFetchResponse
called...configFileAvailable=true configFileRequestPending=true
7717 WRN 08:39:26.340163 JAVA: configmgr MQThread|cip.cfg.SipConfig:? -
generateConfigFetchResponse: configFileFilename= /tmp/ram/SEP547C69D68B99.cnf.xml.59066
7718 NOT 08:39:26.340211 JAVA: SIPCC-CC_API: CCAPI_Config_response: from_memory:0, received new cfg
file sz:38, previous cfg file sz:38, current g_cfg_p buf sz:257
7719 NOT 08:39:26.340254 JAVA: SIPCC-CC_API: CCAPI_Config_response: Phone not registered. do parse
and register.
7720 ERR 08:39:26.340298 JAVA: CFG : config_set_value : natAddress size error entry size=48, len=4
7721 WRN 08:39:26.351731 JAVA: System P7-display
MQThread|cip.sipcc.SipEnhancedAlarmInfo:setLastDeregistrationReason - new
reason=LastTimePhoneRegRej current=24,24,24,24,24,24,
7722 WRN 08:39:26.359394 JAVA: System P7-display
MQThread|cip.sipcc.SipEnhancedAlarmInfo:getLastUnregistrationTimeReason -
TimeStamp=13341330116491334133018993,13341331940060,1334133207642,1334133361948,1334133381960,133413
3534252,1334133566340; Reasons =24,24,24,24,24,24,24
7723 NOT 08:39:26.362461 SECUREAPP-cert info, req done, clnt</tmp/secClnt_pid_2111_34587019>
7724 DEB 08:39:26.363130 JAVA: SIPCC-SIP_ALARM: storeAlarm: stored alarm at index [0].
7725 NOT 08:39:26.385735 dwnld-DDFORK - execing [/usr/sbin/dgetserver][L60][ ]
7726 NOT 08:39:26.440531 dgetfile(5998)-GETXXTP [GT5998][src=dialplan.xml]
[dest=/tmp/cache/DP1846762257][serv=][serv6=][sec=2]
7727 NOT 08:39:26.443302 dgetfile(5998)-EMCC mode is false
7728 NOT 08:39:26.450415 dgetserver(5999)-GETSRVR [GS5999][type:1][index:0] server request.
7729 NOT 08:39:26.486291 NETSD-netsdDhcp6Get(): que = /tmp/dhcp6_get_msg_que64
7730 NOT 08:39:26.488971 dgetfile(5998)-----Wired DHCP6 Info of DOWND -----
--
7731 NOT 08:39:26.489101 dgetfile(5998)-dhcp6Info state:0x6 status:0x0 autocfg:0x2 mbit:0
7732 NOT 08:39:26.489148 dgetfile(5998)- ipv6:: prefixlen:0
7733 NOT 08:39:26.489190 dgetfile(5998)- dns1::
7734 NOT 08:39:26.489229 dgetfile(5998)- dns2::
7735 NOT 08:39:26.489268 dgetfile(5998)- router1::
7736 NOT 08:39:26.489307 dgetfile(5998)- router2::
7737 NOT 08:39:26.489370 dgetfile(5998)- tftp1::
7738 NOT 08:39:26.489409 dgetfile(5998)- tftp2::
7739 NOT 08:39:26.489447 dgetfile(5998)- alt-tftp1::
7740 NOT 08:39:26.489485 dgetfile(5998)- alt-tftp2::
7741 NOT 08:39:26.489524 dgetfile(5998)- domain:
7742 NOT 08:39:26.489562 dgetfile(5998)- tftpname:
7743 NOT 08:39:26.489602 dgetfile(5998)- ipmode:1
7744 NOT 08:39:26.489641 dgetfile(5998)-----
7745 NOT 08:39:26.489682 dgetfile(5998)-parseDhcpInfoIntoTftpList(): no valid load server
7746 NOT 08:39:26.489721 dgetfile(5998)-Set tftpList from tftp_alt
7747 NOT 08:39:26.489759 dgetfile(5998)-tftpList[0] = 10.53.2.36
7748 NOT 08:39:26.489798 dgetfile(5998)-Set tftpList from Final
7749 NOT 08:39:26.489836 dgetfile(5998)-tftpList[0] = 10.53.2.36
7750 NOT 08:39:26.489875 dgetfile(5998)-AUTH.SRVR [GT5998] look up server - 0 - ::ffff:10.53.2.36
7751 NOT 08:39:26.491223 NETSD-netsdDhcp6Get(): que = /tmp/dhcp6_get_msg_que64
```

```

7752 NOT 08:39:26.491320 dgetserver(5999)-----Wired DHCP6 Info of DOWND -----
-----
7753 NOT 08:39:26.491365 dgetserver(5999)-dhcp6Info state:0x6 status:0x0 autocfg:0x2 mbit:0
7754 NOT 08:39:26.491406 dgetserver(5999)-          ipv6:: prefixlen:0
7755 NOT 08:39:26.491445 dgetserver(5999)-          dns1::
7756 NOT 08:39:26.491483 dgetserver(5999)-          dns2::
7757 NOT 08:39:26.491521 dgetserver(5999)-          router1::
7758 NOT 08:39:26.491559 dgetserver(5999)-          router2::
7759 NOT 08:39:26.491598 dgetserver(5999)-          tftp1::
7760 NOT 08:39:26.491670 dgetserver(5999)-          tftp2::
7761 NOT 08:39:26.491709 dgetserver(5999)-          alt-tftp1::
7762 NOT 08:39:26.491748 dgetserver(5999)-          alt-tftp2::
7763 NOT 08:39:26.491786 dgetserver(5999)-          domain:
7764 NOT 08:39:26.491824 dgetserver(5999)-          tftpname:
7765 NOT 08:39:26.491862 dgetserver(5999)-          ipmode:1
7766 NOT 08:39:26.491900 dgetserver(5999)-----
7767 NOT 08:39:26.491939 dgetserver(5999)-parseDhcpInfoIntoTftpList(): no valid load server
7768 NOT 08:39:26.491976 dgetserver(5999)-Set tftpList from tftp_alt
7769 NOT 08:39:26.492014 dgetserver(5999)-tftpList[0] = 10.53.2.36
7770 NOT 08:39:26.492051 dgetserver(5999)-GETSRVR [ip=10.53.2.36] resolved.
7771 NOT 08:39:26.496093 JAVA: ccm0=10.102.112.3 ccm1= ccm2= sip_port_0=5060 sip_port_1=5060
sip_port_2=5060 length=0
7772 NOT 08:39:26.496226 JAVA: ccm0=10.102.112.3 ccm1= ccm2= sec_sip_port_0=5061
sec_sip_port_1=5061 sec_sip_port_2=5061 length=0
7773 NOT 08:39:26.496275 JAVA: ccm0_v6= ccm1_v6= ccm2_v6= length=0
7774 NOT 08:39:26.496317 JAVA: ip_mode is IPv4
7775 DEB 08:39:26.496363 JAVA: Function dnsGetHostByName() is functional, but deprecated. Please
use sip_transport_getaddrinfo() instead.
7776 DEB 08:39:26.496407 JAVA: dnsGetHostByName: 10.102.112.3 is valid v4 addr 0xa667003.
7777 NOT 08:39:26.512073 JAVA: CFG : compare_or_set_multi_level_config_value : apply_config 0
7778 ERR 08:39:26.513079 JAVA: CFG : config_set_string : Parse function failed. ID: 102 myIPv6Addr:
7779 NOT 08:39:26.513269 JAVA: CFG : postConfigParse : Set CFG: dev_name:SEP547C69D68B99
signaling_ip:10.53.13.217 signaling_ipv6: media_ip:10.53.13.217
7780 NOT 08:39:26.513414 JAVA: CFG : postConfigParse : old CFG: timer_register_expires:3600,
timer_invite_expires:180, timer_t1:500, voip_control_port:5060
7781 NOT 08:39:26.513538 JAVA: CFG : postConfigParse : Set CFG: dev_name:SEP547C69D68B99
signaling_ip:10.53.13.217 media_ip:10.53.13.217
7782 NOT 08:39:26.540693 dgetfile(5998)-AUTH.SRVR [GT5998] authentication retval = 10
7783 NOT 08:39:26.540847 dgetfile(5998)-XXTP Secure file requested
7784 NOT 08:39:26.540921 dgetfile(5998)-XXTP Non secure file approved -- dialplan.xml
7785 NOT 08:39:26.540965 dgetfile(5998)-XXTP start request, server 1 - 10.53.2.36
7786 NOT 08:39:26.555483 GHTTP-LIMIT download will be limited to 2048 KB
7787 NOT 08:39:26.561864 GHTTP-fileServer 10.53.2.36
7788 NOT 08:39:26.562415 GHTTP-getaddrinfo ok family 2 socktype 1 protocol 6
7789 NOT 08:39:26.563992 GHTTP-connect6() failed
7790 NOT 08:39:26.572408 dgetfile(5998)-NO-HTTP with code 102 force=0
7791 NOT 08:39:26.580985 TFTPDPid = 6020
7792 NOT 08:39:26.592495 dgetserver(5999)-dgetserver.RESULT [_0_ [PASS] No error
]
7793 NOT 08:39:26.594857 downd-SOCKET accept errno=4 "Interrupted system call"
7794 NOT 08:39:26.617809 JAVA: SIPCC-CC_API: 0x0, CCAPI_Device_setDigestNamePasswd: Name =35693
7795 NOT 08:39:26.622077 TFTPDP-LIMIT download will be limited to 2048 KB
7796 NOT 08:39:26.622216 TFTPDP-ai_family = 2, sockType = 2, protocol = 17
7797 NOT 08:39:26.622267 TFTPDP-Requesting dialplan.xml from 10.53.2.36
7798 NOT 08:39:26.632608 TFTPDP-Finished: rcvd 2103 bytes
7799 NOT 08:39:26.636418 dgetfile(5998)-XXTP complete - status = 0
7800 NOT 08:39:26.636535 dgetfile(5998)-XXTP actualserver [10.53.2.36]
7801 NOT 08:39:26.673327 dgetfile(5998)-DDGETTFTP.RESULT [_0_ [PASS] No error
]
7802 NOT 08:39:26.674770 downd-SOCKET accept errno=4 "Interrupted system call"
7803 INF 08:39:26.839329 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.config.callmanager.changed
7804 INF 08:39:26.841422 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
UserLocaleRdy=true networklocaleRdy=true cmchanged=false
7805 INF 08:39:26.842342 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
propertyChanged(): device.settings.config.localization.networklocale
7806 INF 08:39:26.842445 JAVA: System P7-display MQThread|cip.sipcc.SipCcAdapter: -
UserLocaleRdy=true networklocaleRdy=true cmchanged=false
7807 NOT 08:39:26.851800 JAVA: System P5-traceManager MQThread|cip.l10n.LocalizationManager$1: -
LocaleManager detect property changed: device.settings.config.localization.networklocale

```

7808 NOT 08:39:26.859955 JAVA: SIPCC-SIP_CC_PROV: ccappFeatureUpdated: CCAPP -> GSM: Updating capability set (and generating line event) for line index=[1].

7809 NOT 08:39:26.860093 JAVA: SIPCC-SIP_CC_PROV: ccappFeatureUpdated: CCAPP -> GSM: Updating capability set (and generating line event) for line index=[2].

7810 DEB 08:39:26.860382 JAVA: Function dnsGetHostByName() is functional, but deprecated. Please use sip_transport_getaddrinfo() instead.

7811 DEB 08:39:26.860539 JAVA: dnsGetHostByName: 10.102.112.3 is valid v4 addr 0xa667003.

7812 DEB 08:39:26.860696 JAVA: Function dnsGetHostByName() is functional, but deprecated. Please use sip_transport_getaddrinfo() instead.

7813 DEB 08:39:26.860819 JAVA: dnsGetHostByName: 10.53.2.36 is valid v4 addr 0xa350224.

7814 ERR 08:39:26.861091 JAVA: ccsnap_line_init invalid value 9 for button i=1

7815 ERR 08:39:26.861388 JAVA: ccsnap_line_init invalid value 9 for button i=2

7816 ERR 08:39:26.861524 JAVA: ccsnap_line_init invalid value 0 for button i=3

7817 ERR 08:39:26.861649 JAVA: ccsnap_line_init invalid value 0 for button i=4

7818 ERR 08:39:26.861773 JAVA: ccsnap_line_init invalid value 0 for button i=5

7819 ERR 08:39:26.861896 JAVA: ccsnap_line_init invalid value 0 for button i=6

7820 ERR 08:39:26.862016 JAVA: ccsnap_line_init invalid value 0 for button i=7

7821 ERR 08:39:26.862137 JAVA: ccsnap_line_init invalid value 0 for button i=8

7822 ERR 08:39:26.862257 JAVA: ccsnap_line_init invalid value 0 for button i=9

7823 ERR 08:39:26.862378 JAVA: ccsnap_line_init invalid value 0 for button i=10

7824 ERR 08:39:26.862500 JAVA: ccsnap_line_init invalid value 0 for button i=11

7825 ERR 08:39:26.862623 JAVA: ccsnap_line_init invalid value 0 for button i=12

7826 ERR 08:39:26.862757 JAVA: ccsnap_line_init invalid value 0 for button i=13

7827 ERR 08:39:26.862882 JAVA: ccsnap_line_init invalid value 0 for button i=14

7828 ERR 08:39:26.863005 JAVA: ccsnap_line_init invalid value 0 for button i=15

7829 ERR 08:39:26.863128 JAVA: ccsnap_line_init invalid value 0 for button i=16

7830 ERR 08:39:26.863249 JAVA: ccsnap_line_init invalid value 0 for button i=17

7831 ERR 08:39:26.863411 JAVA: ccsnap_line_init invalid value 0 for button i=18

7832 ERR 08:39:26.863535 JAVA: ccsnap_line_init invalid value 0 for button i=19

7833 ERR 08:39:26.863656 JAVA: ccsnap_line_init invalid value 0 for button i=20

7834 ERR 08:39:26.863777 JAVA: ccsnap_line_init invalid value 0 for button i=21

7835 ERR 08:39:26.863898 JAVA: ccsnap_line_init invalid value 0 for button i=22

7836 NOT 08:39:26.864056 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type : CONFIG_CHANGED

7837 WRN 08:39:26.864530 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter\$CcMgmtListener:? - ccReady called...mgmtState=9

7838 NOT 08:39:26.865391 JAVA: configmgr MQThread - Deletion of file Successful/tmp/ram/SEP547C69D68B99.cnf.xml.59066

7839 NOT 08:39:26.865724 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter\$CcMgmtListener:? - ConfigFile name=ram/SEP547C69D68B99.cnf.xml.59066 DELETE ConfigFile WAS SUCCESSFUL

7840 NOT 08:39:26.865986 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter\$CcMgmtListener:? - ccReady: oldccMode=-1 newccMode=0

7841 WRN 08:39:26.866751 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter\$CcMgmtListener:? - initializeLinePlane called...

7842 INF 08:39:26.874746 JAVA: System P8-sessmgr MQThread|DisplayTask:? - device.callagent.callcount changed

7843 DEB 08:39:26.874907 JAVA: System P8-sessmgr MQThread - ----- detecting property change for device.callagent.callcount

7844 DEB 08:39:26.874959 JAVA: System P8-sessmgr MQThread - DisplayTask-----propertyChanged----- PowerOffTime=24:00

7845 DEB 08:39:26.875005 JAVA: System P8-sessmgr MQThread - DisplayTask-----propertyChanged----- PowerOnTime=00:00

7846 DEB 08:39:26.875050 JAVA: System P8-sessmgr MQThread|DisplayTask:? - isUriTimerSet=false

7847 DEB 08:39:26.875093 JAVA: System P8-sessmgr MQThread|DisplayTask:? - isWithinActiveTime=false

7848 DEB 08:39:26.875136 JAVA: System P8-sessmgr MQThread|DisplayTask:? - Active Call Count: 0

7849 DEB 08:39:26.875179 JAVA: System P8-sessmgr MQThread|DisplayTask:? - isDisplayOn=true

7850 DEB 08:39:26.875223 JAVA: System P8-sessmgr MQThread|DisplayTask:? - isFullyRegistered=false

7851 DEB 08:39:26.875266 JAVA: System P8-sessmgr MQThread|DisplayTask:? - isFullyRegistered=false

7852 INF 08:39:26.875310 JAVA: System P8-sessmgr MQThread|DisplayTask:? - device.callagent.callcount changed

7853 DEB 08:39:26.875355 JAVA: System P8-sessmgr MQThread - ----- detecting property change for device.callagent.callcount

7854 DEB 08:39:26.875412 JAVA: System P8-sessmgr MQThread - DisplayTask-----propertyChanged----- PowerOffTime=24:00

7855 DEB 08:39:26.875461 JAVA: System P8-sessmgr MQThread - DisplayTask-----propertyChanged----- PowerOnTime=00:00

7856 DEB 08:39:26.875506 JAVA: System P8-sessmgr MQThread|DisplayTask:? - isUriTimerSet=false

7857 DEB 08:39:26.875549 JAVA: System P8-sessmgr MQThread|DisplayTask:? - isWithinActiveTime=false

7858 INF 08:39:26.884477 JAVA: System P7-display MQThread|OverviewModel:? - selectFeatureSet----- ---featureSet=[Lcip.app.ApplicationFeature;@15c815c8

```
7859 DEB 08:39:26.884763 JAVA: System P8-sessmgr MQThread|DisplayTask:? - Active Call Count: 0
7860 DEB 08:39:26.884852 JAVA: System P8-sessmgr MQThread|DisplayTask:? - isDisplayOn=true
7861 DEB 08:39:26.884934 JAVA: System P8-sessmgr MQThread|DisplayTask:? - isFullyRegistered=false
7862 DEB 08:39:26.885039 JAVA: System P8-sessmgr MQThread|DisplayTask:? - isFullyRegistered=false
7863 INF 08:39:26.885118 JAVA: System P7-display MQThread|cip.callui.market.OverviewModel:? -
OverviewModel unregistered TRUE
7864 NOT 08:39:26.885423 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener: -
initializeLinePlane(): Mgmt Interface is in Service now..
7865 WRN 08:39:26.886167 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener:? - calling
initializelines...
7866 WRN 08:39:26.886536 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener:? -
initializelines called...
7867 WRN 08:39:26.886958 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener:? -
returned from InfogetLines...
7868 WRN 08:39:26.893691 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener:? -
entering line loop...
7869 WRN 08:39:26.894146 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener:? -
instidx=0 inst=1 calling getLineInfo....
7870 WRN 08:39:26.894832 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener:? -
instidx=1 inst=2 calling getLineInfo....
7871 WRN 08:39:26.895337 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener:? -
returned from InfogetFeatures...
7872 WRN 08:39:26.895539 JAVA: configmgr MQThread|cip.sipcc.SipCcAdapter$CcMgmtListener:? -
features is empty...
7873 NOT 08:39:26.896867 JAVA: SIPCC-SIP_DEVICE_MGR: registration_processEvent: Event
EV_CC_CONFIG_RECEIVED, current State MGMT_STATE_WAITING_FOR_CONFIG_FILE
7874 NOT 08:39:26.896971 JAVA: SIPCC-SIP_DEVICE_MGR: setState: new registration state =
MGMT_STATE_REGISTERING
7875 DEB 08:39:26.897020 JAVA: SIPCC-SIP_TRANS: sip_get_local_ip_addr: dst_addr: 8.8.8.8
7876 DEB 08:39:26.897066 JAVA: SIPCC-SIP_TRANS: sip_get_local_ip_addr: src_addr: 10.53.13.217
7877 NOT 08:39:26.897109 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type : STATE
7878 NOT 08:39:26.897152 JAVA: SNAPSHOT-failed: CCAPI_DeviceInfo_getServiceState: reference
pointer=42404870
7879 NOT 08:39:26.897199 JAVA: SIPCC-SIP_DEVICE_MGR: action: cmd: CMD_RESTART cfg: signaling_ip=
[v4:10.53.13.217,v6:] media_ip=10.53.13.217 pending: signaling_ip=[v4:10.53.13.217,v6:]
media_ip=10.53.13.217
7880 NOT 08:39:26.897242 JAVA: SIPCC-SIP_DEVICE_MGR: action: Setting New Signaling IP
[v4:10.53.13.217,v6:], New Media IP 10.53.13.217
7881 ERR 08:39:26.897286 JAVA: CFG : config_set_string : Parse function failed. ID: 102 myIPv6Addr:
7882 NOT 08:39:26.909305 JAVA: SIPCC-SIP_CTRL: sip_restart: In sip_restart
7883 DEB 08:39:26.909457 JAVA: SIPCC-SIP_CONTACT: init_bulk_reg_info: Called
7884 DEB 08:39:26.909509 JAVA: SIPCC-SIP_REG_BULK: ccsip_set_bulk_reg_status: Transitioning bulk
reg status from BULK_REG_DISABLED to BULK_REG_NONE
7885 DEB 08:39:26.909558 JAVA: SIPCC-SIP_REG: ccsip_set_last_line_button_configured: last line
configured value 0 passed in.Assigning the default: 22
7886 DEB 08:39:26.909604 JAVA: SIPCC-SIP_REG: ccsip_set_last_line_button_present: Updating last
line present from 22 to 22
7887 DEB 08:39:26.909647 JAVA: Button to Line Index Mapping
7888 DEB 08:39:26.909690 JAVA: -----
7889 DEB 08:39:26.909733 JAVA: SIPCC-SIP_BUTTON: button_to_index_map_init: Button : 1 -> LineIndex
: 1
7890 DEB 08:39:26.909777 JAVA: SIPCC-SIP_BUTTON: button_to_index_map_init: Button : 2 -> LineIndex
: 2
7891 DEB 08:39:26.909822 JAVA: SIPCC-SIP_REG: ccsip_set_last_line_button_configured: Updating last
line configured from 22 to 2
7892 DEB 08:39:26.909867 JAVA: SIPCC-SIP_BUTTON: button_to_index_map_init: last line button
configured : 2
7893 DEB 08:39:26.909912 JAVA: SIPCC-SIP_REG: ccsip_set_reg_refresh: Registration Refresh is set to
FALSE
7894 DEB 08:39:26.909956 JAVA: SIPCC-SIP_REG_BULK: init_bulk_reg_info: Bulk reg conditions not
met.Disabling Bulk Reg
7895 DEB 08:39:26.910001 JAVA: SIPCC-SIP_REG_BULK: ccsip_set_bulk_reg_status: Transitioning bulk
reg status from BULK_REG_NONE to BULK_REG_DISABLED
7896 DEB 08:39:26.910045 JAVA: SIPCC-SIP_TRANS: sipTransportCfgTableInit: Transport Interface init
7897 ERR 08:39:26.910089 JAVA: SIP : sip_transport_init_ti_addrs : Admin has not configured a valid
cucm for cucm index=VISITING_CCM=0.
7898 DEB 08:39:26.910136 JAVA: SIPCC-SIP_TRANS: sipTransportCfgTableInit: For VISITING_CCM: IPv4
Addr: Port: 0 listen Port: 0 IPv6 Addr: Port: 0 listen Port: 0 transport: 2 Sec Level: 0 IP type:
0
7899 DEB 08:39:26.910181 JAVA: SIPCC-SIP_TRANS: sip_get_local_ip_addr: dst_addr: 8.8.8.8
```

7900 DEB 08:39:26.910224 JAVA: SIPCC-SIP_TRANS: sip_get_local_ip_addr: src_addr: 10.53.13.217
7901 DEB 08:39:26.910268 JAVA: SIPCC-SIP_TRANS: sip_transport_getaddrinfo: 10.102.112.3 is already
an IPv4 address
7902 ERR 08:39:26.910312 JAVA: SIPCC-SIP_TRANS: sip_transport_init_ti_addr: CCM unprovisioned
7903 DEB 08:39:26.910397 JAVA: SIPCC-SIP_TRANS: sipTransportCfgTableInit: For PRIMARY_CCM: IPv4
Addr: 10.102.112.3 Port: 5060 listen Port: 5060 IPv6 Addr: Port: 5060 listen Port: 5060 transport:
2 Sec Level: 0 IP type: 1
7904 ERR 08:39:26.910445 JAVA: SIP : sip_transport_init_ti_addrs : Admin has not configured a valid
cucm for cucm index=SECONDARY_CCM=2.
7905 DEB 08:39:26.910493 JAVA: SIPCC-SIP_TRANS: sipTransportCfgTableInit: For SECONDARY_CCM: IPv4
Addr: Port: 0 listen Port: 0 IPv6 Addr: Port: 0 listen Port: 0 transport: 2 Sec Level: 0 IP type:
0
7906 ERR 08:39:26.910539 JAVA: SIP : sip_transport_init_ti_addrs : Admin has not configured a valid
cucm for cucm index=TERTIARY_CCM=3.
7907 DEB 08:39:26.910586 JAVA: SIPCC-SIP_TRANS: sipTransportCfgTableInit: For TERTIARY_CCM: IPv4
Addr: Port: 0 listen Port: 0 IPv6 Addr: Port: 0 listen Port: 0 transport: 2 Sec Level: 0 IP type:
0
7908 ERR 08:39:26.910648 JAVA: SIP : sip_transport_init_ti_addrs : Admin has not configured a valid
cucm for cucm index=SRST_CCM=4.
7909 DEB 08:39:26.910691 JAVA: SRST is configured Unsecure on port 0

7910 DEB 08:39:26.910735 JAVA: SRST security level 0
 connection type 2
 port 5060

7911 DEB 08:39:26.910782 JAVA: SIPCC-SIP_TRANS: sipTransportCfgTableInit: For SRST_CCM: IPv4 Addr:
Port: 5060 listen Port: 0 IPv6 Addr: Port: 0 listen Port: 0 transport: 2 Sec Level: 0 IP type: 0
7912 DEB 08:39:26.910827 JAVA: SIPCC-SIP_TRANS: sipTransportResetUDPChannel: resetting UDP channel
7913 DEB 08:39:26.910872 JAVA: SIPCC-SIP SOCK: sip_platform_udp_channel_create: UDP channel created
7914 DEB 08:39:26.910918 JAVA: SIPCC-SIP_ALARM: update_unregister_alarm_info:
Info_type=CC_UNREG_ALARM_PORT_INFO ccm_id=PRIMARY_CCM phone_tcp_port=0 sip_info_msg=
7915 NOT 08:39:26.910960 JAVA: set_active_ccm: ccm=PRIMARY_CCM port=0
7916 NOT 08:39:26.911004 JAVA: SIPCC-SIP_CC_CONN: sip_transport_setup_cc_conn: <SECONDARY_CCM>: CC
address/port not configured.
7917 NOT 08:39:26.911049 JAVA: SIPCC-SIP_CC_CONN: sip_transport_setup_cc_conn: <TERTIARY_CCM>: CC
address/port not configured.
7918 NOT 08:39:26.911093 JAVA: SIPCC-SIP_CC_CONN: sip_transport_setup_cc_conn: <SRST_CCM>: CC
address/port not configured.
7919 ERR 08:39:26.944727 JAVA: SIPCC-SIP_CC_CONN: sip_regmgr_setup_cc_conns: NO VALID STANDBY CALL
CONTROL AVAILABLE!
7920 DEB 08:39:26.944795 JAVA: SIPCC-SIP_FALLBACK: sip_regmgr_trigger_fallback_monitor: Looking to
trigger fallback if any available
7921 NOT 08:39:26.944844 JAVA: SIPCC-SIP_REG: sip_sm_init: Disabling mass reg state
7922 DEB 08:39:26.945015 JAVA: SIPCC-SIP_STATE: 119/1, sip_reg_sm_change_state: Registration state
change: SIP_REG_STATE_IDLE ---> SIP_REG_STATE_IDLE
7923 DEB 08:39:26.945085 JAVA: SIPCC-SIP_REG: ccsip_register_cancel:
7924 DEB 08:39:26.945134 JAVA: SIPCC-SIP_ALARM: sendStoredSIPAlarm: sent stored alarm[0]
request_id=9 alarm_ptr=0x4242c610
7925 DEB 08:39:26.945179 JAVA: SIPCC-SIP_REG: ccsip_register_all_lines:
7926 DEB 08:39:26.945222 JAVA: SIPCC-SIP_REG: ccsip_register_all_lines: registering 22 lines
7927 DEB 08:39:26.945268 JAVA: SIPCC-SIP_STATE: 119/1, sip_reg_sm_change_state: Registration state
change: SIP_REG_STATE_UNKNOWN ---> SIP_REG_STATE_IDLE
7928 DEB 08:39:26.945313 JAVA: SIPCC-SIP_REG: ccsip_register_all_lines: ERROR: Standby ccm entry is
NULL
7929 NOT 08:39:26.945355 JAVA: SIPCC-SIP_REG: ccsip_register_all_lines: Disabling mass reg state
7930 DEB 08:39:26.945399 JAVA: SIPCC-SIP_REG: 97/1, ccsip_register_all_lines: 97, 0x41d46cec
7931 DEB 08:39:26.945444 JAVA: SIPCC-SIP_STATE: 97/1, sip_reg_sm_change_state: Registration state
change: SIP_REG_STATE_UNKNOWN ---> SIP_REG_STATE_IDLE
7932 DEB 08:39:26.945488 JAVA: SIPCC-SIP_MSG_SEND: ccsip_register_send_msg: cmd=85=SIP_REG_REQ
ndx=97
7933 DEB 08:39:26.945531 JAVA: SIPCC-SIP_REG: 98/2, ccsip_register_all_lines: 98, 0x41d47698
7934 DEB 08:39:26.945574 JAVA: SIPCC-SIP_MSG_SEND: ccsip_register_send_msg: cmd=85=SIP_REG_REQ
ndx=98
7935 NOT 08:39:26.945618 JAVA: SIPCC-SIP_CTRL: sip_restart: sip.taskInited is set to true
7936 NOT 08:39:26.945691 JAVA: SIPCC-CC_API: 0/0, cc_int_fail_fallback: SIP -> GSM:
FAILOVER_FALLBACK
7937 DEB 08:39:26.945738 JAVA: SIPCC-SIP_SUB: sipSPIAddRouteHeadersToSubNot: Route info not
available; will not add Route header.
7938 DEB 08:39:26.945783 JAVA: SIPCC-SIP_SUB: xmlEncodeEventData: Encode event data: entered,
7939 DEB 08:39:26.945842 JAVA: SIPCC-SIP_SUB: xmlEncodeEventData: Framed raw buffer: length = 1182,


```

7940 DEB 08:39:26.945886 JAVA: SIP : sipTransportCreateSendMessage : sippmh_write() with message
size=[1933]
7941 NOT 08:39:26.945933 JAVA: SIPCC-SIP_MSG_SEND: ccsip_dump_send_msg_info:
<10.102.112.3:5060>:REFER s: <sip:10.102.112.3> :1000 REFER::547c69d6-8b990009-7aa4f43f-
3ffa8cd8@10.53.13.217
7942 DEB 08:39:26.945977 JAVA: SIPCC-SIP_TRANS: sipTransportSendMessage: bypassing ccm check
7943 DEB 08:39:26.946022 JAVA: SIPCC-SIP_TRANS: sipTransportSendMessage: Sip msg sent handle=
<48>,length=<1933>, message=
7944 DEB 08:39:26.946064 JAVA:
7945 DEB 08:39:26.946141 JAVA: sipio-sent---> REFER sip:10.102.112.3 SIP/2.0^M
Via: SIP/2.0/UDP 10.53.13.217:5060;branch=z9hG4bK210fb7c6^M
From: <sip:547c69d68b99@10.53.13.217>;tag=547c69d68b990017477364a9-365e5a32^M
To: <sip:10.102.112.3>^M
Call-ID: 547c69d6-8b990009-7aa4f43f-3ffa8cd8@10.53.13.217^M
Date: Wed, 11 Apr 2012 08:39:26 GMT^M
CSeq: 1000 REFER^M
User-Agent: Cisco-CP7821/10.1.1^M
Expires: 10^M
Max-Forwards: 70^M
Contact: <sip:547c69d68b99@10.53.13.217:5060>^M
Require: norefersub^M
Referred-By: <sip:547c69d68b99@10.53.13.217>^M
Refer-To: cid:6daea6cb@10.53.13.217^M
Content-Id: <6daea6cb@10.53.13.217>^M
Allow: ACK,BYE,CANCEL,INVITE,NOTIFY,OPTIONS,REFER,REGISTER,UPDATE,SUBSCRIBE^M
Content-Length: 1181^M
Content-Type: application/x-cisco-alarm+xml^M
Content-Disposition: session;handling=required^M
^M
<?xml version="1.0" encoding="UTF-8"?>
<x-cisco-alarm>
<Alarm Name="LastOutOfServiceInformation">
<ParameterList>
<String name="DeviceName">SEP547C69D68B99</String>
<String name="DeviceIPv4Address">10.53.13.217/22</String>
<String name="IPv4DefaultGateway">
7946 DEB 08:39:26.946233 JAVA: 10.53.12.1</String>
<String name="DeviceIPv6Address"></String>
<String name="IPv6DefaultGateway"></String>
<String name="ModelNumber">CP-7821</String>
<String name="NeighborIPv4Address">0.0.0.0</String>
<String name="NeighborIPv6Address"></String>
<String name="NeighborDeviceID"></String>
<String name="NeighborPortID"></String>
<Enum name="DHCPv4Status">1</Enum>
<Enum name="DHCPv6Status">0</Enum>
<Enum name="TFTPCfgStatus">1</Enum>
<Enum name="DNSStatusUnifiedCM1">4</Enum>
<Enum name="DNSStatusUnifiedCM2">0</Enum>
<Enum name="DNSStatusUnifiedCM3">0</Enum>
<String name="VoiceVLAN">10</String>
<String name="UnifiedCMIPAddress"></String>
<String name="LocalPort"></String>
<String name="TimeStamp">13341330116491334133018993</String>
<Enum name="ReasonForOutOfService">24</Enum>
<String name="LastProtocolEventSent"></String>
<String name="LastProtocolEventReceived"></String>
</ParameterList>
</Alarm>
</x-cisco-alarm>
7947 DEB 08:39:26.946288 JAVA: SIPCC-SIP_MSG_SEND: ccsip_store_send_msg_for_alarm: Sent:REFER
sip:10.102.112.3 SIP/2.0 Cseq:1000 REFER CallId:547c69d6-8b990009-7aa4f43f-3ffa8cd8@10.53.13.217
7948 DEB 08:39:26.946335 JAVA: SIPCC-SIP_STATE: 97/1, sip_reg_sm_change_state: Registration state
change: SIP_REG_STATE_IDLE ---> SIP_REG_STATE_IDLE
7949 DEB 08:39:26.946379 JAVA: SIPCC-SIP_STATE: 1/0, sip_stop_ack_timer: ccb->index=97
ack_timer_index=0
7950 DEB 08:39:26.946423 JAVA: SIPCC-SIP_STATE: 1/0, sip_start_ack_timer: ccb->index=97
ack_timer_index=0
7951 NOT 08:39:26.946467 JAVA: ccsip_messaging: sipSPIAddContactHeader: CFGID_DEVICE_NAME =
SEP547C69D68B99

```

7952 NOT 08:39:26.946511 JAVA: ccsip_messaging: sipSPIAddContactHeader: ccb->call_mode = 0, display_name = 35693

7953 WRN 08:39:26.946553 JAVA: LIBCISCO.GET_IMAGE bad partition 2

7954 DEB 08:39:26.946597 JAVA: SIP : sipTransportCreateSendMessage : sippmh_write() with message size=[980]

7955 DEB 08:39:26.946641 JAVA: SIPCC-SIP_TRANS: sipTransportSendMessage: bypassing ccm check

7956 DEB 08:39:26.946698 JAVA: SIPCC-SIP_TRANS: sipTransportSendMessage: Sip msg sent handle=<48>,length=<980>, message=

7957 DEB 08:39:26.946741 JAVA:

7958 DEB 08:39:26.946814 JAVA: sipio-sent---> REGISTER sip:10.102.112.3 SIP/2.0^M
Via: SIP/2.0/UDP 10.53.13.217:5060;branch=z9hG4bK18a8c119^M
From: <sip:35693@10.102.112.3>;tag=547c69d68b99001846e03d56-7f923cd3^M
To: <sip:35693@10.102.112.3>^M
Call-ID: 547c69d6-8b990010-45eb2a7c-64daecad@10.53.13.217^M
Max-Forwards: 70^M
Date: Wed, 11 Apr 2012 08:39:26 GMT^M
CSeq: 115 REGISTER^M
User-Agent: Cisco-CP7821/10.1.1^M
Contact: <sip:0797@10.53.13.217:5060;transport=udp>;+sip.instance="urn:uuid:00000000-0000-0000-0000-547c69d68b99";+u.sip!devicename.ccm.cisco.com="SEP547C69D68B99";+u.sip!model.ccm.cisco.com="621" ^M
Supported: replaces,join,sdp-anat,norefersub,resource-priority,extended-refer,X-cisco-callinfo,X-cisco-serviceuri,X-cisco-escapecodes,X-cisco-service-control,X-cisco-srtp-fallback,X-cisco-monrec,X-cisco-config,X-cisco-sis-6.0.2,X-cisco-xsi-8.5.1^M
Content-Length: 0^M
Reason: SIP;cause=200;text="cisco-alarm:24 Name=SEP547C69D68B99 ActiveLoad=sip78xx.10-1-1SR1-4.loads InactiveLoad= Last=phone-reg-rej" ^M
Expires: 3600^M
^M

7959 DEB 08:39:26.946870 JAVA: SIPCC-SIP_MSG_SEND: ccsip_store_send_msg_for_alarm: Sent:REGISTER sip:10.102.112.3 SIP/2.0 Cseq:115 REGISTER CallId:547c69d6-8b990010-45eb2a7c-64daecad@10.53.13.217

7960 DEB 08:39:26.946917 JAVA: SIPCC-SIP_STATE: 97/1, sip_reg_sm_change_state: Registration state change: SIP_REG_STATE_IDLE ---> SIP_REG_STATE_REGISTERING

7961 DEB 08:39:26.946963 JAVA: SIPCC-SIP_STATE: 98/2, sip_reg_sm_change_state: Registration state change: SIP_REG_STATE_IDLE ---> SIP_REG_STATE_IDLE

7962 DEB 08:39:26.947008 JAVA: SIPCC-SIP_STATE: 2/0, sip_stop_ack_timer: ccb->index=98
ack_timer_index=1

7963 DEB 08:39:26.947052 JAVA: SIPCC-SIP_STATE: 2/0, sip_start_ack_timer: ccb->index=98
ack_timer_index=1

7964 NOT 08:39:26.947096 JAVA: ccsip_messaging: sipSPIAddContactHeader: CFGID_DEVICE_NAME = SEP547C69D68B99

7965 NOT 08:39:26.947139 JAVA: ccsip_messaging: sipSPIAddContactHeader: ccb->call_mode = 0, display_name = 56856

7966 DEB 08:39:26.947182 JAVA: SIP : sipTransportCreateSendMessage : sippmh_write() with message size=[844]

7967 DEB 08:39:26.947239 JAVA: SIPCC-SIP_TRANS: sipTransportSendMessage: bypassing ccm check

7968 DEB 08:39:26.947284 JAVA: SIPCC-SIP_TRANS: sipTransportSendMessage: Sip msg sent handle=<48>,length=<844>, message=

7969 DEB 08:39:26.947327 JAVA:

7970 DEB 08:39:26.947394 JAVA: sipio-sent---> REGISTER sip:10.102.112.3 SIP/2.0^M
Via: SIP/2.0/UDP 10.53.13.217:5060;branch=z9hG4bK604463bb^M
From: <sip:56856@10.102.112.3>;tag=547c69d68b99001935ca68db-0955f1ba^M
To: <sip:56856@10.102.112.3>^M
Call-ID: 547c69d6-8b990011-1c427537-5a126a70@10.53.13.217^M
Max-Forwards: 70^M
Date: Wed, 11 Apr 2012 08:39:26 GMT^M
CSeq: 115 REGISTER^M
User-Agent: Cisco-CP7821/10.1.1^M
Contact: <sip:0797@10.53.13.217:5060;transport=udp>;+sip.instance="urn:uuid:00000000-0000-0000-0000-547c69d68b99";+u.sip!devicename.ccm.cisco.com="SEP547C69D68B99";+u.sip!model.ccm.cisco.com="621" ^M
Supported: replaces,join,sdp-anat,norefersub,resource-priority,extended-refer,X-cisco-callinfo,X-cisco-serviceuri,X-cisco-escapecodes,X-cisco-service-control,X-cisco-srtp-fallback,X-cisco-monrec,X-cisco-config,X-cisco-sis-6.0.2,X-cisco-xsi-8.5.1^M
Content-Length: 0^M
Expires: 3600^M
^M

7971 DEB 08:39:26.947449 JAVA: SIPCC-SIP_MSG_SEND: ccsip_store_send_msg_for_alarm: Sent:REGISTER sip:10.102.112.3 SIP/2.0 Cseq:115 REGISTER CallId:547c69d6-8b990011-1c427537-5a126a70@10.53.13.217

7972 DEB 08:39:26.947497 JAVA: SIPCC-SIP_STATE: 98/2, sip_reg_sm_change_state: Registration state

change: SIP_REG_STATE_IDLE ---> SIP_REG_STATE_REGISTERING
7973 DEB 08:39:26.947543 JAVA: SIPCC-SIP SOCK: sip_platform_udp_channel_read: Recvd 479 bytes on fd 48
7974 DEB 08:39:26.947589 JAVA: SIPCC-SIP_MSG_RECV: SIPProcessUDPMessage: UDP Message rcv: from <10.102.112.3>:<5060>, length=<479>, message=
7975 DEB 08:39:26.947642 JAVA:
7976 DEB 08:39:26.947701 JAVA: sipio-recv<--- SIP/2.0 603 Declined (No dialog)^M
Via: SIP/2.0/UDP 10.53.13.217:5060;branch=z9hG4bK210fb7c6;received=10.53.13.217^M
From: <sip:547c69d68b99@10.53.13.217>;tag=547c69d68b990017477364a9-365e5a32^M
To: <sip:10.102.112.3>;tag=as6f47a737^M
Call-ID: 547c69d6-8b990009-7aa4f43f-3ffa8cd8@10.53.13.217^M
CSeq: 1000 REFER^M
Server: FPBX-2.11.0(11.25.3)^M
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY, INFO, PUBLISH,
MESSAGE^M
Supported: replaces, timer^M
Content-Length: 0^M
^M
7977 NOT 08:39:26.947754 JAVA: SIPCC-SIP_MSG_RECV: ccsip_dump_rcv_msg_info: <10.102.112.3:0 >:603 Dec: <sip:547c69d68b99@10.53.13.217>;tag=547c69d68b990017477364a9-365e5a32 :1000
REFER::547c69d6-8b990009-7aa4f43f-3ffa8cd8@10.53.13.217
7978 DEB 08:39:26.947800 JAVA: SIPCC-SIP_ALARM: remove_stored_alarm: Alarm at index=0 of
request_id=9 sent out successfully
7979 DEB 08:39:26.947845 JAVA: SIPCC-SIP SOCK: sip_platform_udp_channel_read: Recvd 548 bytes on fd 48
7980 DEB 08:39:26.947890 JAVA: SIPCC-SIP_MSG_RECV: SIPProcessUDPMessage: UDP Message rcv: from <10.102.112.3>:<5060>, length=<548>, message=
7981 DEB 08:39:26.947932 JAVA:
7982 DEB 08:39:26.947990 JAVA: sipio-recv<--- SIP/2.0 401 Unauthorized^M
Via: SIP/2.0/UDP 10.53.13.217:5060;branch=z9hG4bK18a8c119;received=10.53.13.217^M
From: <sip:35693@10.102.112.3>;tag=547c69d68b99001846e03d56-7f923cd3^M
To: <sip:35693@10.102.112.3>;tag=as2a1783ec^M
Call-ID: 547c69d6-8b990010-45eb2a7c-64daecad@10.53.13.217^M
CSeq: 115 REGISTER^M
Server: FPBX-2.11.0(11.25.3)^M
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY, INFO, PUBLISH,
MESSAGE^M
Supported: replaces, timer^M
WWW-Authenticate: Digest algorithm=MD5, realm="asterisk", nonce="35fd0dce"^M
Content-Length: 0^M
^M
7983 DEB 08:39:26.948042 JAVA: SIPCC-SIP_RESP: sipSPICheckResponse: Response match:
callid=547c69d6-8b990010-45eb2a7c-64daecad@10.53.13.217, cseq=115, cseq_method=REGISTER
7984 NOT 08:39:26.948089 JAVA: SIPCC-SIP_REG: ccsip_handle_ev_4xx:
SIP_REG_FAILURE_POSSIBLE_UCM_CONFIG_ISSUE - Received 4xx in ccm mode. Setting registration_reject
to TRUE.
7985 NOT 08:39:26.948143 JAVA: ccsip_messaging: sipSPIAddContactHeader: CFGID_DEVICE_NAME =
SEP547C69D68B99
7986 NOT 08:39:26.948188 JAVA: ccsip_messaging: sipSPIAddContactHeader: ccb->call_mode = 0,
display_name = 35693
7987 WRN 08:39:26.948232 JAVA: LIBCISCO.GET_IMAGE bad partition 2
7988 DEB 08:39:26.948276 JAVA: SIP : sipTransportCreateSendMessage : sippmh_write() with message
size=[1135]
7989 DEB 08:39:26.948319 JAVA: SIPCC-SIP_TRANS: sipTransportSendMessage: bypassing ccm check
7990 DEB 08:39:26.948364 JAVA: SIPCC-SIP_TRANS: sipTransportSendMessage: Sip msg sent handle=
<48>,length=<1135>, message=
7991 DEB 08:39:26.948406 JAVA:
7992 DEB 08:39:26.948480 JAVA: sipio-sent---> REGISTER sip:10.102.112.3 SIP/2.0^M
Via: SIP/2.0/UDP 10.53.13.217:5060;branch=z9hG4bK276cc734^M
From: <sip:35693@10.102.112.3>;tag=547c69d68b99001846e03d56-7f923cd3^M
To: <sip:35693@10.102.112.3>^M
Call-ID: 547c69d6-8b990010-45eb2a7c-64daecad@10.53.13.217^M
Max-Forwards: 70^M
Date: Wed, 11 Apr 2012 08:39:26 GMT^M
CSeq: 116 REGISTER^M
User-Agent: Cisco-CP7821/10.1.1^M
Contact: <sip:0797@10.53.13.217:5060;transport=udp>;+sip.instance="<urn:uuid:00000000-0000-
0000-0000-
547c69d68b99>";+u.sip!devicename.ccm.cisco.com="SEP547C69D68B99";+u.sip!model.ccm.cisco.com="621"^M
Authorization: Digest

username="35693",realm="asterisk",uri="sip:10.102.112.3",response="b66420666f8c14c2866617600b2f098",nonce="35fd0dce",algorithm=MD5^M

Supported: replaces,join,sdp-anat,norefersub,resource-priority,extended-refer,X-cisco-callinfo,X-cisco-serviceuri,X-cisco-escapecodes,X-cisco-service-control,X-cisco-srtp-fallback,X-cisco-monrec,X-cisco-config,X-cisco-sis-6.0.2,X-cisco-xsi-8.5.1^M

Content-Length: 0^M

Reason: SIP;cause=200;text=

7993 DEB 08:39:26.948536 JAVA: "cisco-alarm:24 Name=SEP547C69D68B99 ActiveLoad=sip78xx.10-1-1SR1-4.loads InactiveLoad= Last=phone-reg-rej"^M

Expires: 3600^M

^M

7994 DEB 08:39:26.948597 JAVA: SIPCC-SIP_MSG_SEND: ccsip_store_send_msg_for_alarm: Sent:REGISTER sip:10.102.112.3 SIP/2.0 Cseq:116 REGISTER CallId:547c69d6-8b990010-45eb2a7c-64daecad@10.53.13.217
7995 DEB 08:39:26.948657 JAVA: SIPCC-SIP_SOCKET: sip_platform_udp_channel_read: Recvd 548 bytes on fd 48

7996 DEB 08:39:26.948703 JAVA: SIPCC-SIP_MSG_RECV: SIPProcessUDPMessage: UDP Message rcv: from <10.102.112.3>:<5060>, length=<548>, message=

7997 DEB 08:39:26.948746 JAVA:

7998 DEB 08:39:26.948804 JAVA: sipio-recv<--- SIP/2.0 401 Unauthorized^M

Via: SIP/2.0/UDP 10.53.13.217:5060;branch=z9hG4bK604463bb;received=10.53.13.217^M

From: <sip:56856@10.102.112.3>;tag=547c69d68b99001935ca68db-0955f1ba^M

To: <sip:56856@10.102.112.3>;tag=as7b87082d^M

Call-ID: 547c69d6-8b990011-1c427537-5a126a70@10.53.13.217^M

CSeq: 115 REGISTER^M

Server: FPBX-2.11.0(11.25.3)^M

Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY, INFO, PUBLISH, MESSAGE^M

Supported: replaces, timer^M

WWW-Authenticate: Digest algorithm=MD5, realm="asterisk", nonce="29bf897a"^M

Content-Length: 0^M

^M

7999 DEB 08:39:26.948854 JAVA: SIPCC-SIP_RESP: sipSPICheckResponse: Response match: callid=547c69d6-8b990011-1c427537-5a126a70@10.53.13.217, cseq=115, cseq_method=REGISTER

8000 NOT 08:39:26.948900 JAVA: SIPCC-SIP_REG: ccsip_handle_ev_4xx:

SIP_REG_FAILURE_POSSIBLE_UCM_CONFIG_ISSUE - Received 4xx in ccm mode. Setting registration_reject to TRUE.

8001 NOT 08:39:26.948944 JAVA: ccsip_messaging: sipSPIAddContactHeader: CFGID_DEVICE_NAME = SEP547C69D68B99

8002 NOT 08:39:26.949002 JAVA: ccsip_messaging: sipSPIAddContactHeader: ccb->call_mode = 0, display_name = 56856

8003 DEB 08:39:26.949048 JAVA: SIP : sipTransportCreateSendMessage : sippmh_write() with message size=[999]

8004 DEB 08:39:26.949091 JAVA: SIPCC-SIP_TRANS: sipTransportSendMessage: bypassing ccm check

8005 DEB 08:39:26.949136 JAVA: SIPCC-SIP_TRANS: sipTransportSendMessage: Sip msg sent handle=<48>,length=<999>, message=

8006 DEB 08:39:26.949177 JAVA:

8007 DEB 08:39:26.949252 JAVA: sipio-sent---> REGISTER sip:10.102.112.3 SIP/2.0^M

Via: SIP/2.0/UDP 10.53.13.217:5060;branch=z9hG4bK7fb57985^M

From: <sip:56856@10.102.112.3>;tag=547c69d68b99001935ca68db-0955f1ba^M

To: <sip:56856@10.102.112.3>^M

Call-ID: 547c69d6-8b990011-1c427537-5a126a70@10.53.13.217^M

Max-Forwards: 70^M

Date: Wed, 11 Apr 2012 08:39:26 GMT^M

CSeq: 116 REGISTER^M

User-Agent: Cisco-CP7821/10.1.1^M

Contact: <sip:0797@10.53.13.217:5060;transport=udp>;sip.instance="urn:uuid:00000000-0000-0000-0000-0000-0000-547c69d68b99">;+u.sip!devicename.ccm.cisco.com="SEP547C69D68B99";+u.sip!model.ccm.cisco.com="621"^M

Authorization: Digest

username="35693",realm="asterisk",uri="sip:10.102.112.3",response="025ed30075ac687ad6b7fecbc96428b3",nonce="29bf897a",algorithm=MD5^M

Supported: replaces,join,sdp-anat,norefersub,resource-priority,extended-refer,X-cisco-callinfo,X-cisco-serviceuri,X-cisco-escapecodes,X-cisco-service-control,X-cisco-srtp-fallback,X-cisco-monrec,X-cisco-config,X-cisco-sis-6.0.2,X-cisco-xsi-8.5.1^M

Content-Length: 0^M

Expires: 3600^M

^M

8008 DEB 08:39:26.949308 JAVA: SIPCC-SIP_MSG_SEND: ccsip_store_send_msg_for_alarm: Sent:REGISTER sip:10.102.112.3 SIP/2.0 Cseq:116 REGISTER CallId:547c69d6-8b990011-1c427537-5a126a70@10.53.13.217

8009 DEB 08:39:26.949352 JAVA: SIPCC-SIP_SOCKET: sip_platform_udp_channel_read: Recvd 469 bytes on fd

48

8010 DEB 08:39:26.949398 JAVA: SIPCC-SIP_MSG_RECV: SIPProcessUDPMessage: UDP Message rcv: from <10.102.112.3>:<5060>, length=<469>, message=

8011 DEB 08:39:26.949439 JAVA:

8012 DEB 08:39:26.949495 JAVA: sipio-recv<--- SIP/2.0 403 Forbidden^M

Via: SIP/2.0/UDP 10.53.13.217:5060;branch=z9hG4bK276cc734;received=10.53.13.217^M

From: <sip:35693@10.102.112.3>;tag=547c69d68b99001846e03d56-7f923cd3^M

To: <sip:35693@10.102.112.3>;tag=as2a1783ec^M

Call-ID: 547c69d6-8b990010-45eb2a7c-64daecad@10.53.13.217^M

CSeq: 116 REGISTER^M

Server: FPBX-2.11.0(11.25.3)^M

Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY, INFO, PUBLISH, MESSAGE^M

Supported: replaces, timer^M

Content-Length: 0^M

^M

8013 DEB 08:39:26.949557 JAVA: SIPCC-SIP_RESP: sipSPICheckResponse: Response match: callid=547c69d6-8b990010-45eb2a7c-64daecad@10.53.13.217, cseq=116, cseq_method=REGISTER

8014 NOT 08:39:26.962801 JAVA: SIPCC-SIP_REG: ccsip_handle_ev_4xx:

SIP_REG_FAILURE_POSSIBLE_UCM_CONFIG_ISSUE - Received 4xx in ccm mode. Setting registration_reject to TRUE.

8015 DEB 08:39:26.962963 JAVA: SIPCC-SIP_EVT: 97/1, sip_regmgr_ev_failure_response: Received event

8016 DEB 08:39:26.963014 JAVA: SIPCC-SIP_REG: sip_regmgr_ev_failure_response: Registration rejected.

8017 DEB 08:39:26.963060 JAVA: SIPCC-SIP_REG: sip_regmgr_handle_reg_all_fail: All registration attempts failed.

8018 NOT 08:39:26.963105 JAVA: SIPCC-UI_API: ui_set_ccm_conn_status: *****CUCM 10.102.112.3 Not connected*****

8019 NOT 08:39:26.963150 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type : SERVER_STATUS

8020 NOT 08:39:26.963195 JAVA: Thread-4|cip.sipcc.SipCcAdapter\$CcMgmtListener: - setCcmConnStatus():agent is null, ccmAddr=10.102.112.3

8021 NOT 08:39:26.963240 JAVA: Thread-4|cip.sipcc.SipCcAdapter\$CcMgmtListener: - setCcmConnStatus():agent is null, ccmAddr=10.53.2.36

8022 DEB 08:39:26.963285 JAVA: SIPCC-SIP_TRANS: sip_transport_destroy_cc_conn: CC <PRIMARY_CCM>: not closing the UDP connection

8023 DEB 08:39:26.963328 JAVA: SIPCC-SIP_TRANS: sip_get_local_ip_addr: dst_addr: 8.8.8.8

8024 DEB 08:39:26.963372 JAVA: SIPCC-SIP_TRANS: sip_get_local_ip_addr: src_addr: 10.53.13.217

8025 DEB 08:39:26.963416 JAVA: SIPCC-SIP_TRANS: sip_transport_getaddrinfo: 10.102.112.3 is already an IPv4 address

8026 ERR 08:39:26.963459 JAVA: SIPCC-SIP_TRANS: sip_transport_init_ti_addr: CCM unprovisioned

8027 ERR 08:39:26.963503 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found using primary CUCM

8028 ERR 08:39:26.963547 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found using primary CUCM

8029 NOT 08:39:26.963591 JAVA: SIPCC-UI_API: ui_set_ccm_conn_status: *****CUCM 10.102.112.3 Not connected*****

8030 NOT 08:39:26.963634 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type : SERVER_STATUS

8031 NOT 08:39:26.963678 JAVA: Thread-4|cip.sipcc.SipCcAdapter\$CcMgmtListener: - setCcmConnStatus():agent is null, ccmAddr=10.102.112.3

8032 NOT 08:39:26.963722 JAVA: Thread-4|cip.sipcc.SipCcAdapter\$CcMgmtListener: - setCcmConnStatus():agent is null, ccmAddr=10.53.2.36

8033 DEB 08:39:26.963766 JAVA: SIPCC-SIP_TRANS: sip_transport_destroy_cc_conn: CC <SECONDARY_CCM>: connection already closed

8034 ERR 08:39:26.963810 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found using primary CUCM

8035 ERR 08:39:26.963855 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found using primary CUCM

8036 NOT 08:39:26.963899 JAVA: SIPCC-UI_API: ui_set_ccm_conn_status: *****CUCM 10.102.112.3 Not connected*****

8037 NOT 08:39:26.963942 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type : SERVER_STATUS

8038 NOT 08:39:26.963988 JAVA: Thread-4|cip.sipcc.SipCcAdapter\$CcMgmtListener: - setCcmConnStatus():agent is null, ccmAddr=10.102.112.3

8039 NOT 08:39:26.964032 JAVA: Thread-4|cip.sipcc.SipCcAdapter\$CcMgmtListener: - setCcmConnStatus():agent is null, ccmAddr=10.53.2.36

8040 DEB 08:39:26.964077 JAVA: SIPCC-SIP_TRANS: sip_transport_destroy_cc_conn: CC <TERTIARY_CCM>: connection already closed

8041 ERR 08:39:26.964137 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found

```
using primary CUCM
8042 ERR 08:39:26.964184 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found
using primary CUCM
8043 NOT 08:39:26.964229 JAVA: SIPCC-UI_API: ui_set_ccm_conn_status: *****CUCM 10.102.112.3
Not connected*****
8044 NOT 08:39:26.964273 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type :
SERVER_STATUS
8045 NOT 08:39:26.964317 JAVA: Thread-4|cip.sipcc.SipCcAdapter$CcMgmtListener: -
setCcmConnStatus():agent is null, ccmAddr=10.102.112.3
8046 NOT 08:39:26.964394 JAVA: Thread-4|cip.sipcc.SipCcAdapter$CcMgmtListener: -
setCcmConnStatus():agent is null, ccmAddr=10.53.2.36
8047 DEB 08:39:26.964442 JAVA: SIPCC-SIP_TRANS: sip_transport_destroy_cc_conn: CC <SRST_CCM>:
connection already closed
8048 DEB 08:39:26.964488 JAVA: SIPCC-SIP_TIMER: sip_platform_reg_all_fail_timer_start: Timer
started for 133692 msec
8049 NOT 08:39:26.964532 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type : NOTIFYPROMPT
8050 DEB 08:39:26.964575 JAVA: SIPCC-SIP_SOCK: sip_platform_udp_channel_read: Recvd 469 bytes on fd
48
8051 DEB 08:39:26.964621 JAVA: SIPCC-SIP_MSG_RECV: SIPProcessUDPMessage: UDP Message rcv: from
<10.102.112.3>:<5060>, length=<469>, message=
8052 DEB 08:39:26.964663 JAVA:
8053 DEB 08:39:26.964723 JAVA: sipio-recv<--- SIP/2.0 403 Forbidden^M
Via: SIP/2.0/UDP 10.53.13.217:5060;branch=z9hG4bK7fb57985;received=10.53.13.217^M
From: <sip:56856@10.102.112.3>;tag=547c69d68b99001935ca68db-0955f1ba^M
To: <sip:56856@10.102.112.3>;tag=as7b87082d^M
Call-ID: 547c69d6-8b990011-1c427537-5a126a70@10.53.13.217^M
CSeq: 116 REGISTER^M
Server: FPBX-2.11.0(11.25.3)^M
Allow: INVITE, ACK, CANCEL, OPTIONS, BYE, REFER, SUBSCRIBE, NOTIFY, INFO, PUBLISH,
MESSAGE^M
Supported: replaces, timer^M
Content-Length: 0^M
^M
8054 DEB 08:39:26.964776 JAVA: SIPCC-SIP_RESP: sipSPICheckResponse: Response match:
callid=547c69d6-8b990011-1c427537-5a126a70@10.53.13.217, cseq=116, cseq_method=REGISTER
8055 NOT 08:39:26.964824 JAVA: SIPCC-CC_API: CCAPI_Config_response: send event
EV_CC_CONFIG_RECEIVED successfully
8056 NOT 08:39:26.964869 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - --->ConfigManager
PropertyChanged: device.callagent.callcount
8057 NOT 08:39:26.964913 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - <---ConfigManager
PropertyChanged: device.callagent.callcount
8058 NOT 08:39:26.964959 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - --->ConfigManager
PropertyChanged: device.callagent.callcount
8059 NOT 08:39:26.965004 JAVA: configmgr MQThread|cip.cfg.ConfigManager:? - <---ConfigManager
PropertyChanged: device.callagent.callcount
8060 NOT 08:39:26.965050 JAVA: SIPCC-SIP_REG: ccsip_handle_ev_4xx:
SIP_REG_FAILURE_POSSIBLE_UCM_CONFIG_ISSUE - Received 4xx in ccm mode. Setting registration_reject
to TRUE.
8061 DEB 08:39:26.965094 JAVA: SIPCC-SIP_EVT: 98/2, sip_regmgr_ev_failure_response: Received event
8062 DEB 08:39:26.965137 JAVA: SIPCC-SIP_REG: sip_regmgr_ev_failure_response: Registration
rejected.
8063 DEB 08:39:26.965181 JAVA: SIPCC-SIP_REG: sip_regmgr_handle_reg_all_fail: All registration
attempts failed.
8064 NOT 08:39:26.965235 JAVA: SIPCC-UI_API: ui_set_ccm_conn_status: *****CUCM 10.102.112.3
Not connected*****
8065 NOT 08:39:26.965282 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type :
SERVER_STATUS
8066 NOT 08:39:26.965328 JAVA: Thread-4|cip.sipcc.SipCcAdapter$CcMgmtListener: -
setCcmConnStatus():agent is null, ccmAddr=10.102.112.3
8067 NOT 08:39:26.965373 JAVA: Thread-4|cip.sipcc.SipCcAdapter$CcMgmtListener: -
setCcmConnStatus():agent is null, ccmAddr=10.53.2.36
8068 DEB 08:39:26.965418 JAVA: SIPCC-SIP_TRANS: sip_transport_destroy_cc_conn: CC <PRIMARY_CCM>:
connection already closed
8069 ERR 08:39:26.965462 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found
using primary CUCM
8070 ERR 08:39:26.965518 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found
using primary CUCM
8071 NOT 08:39:26.965566 JAVA: SIPCC-UI_API: ui_set_ccm_conn_status: *****CUCM 10.102.112.3
Not connected*****
8072 NOT 08:39:26.965611 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type :
```

SERVER_STATUS

```
8073 NOT 08:39:26.965655 JAVA: Thread-4|cip.sipcc.SipCcAdapter$CcMgmtListener: -
setCcmConnStatus():agent is null, ccmAddr=10.102.112.3
8074 NOT 08:39:26.965700 JAVA: Thread-4|cip.sipcc.SipCcAdapter$CcMgmtListener: -
setCcmConnStatus():agent is null, ccmAddr=10.53.2.36
8075 DEB 08:39:26.965745 JAVA: SIPCC-SIP_TRANS: sip_transport_destroy_cc_conn: CC <SECONDARY_CCM>:
connection already closed
8076 ERR 08:39:26.965802 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found
using primary CUCM
8077 ERR 08:39:26.965847 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found
using primary CUCM
8078 NOT 08:39:26.965902 JAVA: SIPCC-UI_API: ui_set_ccm_conn_status: *****CUCM 10.102.112.3
Not connected*****
8079 NOT 08:39:26.965948 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type :
SERVER_STATUS
8080 NOT 08:39:26.965992 JAVA: Thread-4|cip.sipcc.SipCcAdapter$CcMgmtListener: -
setCcmConnStatus():agent is null, ccmAddr=10.102.112.3
8081 NOT 08:39:26.966038 JAVA: Thread-4|cip.sipcc.SipCcAdapter$CcMgmtListener: -
setCcmConnStatus():agent is null, ccmAddr=10.53.2.36
8082 DEB 08:39:26.966082 JAVA: SIPCC-SIP_TRANS: sip_transport_destroy_cc_conn: CC <TERTIARY_CCM>:
connection already closed
8083 ERR 08:39:26.966126 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found
using primary CUCM
8084 ERR 08:39:26.966170 JAVA: SIPCC-SIP_TRANS: sip_transport_get_ti_addr: No active CUCM found
using primary CUCM
8085 NOT 08:39:26.966214 JAVA: SIPCC-UI_API: ui_set_ccm_conn_status: *****CUCM 10.102.112.3
Not connected*****
8086 NOT 08:39:26.966257 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type :
SERVER_STATUS
8087 NOT 08:39:26.966302 JAVA: Thread-4|cip.sipcc.SipCcAdapter$CcMgmtListener: -
setCcmConnStatus():agent is null, ccmAddr=10.102.112.3
8088 NOT 08:39:26.966348 JAVA: Thread-4|cip.sipcc.SipCcAdapter$CcMgmtListener: -
setCcmConnStatus():agent is null, ccmAddr=10.53.2.36
8089 DEB 08:39:26.966391 JAVA: SIPCC-SIP_TRANS: sip_transport_destroy_cc_conn: CC <SRST_CCM>:
connection already closed
8090 DEB 08:39:26.966435 JAVA: SIPCC-SIP_TIMER: sip_platform_reg_all_fail_timer_start: Timer
started for 156141 msec
8091 NOT 08:39:26.966482 JAVA: SIPCC-SIP_CC_PROV: ccsnap_gen_deviceEvent: event type : NOTIFYPROMPT
8092 ERR 08:39:27.005121 JAVA: messages MQThread|cip.g3.userio.InputManager:? - lightLamp.. type =
8 value= 0 state= 1 color=0
8093 WRN 08:39:27.029172 JAVA: System P8-sessmgr MQThread|DisplayTask:? - Line 1 property added
with dn 35693
8094 INF 08:39:27.029385 JAVA: System P8-sessmgr MQThread|DisplayTask:? - getEnergywiseKeywords():
set the keywords = 547C69D68B99, DN-35693, CP-7821
8095 INF 08:39:27.091329 JAVA: System P7-display MQThread|OverviewModel:? - createLine-----
pos=0
8096 ERR 08:39:27.113631 JAVA: System P7-display MQThread|cip.g3.userio.InputManager:? -
lightLamp.. type = 3 value= 1 state= 1 color=2
8097 INF 08:39:27.117001 JAVA: System P7-display MQThread|OverviewModel:? - createLine-----
pos=1
8098 ERR 08:39:27.143453 JAVA: System P7-display MQThread|cip.g3.userio.InputManager:? -
lightLamp.. type = 3 value= 2 state= 1 color=2
8099 NOT 08:39:39.183536 JAVA: appmenu MQThread|cip.g3.menuapp.MenuApp:? - NO SERVICE URL
Configured
8100 DEB 08:39:39.184455 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=6
8101 DEB 08:39:39.184560 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=1
8102 DEB 08:39:39.312571 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=6
8103 DEB 08:39:39.312749 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=1
8104 DEB 08:39:39.312806 JAVA: System P7-display MQThread|DisplayTask:? - clearUriTimer
8105 INF 08:39:39.312853 JAVA: System P7-display MQThread|DisplayTask:? - ---->
EWTTask.doDefaultUserActiveAction()
8106 INF 08:39:39.312899 JAVA: System P7-display MQThread|DisplayTask:? -
doDefaultUserActiveAction(): processing
8107 DEB 08:39:39.312944 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(0)
8108 DEB 08:39:39.312988 JAVA: System P7-display MQThread|DisplayTask:? - isIdleTimerSet=false
isRunning=false
```

```
8109 WRN 08:39:39.313036 JAVA: System P7-display MQThread|DisplayTask:? -
java.lang.IllegalArgumentException: Timer Interval(0) must be between 1 and 1471228928 using a
default IDLE timer: 3600000
8110 DEB 08:39:39.313110 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(3600000)
8111 DEB 08:39:39.313158 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=false
isRunning=false
8112 DEB 08:39:39.313203 JAVA: System P7-display MQThread|DisplayTask:? - DisplayOn(): is display
currently on? true
8113 DEB 08:39:39.313247 JAVA: System P7-display MQThread|DisplayTask:? - isDisplayOn=true
8114 NOT 08:39:39.314382 PWRMAN-setMode(): NORMAL
8115 NOT 08:39:39.314982 PWRMAN-eventRcv(): recv() failed : Connection reset by peer
8116 WRN 08:39:39.321576 kernel: [ 771.390219] Set LCD backlight 1
8117 DEB 08:39:41.082701 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8118 DEB 08:39:41.082872 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=2
8119 DEB 08:39:41.211262 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8120 DEB 08:39:41.211454 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=2
8121 DEB 08:39:41.211514 JAVA: System P7-display MQThread|DisplayTask:? - clearUriTimer
8122 INF 08:39:41.211563 JAVA: System P7-display MQThread|DisplayTask:? - ---->
EWTask.doDefaultUserActiveAction()
8123 INF 08:39:41.211608 JAVA: System P7-display MQThread|DisplayTask:? -
doDefaultUserActiveAction(): processing
8124 DEB 08:39:41.211653 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(0)
8125 DEB 08:39:41.211698 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8126 WRN 08:39:41.211745 JAVA: System P7-display MQThread|DisplayTask:? -
java.lang.IllegalArgumentException: Timer Interval(0) must be between 1 and 1471228928 using a
default IDLE timer: 3600000
8127 DEB 08:39:41.211790 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(3600000)
8128 DEB 08:39:41.211833 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8129 DEB 08:39:41.211877 JAVA: System P7-display MQThread|DisplayTask:? - DisplayOn(): is display
currently on? true
8130 DEB 08:39:41.211920 JAVA: System P7-display MQThread|DisplayTask:? - isDisplayOn=true
8131 NOT 08:39:41.213213 PWRMAN-setMode(): NORMAL
8132 NOT 08:39:41.213308 PWRMAN-eventRcv(): recv() failed : Connection reset by peer
8133 WRN 08:39:41.221611 kernel: [ 773.282360] Set LCD backlight 1
8134 DEB 08:39:41.272824 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8135 DEB 08:39:41.272989 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=2
8136 DEB 08:39:41.421741 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8137 DEB 08:39:41.421894 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=2
8138 DEB 08:39:41.421956 JAVA: System P7-display MQThread|DisplayTask:? - clearUriTimer
8139 INF 08:39:41.422007 JAVA: System P7-display MQThread|DisplayTask:? - ---->
EWTask.doDefaultUserActiveAction()
8140 INF 08:39:41.422052 JAVA: System P7-display MQThread|DisplayTask:? -
doDefaultUserActiveAction(): processing
8141 DEB 08:39:41.422097 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(0)
8142 DEB 08:39:41.422140 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8143 WRN 08:39:41.422187 JAVA: System P7-display MQThread|DisplayTask:? -
java.lang.IllegalArgumentException: Timer Interval(0) must be between 1 and 1471228928 using a
default IDLE timer: 3600000
8144 DEB 08:39:41.422232 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(3600000)
8145 DEB 08:39:41.422275 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8146 DEB 08:39:41.422320 JAVA: System P7-display MQThread|DisplayTask:? - DisplayOn(): is display
currently on? true
8147 DEB 08:39:41.422399 JAVA: System P7-display MQThread|DisplayTask:? - isDisplayOn=true
8148 NOT 08:39:41.422442 PWRMAN-setMode(): NORMAL
8149 NOT 08:39:41.423739 PWRMAN-eventRcv(): recv() failed : Connection reset by peer
8150 WRN 08:39:41.431590 kernel: [ 773.492334] Set LCD backlight 1
8151 DEB 08:39:41.462725 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
```



```
8152 DEB 08:39:41.462890 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=2
8153 DEB 08:39:41.571718 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8154 DEB 08:39:41.571877 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=2
8155 DEB 08:39:41.571935 JAVA: System P7-display MQThread|DisplayTask:? - clearUriTimer
8156 INF 08:39:41.571981 JAVA: System P7-display MQThread|DisplayTask:? - ---->
EWTask.doDefaultUserActiveAction()
8157 INF 08:39:41.572025 JAVA: System P7-display MQThread|DisplayTask:? -
doDefaultUserActiveAction(): processing
8158 DEB 08:39:41.572069 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(0)
8159 DEB 08:39:41.572113 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8160 WRN 08:39:41.572160 JAVA: System P7-display MQThread|DisplayTask:? -
java.lang.IllegalArgumentException: Timer Interval(0) must be between 1 and 1471228928 using a
default IDLE timer: 3600000
8161 DEB 08:39:41.572205 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(3600000)
8162 DEB 08:39:41.572248 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8163 DEB 08:39:41.572292 JAVA: System P7-display MQThread|DisplayTask:? - DisplayOn(): is display
currently on? true
8164 DEB 08:39:41.572335 JAVA: System P7-display MQThread|DisplayTask:? - isDisplayOn=true
8165 NOT 08:39:41.572374 PWRMAN-setMode(): NORMAL
8166 NOT 08:39:41.573246 PWRMAN-eventRcv(): recv() failed : Connection reset by peer
8167 WRN 08:39:41.581600 kernel: [ 773.642472] Set LCD backlight 1
8168 DEB 08:39:41.642579 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=7
8169 DEB 08:39:41.642748 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=2
8170 DEB 08:39:41.786621 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8171 DEB 08:39:41.786805 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=2
8172 DEB 08:39:41.786864 JAVA: System P7-display MQThread|DisplayTask:? - clearUriTimer
8173 INF 08:39:41.786911 JAVA: System P7-display MQThread|DisplayTask:? - ---->
EWTask.doDefaultUserActiveAction()
8174 INF 08:39:41.786955 JAVA: System P7-display MQThread|DisplayTask:? -
doDefaultUserActiveAction(): processing
8175 DEB 08:39:41.786999 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(0)
8176 DEB 08:39:41.787043 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8177 WRN 08:39:41.787089 JAVA: System P7-display MQThread|DisplayTask:? -
java.lang.IllegalArgumentException: Timer Interval(0) must be between 1 and 1471228928 using a
default IDLE timer: 3600000
8178 DEB 08:39:41.787135 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(3600000)
8179 DEB 08:39:41.787179 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8180 DEB 08:39:41.787222 JAVA: System P7-display MQThread|DisplayTask:? - DisplayOn(): is display
currently on? true
8181 DEB 08:39:41.787265 JAVA: System P7-display MQThread|DisplayTask:? - isDisplayOn=true
8182 NOT 08:39:41.788521 PWRMAN-setMode(): NORMAL
8183 NOT 08:39:41.788617 PWRMAN-eventRcv(): recv() failed : Connection reset by peer
8184 WRN 08:39:41.791413 kernel: [ 773.862303] Set LCD backlight 1
8185 DEB 08:39:42.582512 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8186 DEB 08:39:42.582682 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=9
8187 DEB 08:39:42.689510 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8188 DEB 08:39:42.689661 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=9
8189 DEB 08:39:42.689720 JAVA: System P7-display MQThread|DisplayTask:? - clearUriTimer
8190 INF 08:39:42.689767 JAVA: System P7-display MQThread|DisplayTask:? - ---->
EWTask.doDefaultUserActiveAction()
8191 INF 08:39:42.689812 JAVA: System P7-display MQThread|DisplayTask:? -
doDefaultUserActiveAction(): processing
8192 DEB 08:39:42.689857 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(0)
8193 DEB 08:39:42.689900 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
```

```
8194 WRN 08:39:42.689947 JAVA: System P7-display MQThread|DisplayTask:? -
java.lang.IllegalArgumentException: Timer Interval(0) must be between 1 and 1471228928 using a
default IDLE timer: 3600000
8195 DEB 08:39:42.689993 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(3600000)
8196 DEB 08:39:42.690037 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8197 DEB 08:39:42.690080 JAVA: System P7-display MQThread|DisplayTask:? - DisplayOn(): is display
currently on? true
8198 DEB 08:39:42.690123 JAVA: System P7-display MQThread|DisplayTask:? - isDisplayOn=true
8199 ERR 08:39:42.690166 JAVA: appmenu MQThread|cip.xml.XmlParser: - The Encoding ASCII is invalid
8200 NOT 08:39:42.690205 PWRMAN-setMode(): NORMAL
8201 NOT 08:39:42.691184 PWRMAN-eventRcv(): recv() failed : Connection reset by peer
8202 WRN 08:39:42.691533 kernel: [ 774.762239] Set LCD backlight 1
8203 DEB 08:39:43.492522 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8204 DEB 08:39:43.492693 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=9
8205 DEB 08:39:43.581059 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8206 DEB 08:39:43.581280 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=9
8207 DEB 08:39:43.581339 JAVA: System P7-display MQThread|DisplayTask:? - clearUriTimer
8208 INF 08:39:43.581388 JAVA: System P7-display MQThread|DisplayTask:? - ---->
EWTask.doDefaultUserActiveAction()
8209 INF 08:39:43.581435 JAVA: System P7-display MQThread|DisplayTask:? -
doDefaultUserActiveAction(): processing
8210 DEB 08:39:43.581479 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(0)
8211 DEB 08:39:43.581525 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8212 WRN 08:39:43.581571 JAVA: System P7-display MQThread|DisplayTask:? -
java.lang.IllegalArgumentException: Timer Interval(0) must be between 1 and 1471228928 using a
default IDLE timer: 3600000
8213 DEB 08:39:43.581615 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(3600000)
8214 DEB 08:39:43.581659 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8215 DEB 08:39:43.581703 JAVA: System P7-display MQThread|DisplayTask:? - DisplayOn(): is display
currently on? true
8216 DEB 08:39:43.581746 JAVA: System P7-display MQThread|DisplayTask:? - isDisplayOn=true
8217 NOT 08:39:43.581787 PWRMAN-setMode(): NORMAL
8218 NOT 08:39:43.582661 PWRMAN-eventRcv(): recv() failed : Connection reset by peer
8219 WRN 08:39:43.591604 kernel: [ 775.658420] Set LCD backlight 1
8220 DEB 08:39:45.002554 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8221 DEB 08:39:45.002721 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=9
8222 DEB 08:39:45.131287 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=7
8223 DEB 08:39:45.131487 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=9
8224 DEB 08:39:45.131548 JAVA: System P7-display MQThread|DisplayTask:? - clearUriTimer
8225 INF 08:39:45.131596 JAVA: System P7-display MQThread|DisplayTask:? - ---->
EWTask.doDefaultUserActiveAction()
8226 INF 08:39:45.131643 JAVA: System P7-display MQThread|DisplayTask:? -
doDefaultUserActiveAction(): processing
8227 DEB 08:39:45.131689 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(0)
8228 DEB 08:39:45.131734 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8229 WRN 08:39:45.131781 JAVA: System P7-display MQThread|DisplayTask:? -
java.lang.IllegalArgumentException: Timer Interval(0) must be between 1 and 1471228928 using a
default IDLE timer: 3600000
8230 DEB 08:39:45.131826 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(3600000)
8231 DEB 08:39:45.131869 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8232 DEB 08:39:45.131913 JAVA: System P7-display MQThread|DisplayTask:? - DisplayOn(): is display
currently on? true
8233 DEB 08:39:45.131957 JAVA: System P7-display MQThread|DisplayTask:? - isDisplayOn=true
8234 NOT 08:39:45.133241 PWRMAN-setMode(): NORMAL
8235 NOT 08:39:45.133339 PWRMAN-eventRcv(): recv() failed : Connection reset by peer
8236 WRN 08:39:45.141594 kernel: [ 777.202487] Set LCD backlight 1
8237 ERR 08:39:55.005586 JAVA: System P9-mediacontrolui MQThread|cip.msui.MediaControlUI$2:execute
```

```
- [TR] received event in state: Event =EventHandsetOffHookEvent; State =StateNoAudio
8238 NOT 08:39:55.005782 JAVA: System P9-mediactrolui MQThread|cip.msui.MediaControlUI$2:execute
- [TR] executing the state-event handlerFunction=NoAudioHandsetOffHookFunc
8239 DEB 08:39:55.005848 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=8
8240 DEB 08:39:55.005896 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=7
8241 DEB 08:39:55.005941 JAVA: System P7-display MQThread|DisplayTask:? - clearUriTimer
8242 INF 08:39:55.005984 JAVA: System P7-display MQThread|DisplayTask:? - ---->
EWTask.doDefaultUserActiveAction()
8243 INF 08:39:55.006027 JAVA: System P7-display MQThread|DisplayTask:? -
doDefaultUserActiveAction(): processing
8244 DEB 08:39:55.008589 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(0)
8245 DEB 08:39:55.008714 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8246 WRN 08:39:55.008770 JAVA: System P7-display MQThread|DisplayTask:? -
java.lang.IllegalArgumentException: Timer Interval(0) must be between 1 and 1471228928 using a
default IDLE timer: 3600000
8247 DEB 08:39:55.008816 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(3600000)
8248 DEB 08:39:55.008892 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8249 DEB 08:39:55.008940 JAVA: System P7-display MQThread|DisplayTask:? - DisplayOn(): is display
currently on? true
8250 DEB 08:39:55.008985 JAVA: System P7-display MQThread|DisplayTask:? - isDisplayOn=true
8251 NOT 08:39:55.009041 PWRMAN-setMode(): NORMAL
8252 NOT 08:39:55.010173 PWRMAN-eventRcv(): recv() failed : Connection reset by peer
8253 WRN 08:39:55.011329 kernel: [ 787.085964] Set LCD backlight 1
8254 ERR 08:39:55.313010 JAVA: System P9-mediactrolui MQThread|cip.msui.MediaControlUI$2:execute
- [TR] received event in state: Event =EventHandsetOnHookEvent; State =StateNoAudio
8255 NOT 08:39:55.313172 JAVA: System P9-mediactrolui MQThread|cip.msui.MediaControlUI$2:execute
- [TR] executing the state-event handlerFunction=NoAudioHandsetOnHookFunc
8256 NOT 08:39:55.313227 ms-APATH.ms_setOutputAudioPath Saving [output audio device = 6][volume=7]
8257 NOT 08:39:55.313307 ms-APATH.ms_setOutputAudioPath No active streams, exiting
8258 NOT 08:39:55.319832 JAVA: System P9-mediactrolui MQThread|cip.msui.MediaControlUI:? - [TR]
ONHOOK sent to SessionUI=false
8259 NOT 08:39:55.320440 ms-APATH.ms_setInputAudioPath Saving [input audio device = 261]
8260 NOT 08:39:55.320575 ms-APATH.ms_setInputAudioPath No active streams, exiting
8261 DEB 08:39:55.330931 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=8
8262 DEB 08:39:55.332044 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=6
8263 NOT 08:39:55.332431 ms-APATH.ms_setOutputAudioPath Saving [output audio device = 6][volume=7]
8264 NOT 08:39:55.332763 ms-APATH.ms_setOutputAudioPath No active streams, exiting
8265 DEB 08:39:55.332821 JAVA: System P8-sessmgr MQThread|cip.callagent.CallAgent:? - The
isRegistered is: true
8266 DEB 08:39:55.332868 JAVA: System P8-sessmgr MQThread|cip.callagent.SoftkeyHandler:? - Chan:
newFeatureSet.length4
8267 ERR 08:39:55.332914 JAVA: System P9-mediactrolui MQThread|cip.sidecar.Sidecar:In the
PropertyChanged - EHOOK_ACTIVE and it is false
8268 INF 08:39:55.332961 JAVA: System P7-display MQThread|OverviewModel:? - selectFeatureSet-----
---featureSet=[Lcip.app.ApplicationFeature;@6a196a19
8269 NOT 08:39:55.781320 JAVA: set gTOS = 0, ret=0, sock=47
8270 NOT 08:39:55.781485 JAVA: then get tos = 0, socket=47
8271 NOT 08:39:55.781540 JAVA: set gTOS = 0, ret=0, sock=49
8272 NOT 08:39:55.781667 JAVA: then get tos = 0, socket=49
8273 NOT 08:39:55.788937 JAVA: HTTP JNI| httpServerHandler: uri=/CGI/Java/Serviceability
8274 DEB 08:39:56.084667 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=8
8275 DEB 08:39:56.084836 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=7
8276 DEB 08:39:56.084891 JAVA: System P7-display MQThread|DisplayTask:? - clearUriTimer
8277 INF 08:39:56.084938 JAVA: System P7-display MQThread|DisplayTask:? - ---->
EWTask.doDefaultUserActiveAction()
8278 INF 08:39:56.084985 JAVA: System P7-display MQThread|DisplayTask:? -
doDefaultUserActiveAction(): processing
8279 DEB 08:39:56.085030 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(0)
8280 DEB 08:39:56.085073 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8281 WRN 08:39:56.085120 JAVA: System P7-display MQThread|DisplayTask:? -
java.lang.IllegalArgumentException: Timer Interval(0) must be between 1 and 1471228928 using a
```

```
default IDLE timer: 3600000
8282 DEB 08:39:56.085164 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(3600000)
8283 DEB 08:39:56.085208 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8284 DEB 08:39:56.085252 JAVA: System P7-display MQThread|DisplayTask:? - DisplayOn(): is display
currently on? true
8285 DEB 08:39:56.085296 JAVA: System P7-display MQThread|DisplayTask:? - isDisplayOn=true
8286 NOT 08:39:56.086091 PWRMAN-setMode(): NORMAL
8287 NOT 08:39:56.086665 PWRMAN-eventRcv(): rcv() failed : Connection reset by peer
8288 ERR 08:39:56.087672 JAVA: System P9-mediacontrolui MQThread|cip.msui.MediaControlUI$2:execute
- [TR] received event in state: Event =EventHandsetOffHookEvent; State =StateNoAudio
8289 NOT 08:39:56.087781 JAVA: System P9-mediacontrolui MQThread|cip.msui.MediaControlUI$2:execute
- [TR] executing the state-event handlerFunction=NoAudioHandsetOffHookFunc
8290 WRN 08:39:56.091436 kernel: [ 788.162397] Set LCD backlight 1
8291 NOT 08:39:56.100189 JAVA: HTTP JNI| Java_cip_http_NativeHttpRequestUpdateServletRequest:
conId=0, state=3, error=0, mimeType=0
8292 NOT 08:39:56.102805 JAVA: HTTP JNI| httpServerHandler: conId=0, pushStatus=3
8293 NOT 08:39:56.102948 JAVA: HTTP JNI| httpServerHandler: call to mg_send_file,
fileName=/tmp/cache/PUSH_RESP_0_0.x
8294 NOT 08:39:56.103004 JAVA: before push tos = 0, socket=47
8295 NOT 08:39:56.103047 JAVA: before push tos = 0, socket=47
8296 NOT 08:39:56.145351 JAVA: HTTP JNI| httpServerHandler: call to mg_send_file,
fileName=/tmp/cache/Logo.png
8297 NOT 08:39:56.145482 JAVA: before push tos = 0, socket=49
8298 NOT 08:39:56.145532 JAVA: before push tos = 0, socket=49
8299 NOT 08:39:56.236413 JAVA: set gTOS = 0, ret=0, sock=47
8300 NOT 08:39:56.236557 JAVA: then get tos = 0, socket=47
8301 NOT 08:39:56.239511 JAVA: HTTP JNI| httpServerHandler: call to mg_printf 200 OK
8302 NOT 08:39:56.239624 JAVA: before push tos = 0, socket=47
8303 ERR 08:39:56.269490 JAVA: System P9-mediacontrolui MQThread|cip.msui.MediaControlUI$2:execute
- [TR] received event in state: Event =EventHandsetOnHookEvent; State =StateNoAudio
8304 NOT 08:39:56.269665 JAVA: System P9-mediacontrolui MQThread|cip.msui.MediaControlUI$2:execute
- [TR] executing the state-event handlerFunction=NoAudioHandsetOnHookFunc
8305 NOT 08:39:56.269746 ms-APATH.ms_setOutputAudioPath Saving [output audio device = 6][volume=7]
8306 NOT 08:39:56.269792 ms-APATH.ms_setOutputAudioPath No active streams, exiting
8307 NOT 08:39:56.269861 JAVA: System P9-mediacontrolui MQThread|cip.msui.MediaControlUI:? - [TR]
ONHOOK sent to SessionUI=false
8308 NOT 08:39:56.269906 ms-APATH.ms_setInputAudioPath Saving [input audio device = 261]
8309 NOT 08:39:56.269948 ms-APATH.ms_setInputAudioPath No active streams, exiting
8310 NOT 08:39:56.269989 ms-APATH.ms_setOutputAudioPath Saving [output audio device = 6][volume=7]
8311 NOT 08:39:56.270029 ms-APATH.ms_setOutputAudioPath No active streams, exiting
8312 ERR 08:39:56.270073 JAVA: System P9-mediacontrolui MQThread|cip.sidecar.Sidecar:In the
PropertyChanged - EHOOK_ACTIVE and it is false
8313 DEB 08:39:56.270118 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=8
8314 DEB 08:39:56.270164 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=6
8315 DEB 08:39:56.270207 JAVA: System P8-sessmgr MQThread|cip.callagent.CallAgent:? - The
isRegistered is: true
8316 DEB 08:39:56.270250 JAVA: System P8-sessmgr MQThread|cip.callagent.SoftkeyHandler:? - Chan:
newFeatureSet.length4
8317 INF 08:39:56.270294 JAVA: System P7-display MQThread|OverviewModel:? - selectFeatureSet-----
---featureSet=[Lcip.app.ApplicationFeature;@5fe45fe4
8318 DEB 08:39:56.633498 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=2
8319 DEB 08:39:56.633659 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=1
8320 DEB 08:39:56.704087 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventType.intValue()=2
8321 DEB 08:39:56.704260 JAVA: System P7-display MQThread|DisplayTask:? - DisplayTask-----
userActive---eventValue.intValue()=1
8322 DEB 08:39:56.704318 JAVA: System P7-display MQThread|DisplayTask:? - clearUriTimer
8323 INF 08:39:56.704367 JAVA: System P7-display MQThread|DisplayTask:? - ---->
EWTask.doDefaultUserActiveAction()
8324 INF 08:39:56.704413 JAVA: System P7-display MQThread|DisplayTask:? -
doDefaultUserActiveAction(): processing
8325 DEB 08:39:56.704457 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(0)
8326 DEB 08:39:56.704500 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8327 WRN 08:39:56.704547 JAVA: System P7-display MQThread|DisplayTask:? -
```

```
java.lang.IllegalArgumentException: Timer Interval(0) must be between 1 and 1471228928 using a
default IDLE timer: 3600000
8328 DEB 08:39:56.704591 JAVA: System P7-display MQThread|DisplayTask:? - setIdleTimer(3600000)
8329 DEB 08:39:56.704633 JAVA: System P7-display MQThread|DisplayTask:? - IsIdleTimerSet=true
isRunning=true
8330 DEB 08:39:56.704676 JAVA: System P7-display MQThread|DisplayTask:? - DisplayOn(): is display
currently on? true
8331 DEB 08:39:56.704719 JAVA: System P7-display MQThread|DisplayTask:? - isDisplayOn=true
8332 NOT 08:39:56.705542 PWRMAN-setMode(): NORMAL
8333 NOT 08:39:56.706119 PWRMAN-eventRcv(): recv() failed : Connection reset by peer
```