

DF5-PG-E1(Outdoor)



Standard Price \$340.00



Heavy duty \$534.95

Product Features

- 5.9-Inch Acrylic Bubble with plenum-Rated Back Box
- Hard Ceiling and Suspended Ceiling Applications
- Versatile and Adjustable Fixed Camera Mount Bracket
- Environmentally Sealed and Weatherized Pendant for Use in Temperatures to -60°F (-51°C)
- Pendant Models Meet NEMA Type 4X, IP66 Standards
- Input 24 VAC
- Heavy-Duty Models
 - Tough, Reinforced Construction
 - 0.090-Inch Injection-Molded Polycarbonate Bubble

The **DF5 Series** pendant models mount directly to any recommended mount flush to a ceiling, or to 1.5-inch NPT female threaded pipe and are available for indoor and environmental applications. All environmental versions include a sun shield and heater kit and are suitable for use in temperatures to -60°F (-51°C). Heavy-duty pendant models (DF5HD-PG) are strengthened by a thicker sun shroud and dual wall construction.

A variety of lower domes are available for this series. Standard and shortened back box models are equipped with an acrylic bubble; available colors for standard models include smoked, clear, chrome, or gold, and smoked or clear for shortened models. The standard back box is also available with a flat acrylic window for use in applications where overhead space is minimal. Flat window colors are clear or smoked. All heavy-duty domes feature a clear polycarbonate bubble, 0.090-inch thick, which provides an optimum combination of strength and optical clarity.