

Directory Numbers

Base Phone

Line 1 - 1164

Line 2 - Add new DN

Phone: SEP0015FA348885 (1164)

Registration: Not Registered

IP Address: 192.168.19.222

Status: Ready

Copy Update Delete Reset Phone

Phone Configuration (Model = Cisco 7960)

Device Information

MAC Address* 0015FA348885

Description 1164

Owner User ID [\(Select User ID\)](#)

Device Pool* BKIS [\(View details\)](#)

Calling Search Space < None >

AAR Calling Search Space < None >

Media Resource Group List < None >

User Hold Audio Source < None >

Network Hold Audio Source < None >

Location < None >

User Locale < None >

Network Locale < None >

Device Security Mode Use System Default

Device security mode only takes effect if the enterprise parameter Cluster Security Mode is set to 1

Signal Packet Capture Mode None

Packet Capture Duration 0

Built In Bridge Default

Privacy Default

- Retry Video Call as Audio
- Ignore Presentation Indicators (internal calls only)

Phone Button Template Information

Phone Button Template* Standard 7960 [\(View button list\)](#)

Softkey Template Information

Softkey Template < None >

Expansion Module Information

Module 1 < None >

Module 2 < None >

Firmware Load Information (leave blank to use default)

Phone Load Name


Module 1 Load Name (Module 1 selection required)

Module 2 Load Name (Module 2 selection required)

Cisco IP Phone - External Data Locations (leave blank to use default)

Information

Directory

Authentication Server	<input type="text"/>
Proxy Server	<input type="text"/>
Idle	<input type="text"/>
Idle Timer (seconds)	<input type="text"/>
Extension Mobility (Device Profile) Information	
<input type="checkbox"/> Enable Extension Mobility Feature	
Log Out Profile	<input type="text" value="--- Not Selected ---"/>
Log In User ID	< None >
Log In Time	< None >
Log Out Time	< None >
Certification Authority Proxy Function (CAPF) Information	
Certificate Operation	<input type="text" value="No Pending Operation"/>
Authentication Mode	<input type="text" value="By Authentication String"/>
Authentication String	<input type="text"/> <input type="button" value="Generate String"/>
Key Size (bits)	<input type="text" value="1024"/>
Operation Completes By**	<input type="text"/> : <input type="text"/> : <input type="text"/> : <input type="text"/> (YYYY : MM : DD : HH)
Certificate Operation Status : None	
Multilevel Precedence and Preemption (MLPP) Information	
MLPP Domain	<input type="text"/> (e.g., "0000FF")
MLPP Indication	<input type="text" value="Default"/>
MLPP Preemption	<input type="text" value="Default"/>
Product Specific Configuration 	
Disable Speakerphone	<input type="checkbox"/>
Disable Speakerphone and Headset	<input type="checkbox"/>
Forwarding Delay*	<input type="text" value="Disabled"/>
PC Port*	<input type="text" value="Enabled"/>
Settings Access*	<input type="text" value="Enabled"/>
Gratuitous ARP*	<input type="text" value="Enabled"/>
PC Voice VLAN Access*	<input type="text" value="Enabled"/>
Video Capabilities*	<input type="text" value="Disabled"/>
Auto Line Select*	<input type="text" value="Disabled"/>
Web Access*	<input type="text" value="Enabled"/>
* indicates a required item.	
** Indicates time on Publisher.	
Back to top of page Back to Find/List Phones	

Directory Number Configuration

[Configure Device \(SEP0015FA348885\)](#)
[Dependency Records](#)

Associated With

SEP0015FA348885
7960 (Line 1)

Directory Number: 1164

Status: Ready

Note: Any update to this Directory Number automatically resets the associated devices

Directory Number

Directory Number*
Partition

Directory Number Settings

Voice Mail Profile
(Choose <None> to use default)
Calling Search Space
AAR Group
User Hold Audio Source
Network Hold Audio Source
Auto Answer

Call Forward and Pickup Settings

	Voice Mail	Coverage/ Destination	Calling Search Space
Forward All	<input type="checkbox"/>	<input type="text"/>	<input type="text" value=" < None >"/>
Forward Busy Internal	<input type="checkbox"/>	<input type="text"/>	<input type="text" value=" < None >"/>
Forward Busy External	<input type="checkbox"/>	<input type="text"/>	<input type="text" value=" < None >"/>
Forward Busy External	<input type="checkbox"/>	<input type="text"/>	<input type="text" value=" < None >"/>
Forward No Answer Internal	<input type="checkbox"/>	<input type="text"/>	<input type="text" value=" < None >"/>
Forward No Answer External	<input type="checkbox"/>	<input type="text"/>	<input type="text" value=" < None >"/>
Forward No Coverage Internal	<input type="checkbox"/>	<input type="text"/>	<input type="text" value=" < None >"/>
Forward No Coverage External	<input type="checkbox"/>	<input type="text"/>	<input type="text" value=" < None >"/>
No Answer Ring Duration	<input type="text"/>	(seconds)	
Call Pickup Group	<input type="text" value=" < None >"/>	(View Details)	

MLPP Alternate Party Settings

Target (Destination)
Calling Search Space
No Answer Ring Duration (seconds)

Line Settings for all Devices

Alerting Name

Line Settings for this Device

Display (Internal Caller ID)
Line Text Label
External Phone Number Mask
Message Waiting Lamp Policy
Ring Setting (Phone Idle)
Ring Setting (Phone Active)**

Multiple Call / Call Waiting Settings

Maximum Number of Calls* (1 - 200)
Busy Trigger* (<= Max. Calls)

Forwarded Call Information Display

Caller Name Caller Number
 Redirected Number Dialed Number

* indicates required item; changes to Line or Directory Number settings require restart.

** Ring Setting (Phone Active) applies to this line when any line on the phone has a call in progress.

Note:

If you are using a language other than English for Display (Internal Caller ID) or Line Text Label text, make sure the correct character set (shown below) is selected. Text displays incorrectly if the wrong characterset is selected. (English characters are included in all character sets.)

Character Set

