



- Getting Started
- Run Setup Wizard
- ▶ Status
- ▼ Networking
 - ▼ WAN (Internet)
 - IPv4 WAN (Internet)**
 - PPPoE Profiles
 - ▶ LAN (Local Network)
 - ▶ Routing
 - Port Management
 - Dynamic DNS
 - ▶ IPv6
- ▶ Wireless
- ▶ Firewall
- ▶ Cisco ProtectLink Web
- ▶ VPN
- ▶ Security
- ▶ QoS
- ▶ Administration

IPv4 WAN (Internet)

Internet Connection Type

Internet Connection Type

Static IP Settings

IP Address (xxx.xxx.xxx.xxx)

Subnet Mask (xxx.xxx.xxx.xxx)

Default Gateway

Primary DNS Server

Secondary DNS Server (Optional)

MTU Size

MTU Type Default

Custom

MTU Size Bytes (Range : 1200 - 1500, Default : 1500)

Router MAC Address

MAC Address Source

MAC Address

Save

Cancel



Small Business

RV220W Wireless-N Network Security Firewall

Getting Started

Run Setup Wizard

▶ Status

▼ Networking

▶ WAN (Internet)

▼ LAN (Local Network)

IPv4 LAN (Local Network)

VLAN Membership

Multiple VLAN Subnets

Static DHCP

Advanced DHCP Configuration

DHCP Leased Clients

Jumbo Frames

▶ Routing

Port Management

Dynamic DNS

▶ IPv6

▶ Wireless

▶ Firewall

▶ Cisco ProtectLink Web

▶ VPN

▶ Security

▶ QoS

▶ Administration

IPv4 LAN (Local Network)

Network

Host Name

SBS 2011 Computer

LAN (Local Network) Configuration

IP Address

(xxx.xxx.xxx.xxx)

Subnet Mask

(xxx.xxx.xxx.xxx)

DHCP

DHCP Mode

Configure Static DHCP

Domain Name

Starting IP Address

(xxx.xxx.xxx.xxx)

Ending IP Address

(xxx.xxx.xxx.xxx)

Primary DNS Server

(Optional)

Secondary DNS Server

(Optional)

Lease Time

Hours (Range : 1 - 262800, Default : 24)

Remote DHCP Server

LAN (Local Network) Proxy

DNS Proxy

 Enable

Save

Cancel

- Getting Started
- Run Setup Wizard
- ▶ Status
- ▼ **Networking**
 - ▶ WAN (Internet)
 - ▼ LAN (Local Network)
 - IPv4 LAN (Local Network)
 - VLAN Membership**
 - Multiple VLAN Subnets
 - Static DHCP
 - Advanced DHCP Configuration
 - DHCP Leased Clients
 - Jumbo Frames
 - ▶ Routing
 - Port Management
 - Dynamic DNS
 - ▶ IPv6
- ▶ Wireless
- ▶ Firewall
- ▶ Cisco ProtectLink Web
- ▶ VPN
- ▶ Security
- ▶ QoS
- ▶ Administration

VLAN Membership

VLAN Enable

Create VLANs and assign the Outgoing Frame Type.

Up to Fifteen new VLANs can be created. VLAN IDs must be in the range (2 - 4093)

VLAN Membership Table

<input type="checkbox"/>	VLAN ID	Description	Inter VLAN Routing	Device Management	Port 1	Port 2	Port 3	Port 4
<input type="checkbox"/>	1	Default	Disabled	Enabled	Untagged	Untagged	Untagged	Excluded
<input type="checkbox"/>	99	Voice3CX	Disabled	Enabled	Excluded	Excluded	Excluded	Untagged

1 - 2 of 2

Plugged into Domain Switch
Cisco SLM2024

Plugged into Voice Switch
Cisco SG300-28P

Administration



Small Business

RV220W Wireless-N Network Security Firewall

Getting Started

Run Setup Wizard

▶ Status

▼ Networking

▶ WAN (Internet)

▼ LAN (Local Network)

IPv4 LAN (Local Network)

VLAN Membership

Multiple VLAN Subnets

Static DHCP

Advanced DHCP Configuration

DHCP Leased Clients

Jumbo Frames

▶ Routing

Port Management

Dynamic DNS

▶ IPv6

▶ Wireless

▶ Firewall

▶ Cisco ProtectLink Web

▶ VPN

▶ Security

▶ QoS

▶ Administration

Multiple VLAN Subnets

Multiple VLAN Subnet Table

	VLAN ID	IP Address	Subnet Mask	DHCP Mode	DNS Proxy Status
<input type="checkbox"/>	1	172.20.8.1	255.255.255.0	None	Enabled
<input type="checkbox"/>	99	192.168.66.1	255.255.255.0	DHCP Server	Enabled

Edit