

Status: Ready

- Association Information**
- 1 Line 711 - 1595 in PhonesPT
 - 2 Line 721 - Add a new DN
 - Unassigned Associated Items
 - 3 Line 731 - 2263 in PhonesPT
 - 4 Line 741 - 2259 in PhonesPT
 - 5 Line 751 - 2253 in PhonesPT
 - 6 Line 761 - Add a new DN
 - 7 Add a new SQ
 - 8 Add a new SUBI
 - 9 Add a new BLF S3
 - 10 Add a new BLF Directed Call Park
 - 11 Privat
 - 12 Ingen

Phone Type
Product Type: Cisco 7940
Device Protocol: SCCP

Device Information

Registration: Registered with Cisco Unified Communications Manager 10.10.2.159
 IP Address: 10.10.1.46
 MAC Address: 0014491B5534
 Description: 1595
 Device Pool: Silkeborg-CP
 Common Device Configuration: Highsec/CommonProfile1
 Phone Button Template: SEP0014491B5534-SCCP-Individual Template
 Softkey Template: Standard User Silkeborg
 Common Phone Profile: Standard Common Phone Profile
 Calling Search Space: < None >
 AAR Calling Search Space: < None >
 Media Resource Group List: < None >
 User Hold MOH Audio Source: < None >
 Network Hold MOH Audio Source: < None >
 Location: IT
 AAR Group: < None >
 User Locale: < None >
 Network Locale: < None >
 Built In Bridge: Standard
 Privacy: Standard
 Device Mobility Mode: Standard
 Owner User ID: < None >
 Phone Load Name:
 Join Across Lines: Standard
 Use Trusted Relay Point: Standard
 BLF Audible Alert Setting (Phone Idle): Standard
 BLF Audible Alert Setting (Phone Busy): Standard
 Calling Party Transformation CSS: < None >
 Use Device Pool Calling Party Transformation CSS
 Is Active
 Retry Video Call as Audio
 Ignore Presentation Indicators (Internal calls only)
 Allow Control of Device from CTI
 Logged Into Hunt Group
 Remote Device

Protocol Specific Information

Packet Capture Mode: Ingen
 Packet Capture Duration: 60
 Presence Group: Standard Presence group
 Device Security Profile: Security Profile-3
 SUBSCRIBE Calling Search Space: < None >
 Unattended Port
 Require DTMF Reception
 RFC2833 Disabled

Certification Authority Proxy Function (CAPF) Information

Certificate Operation: No Pending Operation
 Authentication Mode: By Authentication String
 Authentication String:

 Key Size (bits): 1024
 Operation Completes By: 00:05:12 (YYYY-MM-DD:HH)
 Certificate Operation Status: Ingen
 Note: Security Profile Contains Addition CAPF Settings.

External Data Locations Information (Leave blank to use default)

Information:
 Directory:
 Messages:
 Services:
 Authentication Server:
 Proxy Server:
 Idle:
 Idle Timer (seconds):

Extension Information

Enable Extension Mobility
 Log Out Profile: Use Current Device Settings
 Log in Time: < None >
 Log out Time: < None >

MLPP Information

MLPP Domain: < None >
 MLPP Indication: Standard
 MLPP Preemption: Default

Do Not Disturb

Do Not Disturb
 DND Option: Ringer er afbrudt
 DND Incoming Call Alert: < None >

Product Specific Configuration Layout

Disable Speakerphone
 Disable Speakerphone and Headset
 PC Port: Enabled
 Settings Access: Enabled
 Gratuitous Atp: Enabled
 PC Voice VLAN Access: Enabled
 Video Capabilities: Enabled
 Auto Line Select: Disabled
 Web Access: Enabled

* - indicates required item.
 ** - Device reset is not required for changes to Packet Capture Mode and Packet Capture Duration.
 ***Note: Security Profile Contains Addition CAPF Settings.
 ****Note: A new softkey template without supplementary service softkeys must be used for a protected phone.

Save Delete Reset Add New

Status: Ready

Directory Number Information

Directory Number* 1595
 Route Partition PhonesPT
 Description
 Alerting Name Carl-Marius Steensen
 ASCII Alerting Name Carl-Marius Steensen
 Allow Control of Device from CTI
 Associated Devices
 SEP0014691B5534
 SEP0013C4ECA124
 SEP0013C4FBB80E
 Edit Device
 Edit Line Appearance
 Dissociate Devices

Directory Number Settings

Voice Mail Profile < None > (Choose <None> to use system default)
 Calling Search Space NationalCSS
 Presence Group* Standard Presence group
 User Hold MOH Audio Source < None >
 Network Hold MOH Audio Source < None >
 Auto Answer* Auto Answer Off

AAR Settings

AAR or AAR Destination Mask < None > AAR Group < None >
 Retain this destination in the call forwarding history

Call Forward and Call Pickup Settings

	Voice Mail	Destination	Calling Search Space
Calling Search Space Activation Policy			Brug systemstandard
Forward All	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Secondary Calling Search Space for Forward All			< None >
Forward Busy Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward Busy External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Answer Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Answer External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Coverage Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Coverage External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward on CTI Failure	<input type="checkbox"/> or <input type="checkbox"/>		< None >
Forward Unregistered Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward Unregistered External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
No Answer Ring Duration (seconds)			
Call Pickup Group	IT-Applikationer in InternPT Find		

MLPP Alternate Party Settings

Target (Destination)
 MLPP Calling Search Space < None >
 MLPP No Answer Ring Duration (seconds)

Line Settings for All Devices

Hold Reversion Ring Duration (seconds) Setting the Hold Reversion Ring Duration to zero will disable the feature
 Hold Reversion Notification Interval (seconds) Setting the Hold Reversion Notification Interval to zero will disable the feature

Line 1 on Device SEP0014691B5534

	Value	Update Shared Device Settings
Display (Internal Caller ID)	Carl-Marius Steensen <small>Display text for a line appearance is intended for displaying text such as a name instead of a directory number for internal calls. If you specify a number, the person receiving a call may not see the proper identity of the caller.</small>	<input type="checkbox"/>
ASCII Display (Internal Caller ID)	Carl-Marius Steensen	<input type="checkbox"/>
Line Text Label		<input type="checkbox"/>
ASCII Line Text Label		<input type="checkbox"/>
External Phone Number Mask		<input type="checkbox"/>
Visual Message Waiting Indicator Policy*	Use System Policy	<input type="checkbox"/>
Ring Setting (Phone Idle)*	Brug systemstandard	<input type="checkbox"/>
Ring Setting (Phone Active)	Brug systemstandard <small>Applies to this line when any line on the phone has a call in progress.</small>	<input type="checkbox"/>
Call Pickup Group Audio Alert Setting (Phone Idle)	Brug systemstandard	
Call Pickup Group Audio Alert Setting (Phone Active)	Brug systemstandard	
Monitoring Calling Search Space	< None >	

Propagate Selected

Multiple Call/Call Waiting Settings on Device SEP0014691B5534

Note: The range to select the Max Number of calls is: 1-288
 Maximum Number of Calls* 4
 Busy Trigger* 1 (Less than or equal to Max. Calls)

Forwarded Call Information Display on Device SEP0014691B5534

Caller Name
 Caller Number
 Redirected Number
 Dialed Number

Users Associated with Line

Associate End Users

Save Delete Reset Add New

* indicates required item.
 ** Changes to Line or Directory Number settings require restart.

Save Delete Reset Add New

Status: Ready

Directory Number Information

Directory Number* 1595
 Route Partition PhonesPT
 Description
 Alerting Name Carl-Marius Steensen
 ASCII Alerting Name Carl-Marius Steensen
 Allow Control of Device from CTI
 Associated Devices
 SEP0014691B5534
 SEP0013C4ECA124
 SEP0013C4FBB80E
 Edit Device
 Edit Line Appearance
 Dissociate Devices

Directory Number Settings

Voice Mail Profile < None > (Choose <None> to use system default)
 Calling Search Space NationalCSS
 Presence Group* Standard Presence group
 User Hold MOH Audio Source < None >
 Network Hold MOH Audio Source < None >
 Auto Answer* Auto Answer Off

AAR Settings

AAR or AAR Destination Mask < None > AAR Group < None >
 Retain this destination in the call forwarding history

Call Forward and Call Pickup Settings

	Voice Mail	Destination	Calling Search Space
Calling Search Space Activation Policy			Brug systemstandard
Forward All	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Secondary Calling Search Space for Forward All			< None >
Forward Busy Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward Busy External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Answer Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Answer External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Coverage Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Coverage External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward on CTI Failure	<input type="checkbox"/> or <input type="checkbox"/>		< None >
Forward Unregistered Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward Unregistered External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
No Answer Ring Duration (seconds)			
Call Pickup Group	IT-Applikationer in InternPT Find		

MLPP Alternate Party Settings

Target (Destination)
 MLPP Calling Search Space < None >
 MLPP No Answer Ring Duration (seconds)

Line Settings for All Devices

Hold Reversion Ring Duration (seconds) Setting the Hold Reversion Ring Duration to zero will disable the feature
 Hold Reversion Notification Interval (seconds) Setting the Hold Reversion Notification Interval to zero will disable the feature

Line 1 on Device SEP0014691B5534

	Value	Update Shared Device Settings
Display (Internal Caller ID)	Carl-Marius Steensen <small>Display text for a line appearance is intended for displaying text such as a name instead of a directory number for internal calls. If you specify a number, the person receiving a call may not see the proper identity of the caller.</small>	<input type="checkbox"/>
ASCII Display (Internal Caller ID)	Carl-Marius Steensen	<input type="checkbox"/>
Line Text Label		<input type="checkbox"/>
ASCII Line Text Label		<input type="checkbox"/>
External Phone Number Mask		<input type="checkbox"/>
Visual Message Waiting Indicator Policy*	Use System Policy	<input type="checkbox"/>
Ring Setting (Phone Idle)*	Brug systemstandard	<input type="checkbox"/>
Ring Setting (Phone Active)	Brug systemstandard <small>Applies to this line when any line on the phone has a call in progress.</small>	<input type="checkbox"/>
Call Pickup Group Audio Alert Setting (Phone Idle)	Brug systemstandard	
Call Pickup Group Audio Alert Setting (Phone Active)	Brug systemstandard	
Monitoring Calling Search Space	< None >	

Propagate Selected

Multiple Call/Call Waiting Settings on Device SEP0014691B5534

Note: The range to select the Max Number of calls is: 1-288
 Maximum Number of Calls* 4
 Busy Trigger* 1 (Less than or equal to Max. Calls)

Forwarded Call Information Display on Device SEP0014691B5534

Caller Name
 Caller Number
 Redirected Number
 Dialed Number

Users Associated with Line

Associate End Users

Save Delete Reset Add New

* indicates required item.
 ** Changes to Line or Directory Number settings require restart.