

Cisco Unified CM Administration
 TII Cisco Unified Communications Solutions

Navigation: Cisco Unified CM Administration | Status: Ready

System > Call Routing > Media Resources > Voice Mail > Device > Application > User Management > Bulk Administration > Help

Directory Number Configuration | Related Links: [Configure Device \(SEP0013C4ECA124\)](#)

Save | Delete | Reset | Add New

Status
 Status: Ready

Directory Number Information

Directory Number* 1557
 Route Partition PhonesPT
 Description
 Alerting Name IT-servicesdesk
 ASCII Alerting Name IT-servicesdesk
 Allow Control of Device from CTI
 Associated Devices SEP0013C4ECA124
 Edit Device | Edit Line Appearance

Dissociate Devices

Directory Number Settings

Voice Mail Profile < None > (Choose <None> to use system default)
 Calling Search Space NationalCSS
 Presence Group* Standard Presence group
 User Hold MOH Audio Source < None >
 Network Hold MOH Audio Source < None >
 Auto Answer* Auto Answer Off

AAR Settings

AAR or
 Retain this destination in the call forwarding history

Call Forward and Call Pickup Settings

	Voice Mail	Destination	Calling Search Space
Calling Search Space Activation Policy			Brug systemstandard
Forward All	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Secondary Calling Search Space for Forward All			< None >
Forward Busy Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward Busy External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Answer Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Answer External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Coverage Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward No Coverage External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward on CTI Failure	<input type="checkbox"/> or <input type="checkbox"/>		< None >
Forward Unregistered Internal	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
Forward Unregistered External	<input type="checkbox"/> or <input type="checkbox"/>		InternCSS
No Answer Ring Duration (seconds)	<input type="text"/>		
Call Pickup Group	IT in InternPT <input type="button" value="Find"/>		

MLPP Alternate Party Settings

Target (Destination)
 MLPP Calling Search Space < None >
 MLPP No Answer Ring Duration (seconds)

Line Settings for All Devices

Hold Reversion Ring Duration (seconds) Setting the Hold Reversion Ring Duration to zero will disable the feature
 Hold Reversion Notification Interval (seconds) Setting the Hold Reversion Notification Interval to zero will disable the feature

Line 1 on Device SEP0013C4ECA124

Display (Internal Caller ID) Lisbeth Kanstrup
Display text for a line appearance is intended for displaying text such as a name instead of a directory number for internal calls. If you specify a number, the person receiving a call may not see the proper identity of the caller.

ASCII Display (Internal Caller ID) Lisbeth Kanstrup
 Line Text Label
 ASCII Line Text Label
 External Phone Number Mask
 Visual Message Waiting Indicator Policy* Use System Policy
 Ring Setting (Phone Idle)* Brug systemstandard
 Ring Setting (Phone Active) Brug systemstandard Applies to this line when any line on the phone has a call in progress.
 Call Pickup Group Audio Alert Setting (Phone Idle) Brug systemstandard
 Call Pickup Group Audio Alert Setting (Phone Active) Brug systemstandard
 Monitoring Calling Search Space < None >

Multiple Call/Call Waiting Settings on Device SEP0013C4ECA124

Note: The range to select the Max. Number of calls is: 1-172
 Maximum Number of Calls*
 Busy Trigger* (Less than or equal to Max. Calls)

Forwarded Call Information Display on Device SEP0013C4ECA124

Caller Name
 Caller Number
 Redirected Number
 Dialed Number

Users Associated with Line

Save | Delete | Reset | Add New

Info *- indicates required item.
Info **- Changes to Line or Directory Number settings require restart.

Status
 Status: Ready

Directory Number Information

Directory Number* 1558
 Route Partition PhonesPT
 Description
 Alerting Name Susanne Burchall
 ASCII Alerting Name Susanne Burchall
 Allow Control of Device from CTI
 Associated Devices SEP0013C4FB80E Edit Device Edit Line Appearance
 Dissociate Devices

Directory Number Settings

Voice Mail Profile < None > (Choose <None> to use system default)
 Calling Search Space NationalCSS
 Presence Group* Standard Presence group
 User Hold MOH Audio Source < None >
 Network Hold MOH Audio Source < None >
 Auto Answer* Auto Answer Off

AAR Settings

AAR	Voice Mail	AAR Destination Mask	AAR Group
<input type="checkbox"/>	or		< None >

Retain this destination in the call forwarding history

Call Forward and Call Pickup Settings

	Voice Mail	Destination	Calling Search Space
Calling Search Space Activation Policy			Brug.systemstandard
Forward All	<input type="checkbox"/>		NationalCSS
Secondary Calling Search Space for Forward All			< None >
Forward Busy Internal	<input type="checkbox"/>		InternCSS
Forward Busy External	<input type="checkbox"/>		InternCSS
Forward No Answer Internal	<input type="checkbox"/>		InternCSS
Forward No Answer External	<input type="checkbox"/>		InternCSS
Forward No Coverage Internal	<input type="checkbox"/>		InternCSS
Forward No Coverage External	<input type="checkbox"/>		InternCSS
Forward on CTI Failure	<input type="checkbox"/>		< None >
Forward Unregistered Internal	<input type="checkbox"/>		InternCSS
Forward Unregistered External	<input type="checkbox"/>		InternCSS
No Answer Ring Duration (seconds)			
Call Pickup Group		IT in InternPT	Find

MLPP Alternate Party Settings

Target (Destination)
 MLPP Calling Search Space < None >
 MLPP No Answer Ring Duration (seconds)

Line Settings for All Devices

Hold Reversion Ring Duration (seconds) Setting the Hold Reversion Ring Duration to zero will disable the feature
 Hold Reversion Notification Interval (seconds) Setting the Hold Reversion Notification Interval to zero will disable the feature

Line 1 on Device SEP0013C4FB80E

Display (Internal Caller ID) IT-Servicedesk Display text for a line appearance is intended for displaying text such as a name instead of a directory number for internal calls. If you specify a number, the person receiving a call may not see the proper identity of the caller.
 ASCII Display (Internal Caller ID) IT-Servicedesk
 Line Text Label
 ASCII Line Text Label
 External Phone Number Mask
 Visual Message Waiting Indicator Policy* Use System Policy
 Ring Setting (Phone Idle)* Brug.systemstandard
 Ring Setting (Phone Active) Brug.systemstandard Applies to this line when any line on the phone has a call in progress.
 Call Pickup Group Audio Alert Setting (Phone Idle) Brug.systemstandard
 Call Pickup Group Audio Alert Setting (Phone Active) Brug.systemstandard
 Monitoring Calling Search Space < None >

Multiple Call/Call Waiting Settings on Device SEP0013C4FB80E
 Note: The range to select the Max Number of calls is: 1-172
 Maximum Number of Calls* 4
 Busy Trigger* 1 (Less than or equal to Max. Calls)

Forwarded Call Information Display on Device SEP0013C4FB80E

Caller Name
 Caller Number
 Redirected Number
 Dialed Number

Users Associated with Line

	Full Name	User ID	Permission
<input type="checkbox"/>	Burchall,Susanne	dr17618	

Associate End Users Select All Clear All Delete Selected

Save Delete Reset Add New

* indicates required item.
 ** Changes to Line or Directory Number settings require restart.