

Cisco ATA 186 (SCCP) Configuration

UIPassword:		UseTftp:	1
TftpURL:	0	AltTftpURL:	0
CfgInterval:	3600	EncryptKey:	
EncryptKeyEx:	00000000000000000000	Dhcp:	1
StaticIP:	0.0.0.0	StaticRoute:	0.0.0.0
StaticNetMask:	255.255.255.0	EPID0orSID0:	.
EPID1orSID1:	.	CA0orCM0:	0
CA1orCM1:	0	LBRCCodec:	3
PrfCodec:	1	AudioMode:	0x00350035
ConnectMode:	0x90000400	CallerIdMethod:	0xc0019e60
DNS1IP:	0.0.0.0	DNS2IP:	0.0.0.0
Domain:	0	NumTxFrames:	2
TOS:	0x000068b8	OpFlags:	0x00000002
VLANSetting:	0x0000002b	Polarity:	0x00000000
FXSInputLevel:	-1	FXSOutputLevel:	-4
SigTimer:	0x00000064	RingCadence:	2,4,25
DialTone:	2,31538,30831,1380,17	DialTone2:	2,29780,30743,1252,13
BusyTone:	2,30467,28959,1191,15	ReorderTone:	2,30467,28959,1191,15
RingBackTone:	2,30831,30467,1943,21	CallWaitTone:	1,30831,0,5493,0,0,240
AlertTone:	1,30467,0,5970,0,0,240	NPrintf:	0.0.0.0
TraceFlags:	0x00000000	SyslogIP:	0.0.0.0.514
SyslogCtrl:	0x00000000	MediaPort:	16384
CFGID:	0x00000000		

apply

ata3037a6172e1e

Version: v3.1.0 atascpp (Build 040305B)

DHCP Assigned: IP[172.17.39.60] Subnet[255.255.255.0] Route[172.17.39.1]

MAC: 48.55.166.23.46.30

SerialNumber: FCH14078L1G

ProductId: ATA186I2-A

Features: 0x00000016

HardwareVersion: 0x0014 0x0000