

Building configuration...

```
Current configuration : 18634 bytes
!
! Last configuration change at 17:21:54 UTC Sun Oct 20 2013 by FRH
version 15.2
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname FRH1861E
!
boot-start-marker
boot-end-marker
!
!
!
aaa new-model
!
!
aaa authentication login default local
aaa authorization exec default local
!
!
!
!
aaa session-id common
mmi polling-interval 60
no mmi auto-configure
no mmi pvc
mmi snmp-timeout 180
!
crypto pki trustpoint TP-self-signed-1964371378
enrollment selfsigned
subject-name cn=IOS-Self-Signed-Certificate-1964371378
revocation-check none
rsa-keypair TP-self-signed-1964371378
!
!
dot11 syslog
!
!
!
!
ip dhcp relay information trust-all
ip dhcp excluded-address 10.10.10.1 10.10.10.10
!
ip dhcp pool phone
network 10.10.10.0 255.255.255.0
default-router 10.10.10.1
dns-server 217.0.43.97 217.0.43.113 192.168.2.1
option 150 ip 10.10.10.1
!
!
!
ip name-server 217.0.43.97
ip cef
no ipv6 cef
!
multilink bundle-name authenticated
!
!
!
!
!
!
voice service voip
ip address trusted list
ipv4 217.0.16.39
ipv4 217.0.16.231
ipv4 217.10.79.9
ipv4 217.0.17.103
ipv4 217.0.16.234
ipv4 217.0.16.170
callmonitor
no callmonitor trace
allow-connections h323 to h323
allow-connections h323 to sip
allow-connections sip to h323
allow-connections sip to sip
no supplementary-service sip handle-replaces
sip
registrar server expires max 3600 min 1800
asymmetric payload full
sip-profiles 10
video screening
!
voice class codec 1
codec preference 1 g711alaw
codec preference 2 g711ulaw
codec preference 3 g723r53
codec preference 4 g729r8
codec preference 5 g729br8
codec preference 6 g726r32
codec preference 7 g728
!
voice class sip-profiles 10
request INVITE sip-header From modify "< sip:06209123456@(.*)>" "< sip:06209123456@tel.t-online.de>"
request ANY sip-header From modify "Frank" "06209123456"
request INVITE sip-header From modify "< sip:06209789012@(.*)>" "< sip:06209789012@tel.t-online.de>"
request ANY sip-header From modify "Office" "06209789012"
!
!
voice register global
mode cse
source-address 10.10.10.1 port 5060
max-dn 10
max-pool 2
load 9971 sip9971.9-3-25R1-1
authenticate register
authenticate realm all
timezone 21
time-format 24
date-format 0/M/Y
tftp-path flash:
file text
create profile sync 0000420080667257
network-locale DE
user-locale DE
camera
video
overlap-signal
!
voice register dn 1
translation-profile outgoing OUT
number 11
name Frank
no-reg
label Frank
mwi
!
voice register dn 2
translation-profile outgoing OUTOffice
number 10
name Office
no-reg
label Office
mwi
!
voice register pool 1
id mac 0008.3030.6AAA
session-transport tcp
type 9971
number 1 dn 1
number 3 dn 2
username cisco password cisco
codec g711alaw
!
!
!
!
!
voice translation-rule 1
!
voice translation-rule 2
rule 1 /06209123456/ /11/
rule 2 /06209789012/ /11/
rule 3 /1132000/ /11/
!
voice translation-rule 3
rule 1 /.*\//06209123456/
!
voice translation-rule 4
rule 1 /.*\//06209789012/
!
!
voice translation-profile IN
translate called 2
```



```

session target dns:tel.t-online.de
voice-class sip dtmf-relay force rtp-nte
dtmf-relay rtp-nte
codec g711alaw
no vad
!
!
sip-ua
credentials username 1132000 password 7 ***password*** realm sippgate.de
credentials username 06209123456 password 7 ***password*** realm tel.t-online.de
credentials username 06209789012 password 7 ***password*** realm tel.t-online.de
authentication username 1132000 password 7 ***password*** realm sippgate.de
authentication username f.hohenadel@t-online.de password 7 ***password*** realm tel.t-online.de
no remote-party-id
retry invite 4
retry response 3
retry bye 2
retry cancel 2
retry register 5
retry options 10
timers connect 100
timers register 250
registrar 1 dns:tel.t-online.de expires 3600
registrar 2 dns:sippgate.de expires 3600
sip-server dns:tel.t-online.de
connection-reuse
host-registrar
!
!
!
telephony-service
no auto-reg-ephone
max-ephones 12
max-dn 30
ip source-address 10.10.10.1 port 2000
max-redirect 5
cnf-file location flash:
user-locale UI load CME-locale-de_DE-German-8.8.2.5.tar
load 7925 CP7925G-1.4.4.3.LOADS
time-zone 23
time-format 24
date-format dd-mm-yy
max-conferences 4 gain -6
moh "flash:/on_bacd_music_on_hold.au"
web admin system name FRH secret 5 $152Wqj$Ki.gdre0MzTLR0CYxcG51
dn-webedit
time-webedit
transfer-system full-consult
create cnf-files version-stamp Jan 01 2002 00:00:00
!
!
ephone-dn 1 dual-line
number 12
!
!
ephone-dn 2 dual-line
number 13
!
!
ephone 1
device-security-mode none
description Phone1
mac-address E05F.B9BC.74CE
max-calls-per-button 4
type 7925
button 1:1
!
!
!
ephone 2
device-security-mode none
description Phone2
mac-address E05F.B9BB.F4D9
max-calls-per-button 4
type 7925
button 1:2
!
!
!
line con 0
no modem enable
line aux 0
line 0/2/0
no exec
line vty 0 4
privilege level 15
transport input telnet ssh
transport output telnet ssh
line vty 5 15
exec-timeout 30 0
privilege level 15
transport input telnet ssh
transport output telnet ssh
!
!
end

```