

Building configuration...

Current configuration : 10821 bytes

```
!  
! Last configuration change at 18:22:38 UTC Sun Oct 6 2013 by FRH  
! NVRAM config last updated at 19:15:03 UTC Sun Oct 6 2013 by FRH  
! NVRAM config last updated at 19:15:03 UTC Sun Oct 6 2013 by FRH  
version 15.1  
service timestamps debug datetime msec  
service timestamps log datetime msec  
no service password-encryption  
!  
hostname FRH1861  
!  
boot-start-marker  
boot-end-marker  
!  
!  
!  
aaa new-model  
!  
!  
aaa authentication login default local  
aaa authorization exec default local  
!  
!  
!  
aaa session-id common  
!  
network-clock-participate wic 1  
mmi polling-interval 60  
no mmi auto-configure  
no mmi pvc  
mmi snmp-timeout 180  
crypto pki token default removal timeout 0  
!  
crypto pki trustpoint TP-self-signed-1523924997  
  enrollment selfsigned  
  subject-name cn=IOS-Self-Signed-Certificate-1523924997  
  revocation-check none  
  rsakeypair TP-self-signed-1523924997  
!  
!  
crypto pki certificate chain TP-self-signed-1523924997  
certificate self-signed 01  
  3082022B 30820194 A0030201 02020101 300D0609 2A864886 F70D0101 05050030  
  31312F30 2D060355 04031326 494F532D 53656C66 2D536967 6E65642D 43657274  
  69666963 6174652D 31353233 39323439 3937301E 170D3133 30393237 31323139  
  34305A17 0D323030 31303130 30303030 305A3031 312F302D 06035504 03132649  
  4F532D53 656C662D 5369676E 65642D43 65727469 66696361 74652D31 35323339  
  32343939 3730819F 300D0609 2A864886 F70D0101 01050003 818D0030 81890281  
  8100F41B C9EEA3BD 15073826 968522F0 1122027B 22D3E8FC 5C0D91B9 B717C0CE  
  E7818621 9D0F0C67 1C57EDA3 F806CB4A 57852B00 D08B9BC7 A88A8C73 AB324111  
  CD64DC2C 4572170E CFEF680B 04F41D0C 39379A32 3EEF51B5 E9B36828 5A880872  
  048546E3 9DE46980 4125BAC6 301E37E1 B3403513 D4814728 202F7AB8 238D2C9C  
  E3B50203 010001A3 53305130 0F060355 1D130101 FF040530 030101FF 301F0603  
  551D2304 18301680 14A8AAE9 81606ADD 10C70A06 93D3E686 DE74127B 0B301D06  
  03551D0E 04160414 A8AAE981 605ADD10 C70A0693 D3E686DE 74127B0B 300D0609  
  2A864886 F70D0101 05050003 81810021 42D1417B 80D3C229 A64034B6 E6093B4F  
  4ACA045D A9A4493A B180039F 224AB9A1 F46F6D16 182E1CB8 8393CF90 591A03C2  
  EF361C85 9098A1FA 71A2B865 0E80BF5B 290DE2D4 22B0E99C 05371898 5BE00E30  
  9ED263C5 C91137C6 A7ED3A0F B8060D4E 26FB0985 5D282CDA 0D6B8B53 28ABDF03  
  F4405FAA B01E1F56 19E65AD2 5A79DF  
  quit  
dot11 syslog  
ip source-route  
ip cef  
!  
!  
!  
ip dhcp relay information trust-all  
ip dhcp excluded-address 192.168.10.1 192.168.10.99
```

```
ip dhcp excluded-address 10.10.10.1 10.10.10.10
!
ip dhcp pool data
network 192.168.10.0 255.255.255.0
dns-server 217.0.43.97 217.0.43.113
default-router 192.168.10.1
!
ip dhcp pool phone
network 10.10.10.0 255.255.255.0
default-router 10.10.10.1
dns-server 217.0.43.97 217.0.43.113
option 150 ip 10.10.10.1
!
!
ip name-server 217.0.43.97
no ipv6 cef
!
multilink bundle-name authenticated
!
!
!
!
!
!
voice rtp send-recv
!
voice service voip
ip address trusted list
ipv4 217.0.16.39
ipv4 217.0.16.231
ipv4 217.10.79.9
ipv4 217.0.17.103
no ip address trusted authenticate
callmonitor
allow-connections h323 to h323
allow-connections h323 to sip
allow-connections sip to h323
allow-connections sip to sip
sip
bind control source-interface Vlan1
bind media source-interface Vlan1
registrar server expires max 3600 min 120
asymmetric payload full
video screening
!
voice class codec 1
codec preference 1 g711alaw
codec preference 2 g711ulaw
codec preference 3 g723r53
codec preference 4 g729r8
codec preference 5 g729br8
codec preference 6 g726r32
codec preference 7 g728
!
!
voice register global
mode cme
source-address 10.10.10.1 port 5060
max-dn 10
max-pool 2
load 9971 sip9971.9-1-1SR1
authenticate register
authenticate realm all
timezone 21
time-format 24
date-format D/M/Y
tftp-path flash:
file text
create profile sync 0000420080667258
network-locale DE
user-locale DE
camera
video
overlap-signal
!
voice register dn 1
```

```

translation-profile outgoing OUT
number 11
name Frank
no-reg
mwi
!
voice register dn 2
number 10
name Office
no-reg
mwi
!
voice register pool 1
id mac 0008.3030.6AAA
type 9971
number 1 dn 1
number 3 dn 2
voice-class codec 1
username cisco password cisco
no vad
camera
video
!
voice hunt-group 1 parallel
list 11,12,13
pilot 24
!
!
!
!
voice translation-rule 1
rule 1 /10/ /1132000/
!
voice translation-rule 2
rule 3 /1132000/ /10/
!
voice translation-rule 3
rule 1 /^.* / /1132000/
!
!
voice translation-profile IN
translate called 2
!
voice translation-profile OUT
translate calling 3
!
!
voice-card 0
!
!
!
license udi pid C1861-UC-B/K9-MS sn FHK144871U3
username cisco
!
!
no ip ftp passive
!
!
!
bridge irb
!
!
!
!
interface FastEthernet0/0
description ***ISP Provider***
ip address dhcp
ip nat outside
ip virtual-reassembly in
duplex full
speed 100
!
interface Integrated-Service-Engine0/0
no ip address
ip nat inside

```

```

ip virtual-reassembly in
!
interface FastEthernet0/1/0
no ip address
!
interface FastEthernet0/1/1
no ip address
!
interface FastEthernet0/1/2
no ip address
!
interface FastEthernet0/1/3
no ip address
!
interface FastEthernet0/1/4
no ip address
!
interface FastEthernet0/1/5
no ip address
!
interface FastEthernet0/1/6
no ip address
!
interface FastEthernet0/1/7
no ip address
!
interface FastEthernet0/1/8
no ip address
!
interface BRI0/1/0
no ip address
!
interface BRI0/1/1
no ip address
!
interface Vlan1
ip address 10.10.10.1 255.255.255.0
ip nat inside
ip virtual-reassembly in
!
ip forward-protocol nd
ip http server
ip http authentication local
ip http secure-server
ip http timeout-policy idle 600 life 86400 requests 10000
!
!
ip nat inside source list 1 interface FastEthernet0/0 overload
ip route 0.0.0.0 0.0.0.0 FastEthernet0/0
!
access-list 1 permit 10.10.10.0 0.0.0.255
access-list 1 permit 192.168.10.0 0.0.0.255
!
!
!
!
!
tftp-server flash:APPSH-1.4.1SR1.SBN alias APPSH-1.4.1SR1.SBN
tftp-server flash:CP7925G-1.4.1SR1.LOADS alias CP7925G-1.4.1SR1.LOADS
tftp-server flash:GUIH-1.4.1SR1.SBN alias GUIH-1.4.1SR1.SBN
tftp-server flash:JSYSH-1.4.1SR1.SBN alias JSYSH-1.4.1SR1.SBN
tftp-server flash:JUIH-1.4.1SR1.SBN alias JUIH-1.4.1SR1.SBN
tftp-server flash:SYSH-1.4.1SR1.SBN alias SYSH-1.4.1SR1.SBN
tftp-server flash:TNUXH-1.4.1SR1.SBN alias TNUXH-1.4.1SR1.SBN
tftp-server flash:TNUXRH-1.4.1SR1.SBN alias TNUXRH-1.4.1SR1.SBN
tftp-server flash:WLANH-1.4.1SR1.SBN alias WLANH-1.4.1SR1.SBN
tftp-server flash:sip9971.9-1-1SR1.loads alias sip9971.9-1-1SR1.loads
tftp-server flash:dkern9971.100609R2-9-1-1SR1.sebn alias dkern9971.100609R2-9-1-1SR1.sebn
tftp-server flash:kern9971.9-1-1SR1.sebn alias kern9971.9-1-1SR1.sebn
tftp-server flash:rootfs9971.9-1-1SR1.sebn alias rootfs9971.9-1-1SR1.sebn
tftp-server flash:sboot9971.031610R1-9-1-1SR1.sebn alias sboot9971.031610R1-9-1-1SR1.sebn
tftp-server flash:skern9971.022809R2-9-1-1SR1.sebn alias skern9971.022809R2-9-1-1SR1.sebn
tftp-server flash:/Ringtones/RingList.xml alias RingList.xml
tftp-server flash:/Ringtones/Ring1.raw alias Ring1.raw
tftp-server flash:/Ringtones/Ring2.raw alias Ring2.raw
tftp-server flash:/Ringtones/Ring3.raw alias Ring3.raw

```

```

tftp-server flash:/Ringtones/Ring4.raw alias Ring4.raw
tftp-server flash:/Ringtones/Ring5.raw alias Ring5.raw
tftp-server flash:/Ringtones/Ring6.raw alias Ring6.raw
tftp-server flash:/Ringtones/Ring7.raw alias Ring7.raw
tftp-server flash:/Ringtones/Bass.raw alias Bass.raw
tftp-server flash:/Ringtones/Chime.raw alias Chime.raw
tftp-server flash:/Ringtones/Jamaica.raw alias Jamaica.raw
tftp-server flash:/Ringtones/Pop.raw alias Pop.raw
tftp-server flash:/Ringtones/Analog1.raw alias Analog1.raw
tftp-server flash:/Ringtones/Analog2.raw alias Analog2.raw
tftp-server flash:/Germany/G4-TONES.XML alias Germany/g4-tones.xml
tftp-server flash:/German_Germany/GD-SIP.JAR alias German_Germany/gd-sip.jar
tftp-server flash:/German_Germany/GH-SIP.JAR alias German_Germany/gh-sip.jar
!
!
!
control-plane
!
bridge 1 protocol ieee
bridge 1 route ip
!
voice-port 0/0/0
!
voice-port 0/0/1
!
voice-port 0/0/2
!
voice-port 0/0/3
!
voice-port 0/1/0
!
voice-port 0/1/1
!
voice-port 0/4/0
  auto-cut-through
  signal immediate
  input gain auto-control
  description Music On Hold Port
!
!
mgcp bind control source-interface FastEthernet0/0
mgcp bind media source-interface FastEthernet0/0
!
mgcp profile default
!
sccp local Vlan1
sccp ccm 10.10.10.1 identifier 1 version 7.0
sccp
!
sccp ccm group 1
  bind interface Vlan1
  associate ccm 1 priority 1
  associate profile 1 register MOTMTP
!
dspfarm profile 1 mtp
  codec g711alaw
  codec pass-through
  maximum sessions software 200
  associate application SCCP
  shutdown
!
dial-peer voice 2 voip
  description **Incoming VOIP Call**
  translation-profile incoming IN
  session protocol sipv2
  session target dns:sipgate.de
  incoming called-number .%
  voice-class codec 1
  voice-class sip dtmf-relay force rtp-nte
  dtmf-relay rtp-nte
  no vad
!
dial-peer voice 1 voip
  description **Outgoing VOIP Call**
  translation-profile outgoing OUT
  destination-pattern .T

```

```
session protocol sipv2
session target ipv4:10.10.10.1
voice-class codec 1
voice-class sip dtmf-relay force rtp-nte
dtmf-relay rtp-nte
no vad
!
!
sip-ua
credentials username 1132000 password 7 **password** realm sipgate.de
authentication username 1132000 password 7 **password** realm sipgate.de
no remote-party-id
retry invite 4
retry response 3
retry bye 2
retry cancel 2
retry register 5
retry options 10
timers connect 100
timers register 250
registrar 1 dns:sipgate.de expires 3600
sip-server dns:sipgate.de
!
!
!
telephony-service
sdspfarm units 3
sdspfarm transcode sessions 8
sdspfarm tag 1 MOTMTP
no auto-reg-ephone
max-ephones 12
max-dn 30
ip source-address 10.10.10.1 port 2000
cnf-file location flash:
user-locale U1 load CME-locale-de_DE-German-8.6.2.4.tar
load 7925 CP7925G-1.4.1SR1.LOADS
time-zone 23
time-format 24
date-format dd-mm-yy
max-conferences 4 gain -6
dn-webedit
time-webedit
transfer-system full-consult
create cnf-files version-stamp Jan 01 2002 00:00:00
!
!
ephone-dn 1 dual-line
number 12
!
!
ephone-dn 2 dual-line
number 13
!
!
ephone 1
device-security-mode none
description Phone1
mac-address E05F.B9BC.74CE
max-calls-per-button 4
type 7925
button 1:1
!
!
!
ephone 2
device-security-mode none
description Phone2
mac-address E05F.B9BB.F4D9
max-calls-per-button 4
type 7925
button 1:2
!
!
!
line con 0
no modem enable
```

```
line aux 0
line 2
  no activation-character
  no exec
  transport preferred none
  transport input all
  transport output lat pad telnet rlogin lapb-ta mop udptn v120 ssh
line vty 0 4
  privilege level 15
  transport input telnet ssh
  transport output telnet ssh
line vty 5 15
  exec-timeout 30 0
  privilege level 15
  transport input telnet ssh
  transport output telnet ssh
!
end
```