

```

version 15.2
service timestamps debug datetime msec
service timestamps log datetime msec
!
!
boot-start-marker
boot-end-marker
!
!
no logging buffered
!
aaa new-model
!
!
aaa authentication login default local
aaa authorization exec default local
!
!
!
aaa session-id common
network-clock-participate wic 1
mmi polling-interval 60
no mmi auto-configure
no mmi pvc
mmi snmp-timeout 180
!
!
!
ip dhcp relay information trust-all
ip dhcp excluded-address 10.10.10.1 10.10.10.10
!
ip dhcp pool phone
network 10.10.10.0 255.255.255.0
default-router 10.10.10.1
dns-server 217.0.43.97 217.0.43.113
option 150 ip 10.10.10.1
!
!
ip name-server 217.0.43.97
ip cef
no ipv6 cef
!
multilink bundle-name authenticated
!
!
voice rtp send-recv
!
voice service voip
ip address trusted list
no ip address trusted authenticate
callmonitor
no callmonitor trace
allow-connections h323 to h323
allow-connections h323 to sip
allow-connections sip to h323
allow-connections sip to sip
no supplementary-service sip handle-replaces
sip
registrar server expires max 3600 min 180
asymmetric payload full
video screening
!
voice class codec 1
codec preference 1 g711ulaw
codec preference 2 g711ulaw
codec preference 3 g723r53
codec preference 4 g729r8
codec preference 5 g729br8
codec preference 6 g726r32
codec preference 7 g728
!
!
voice register global
mode cme
source-address 10.10.10.1 port 5060
max-dn 10
max-pool 4
load 9971 sip9971.9-3-2SR1-1
authenticate register
authenticate realm all
timezone 21
time-format 24
date-format D/M/Y
voicemail 999
tftp-path flash:
file text
create profile sync 0000420080667251
network-locale DE
user-locale DE
camera
video
overlap-signal
!
voice register dn 1
number 91
allow watch
no-reg
mwi
!
!
voice register pool 1
registration-timer max 300 min 60
id mac 0008.3030.6AAA
session-transport tcp
type 9971
number 1 dn 1
template 1
voice-class codec 1
username cisco password cisco
no vad
camera
video
!
!
!
!
voice translation-rule 1
rule 2 /^(.*)\.(.*)\.(.*)\/ /0/2/
!
voice translation-rule 2
rule 1 /123456/ /91/
!
voice translation-rule 3
rule 1 /.*\/ /123456/
!
!
!
voice translation-profile IN
translate calling 1
translate called 2
!
voice translation-profile OUT
translate calling 3
!
!
!
voice-card 0
!
!
!
license udi pid C1861-UC-B/K9-MS sn FHK144871U3
file privilege 0
!
!
no ip ftp passive
!
!
!
interface FastEthernet0/0
description ***ISP Provider***
ip address dhcp
no ip proxy-arp
ip nat outside
ip virtual-reassembly in
duplex auto
speed auto
!
interface Integrated-Service-Engine0/0
ip unnumbered Vlan1
ip nat inside
ip virtual-reassembly in
service-module ip address 10.10.10.2 255.255.255.0
service-module ip default-gateway 10.10.10.1
!
!
interface Vlan1
ip address 10.10.10.1 255.255.255.0
ip nat inside
ip virtual-reassembly in
!
ip forward-protocol nd
ip http server
ip http authentication aaa
ip http secure-server
ip http timeout-policy idle 60 life 86400 requests 10000

```

```
ip http path flash:
!
!
ip nat inside source list 1 interface FastEthernet0/0 overload
ip route 0.0.0.0 0.0.0.0 87.186.225.92 254
ip route 10.10.10.2 255.255.255.255 Integrated-Service-Engine0/0
!
access-list 1 permit 10.10.10.0 0.0.0.255
access-list 1 permit 192.168.2.0 0.0.0.255
!
!
control-plane
!
!
voice-port 0/0/0
cptone DE
station-id number 94
caller-id enable
!
voice-port 0/0/1
!
voice-port 0/0/2
!
voice-port 0/0/3
!
voice-port 0/1/0
!
voice-port 0/1/1
!
voice-port 0/4/0
auto-cut-through
signal immediate
input gain auto-control
description Music On Hold Port
!
!
!
mgcp profile default
!
!
!
dial-peer voice 4 voip
description **Outgoing VOIP**
translation-profile outgoing OUT
destination-pattern ...1
session protocol sip2
session target dns:tel.t-online.de
voice-class sip dtmf-relay force rtp-nte
dtmf-relay rtp-nte
codec g711alaw
no vad
!
dial-peer voice 10 voip
description **Incoming VOIP**
translation-profile incoming IN
session protocol sip2
session target ipv4:10.10.10.1
incoming called-number 123456
voice-class sip dtmf-relay force rtp-nte
dtmf-relay rtp-nte
no vad
!
!
dial-peer voice 20 voip
description **Mailbox**
destination-pattern 99
session protocol sip2
session target ipv4:10.10.10.2
voice-class codec 1
dtmf-relay rtp-nte
no vad
!
dial-peer voice 19 pots
destination-pattern 94
port 0/0/0
no sip-register
!
!
presence
presence call-list
!
!
sip-ua
credentials username 123456 password ***password*** realm tel.t-online.de
authentication username ***user*** password ***password*** realm tel.t-online.de
nat symmetric rtp active
nat symmetric check-media-src
no remote-party-id
retry invite 4
retry response 3
retry bye 2
retry cancel 2
retry notify 6
retry register 5
retry options 10
timers connect 100
timers notify 100
timers register 250
mdf-server ipv4:10.10.10.2 expires 3600 port 5060 transport udp
registrar 1 dns:tel.t-online.de expires 3600
sip-server dns:tel.t-online.de
connection-reuse
host-registrar
presence enable
!
!
telephony-service
no auto-reg-ephone
max-ephones 12
max-dn 30
ip source-address 10.10.10.1 port 2000
max-redirect 5
timeouts interdigit 2
url services http://10.10.10.2/voiceview/common/login.do
cnf-file location flash:
user-locale U1 load CME-locale-de_DE-German-8.8.2.5.tar
load 7925 (P7925G-1.4.4.3.LOADS)
time-zone 23
time-format 24
date-format dd-mm-yy
voicemail 999
max-conferences 4 gain -6
dn-webedit
time-webedit
transfer-system full-consult
create cnf-files version-stamp 7960 Nov 11 2013 14:07:24
!
!
!
ephone-dn 1 dual-line
number 92 no-reg primary
label IP-Mobil-1
description IP-Mobil-1
name IP-Mobil-1
allow watch
!
!
ephone-dn 2 dual-line
number 93 no-reg primary
label IP-Mobil-2
description IP-Mobil-2
name IP-Mobil-2
allow watch
!
!
!
ephone 1
device-security-mode none
description IP-Mobil-1
mac-address E08F.898C.74CE
max-calls-per-button 4
type 7925
button 1:1
!
!
!
ephone 2
device-security-mode none
description IP-Mobil-2
mac-address E08F.898B.F409
max-calls-per-button 4
type 7925
button 1:2
!
!
!
line con 0
```

```
no modem enable
line aux 0
line 2
no activation-character
no exec
transport preferred none
transport input all
transport output pad telnet rlogin lapb-ta mop udptn v120 ssh
line vty 0 4
access-class 102 in
privilege level 15
transport input all
transport output all
line vty 5 15
access-class 101 in
exec-timeout 30 0
privilege level 15
transport input all
transport output all
!
!
end
```