

Aug 24 11:58:30.656: ISDN BR0/0/1 Q931: Applying typeplan for sw-type 0x1 is 0x0 0x0, Calling num 417660107  
\*Aug 24 11:58:30.656: ISDN BR0/0/1 Q931: Sending SETUP callref = 0x0023 callID = 0x8031 switch = basic-net3 interface = User  
\*Aug 24 11:58:30.656: ISDN BR0/0/1 Q931: TX -> SETUP pd = 8 callref = 0x23  
    Bearer Capability i = 0x8890  
        Standard = CCITT  
        Transfer Capability = Unrestricted Digital  
        Transfer Mode = Circuit  
        Transfer Rate = 64 kbit/s  
    Channel ID i = 0x81  
        Preferred, B1  
    Progress Ind i = 0x8183 - Origination address is non-ISDN  
    Calling Party Number i = 0x0080, '417660107'  
        Plan:Unknown, Type:Unknown  
    Called Party Number i = 0x80, '0797203223'  
        Plan:Unknown, Type:Unknown  
\*Aug 24 11:58:30.696: ISDN BR0/0/1 Q931: RX <- SETUP\_ACK pd = 8 callref = 0xA3  
    Channel ID i = 0x89  
        Exclusive, B1  
\*Aug 24 11:58:35.700: ISDN BR0/0/1 Q931: RX <- CALL\_PROC pd = 8 callref = 0xA3  
\*Aug 24 11:58:52.112: ISDN BR0/0/1 Q931: RX <- DISCONNECT pd = 8 callref = 0xA3  
    Cause i = 0x829F - Normal, unspecified  
\*Aug 24 11:58:52.116: ISDN BR0/0/1 Q931: TX -> RELEASE pd = 8 callref = 0x23  
    Cause i = 0x809F - Normal, unspecified  
\*Aug 24 11:58:52.140: ISDN BR0/0/1 Q931: RX <- RELEASE\_COMP pd = 8 callref = 0xA3  
\*Aug 24 11:58:52.144: ISDN BR0/1/0 Q931: Applying typeplan for sw-type 0x1 is 0x0 0x0, Calling num 417660107  
\*Aug 24 11:58:52.148: ISDN BR0/1/0 Q931: Sending SETUP callref = 0x0024 callID = 0x8032 switch = basic-net3 interface = User  
\*Aug 24 11:58:52.148: ISDN BR0/1/0 Q931: TX -> SETUP pd = 8 callref = 0x24  
    Bearer Capability i = 0x8890  
        Standard = CCITT  
        Transfer Capability = Unrestricted Digital  
        Transfer Mode = Circuit  
        Transfer Rate = 64 kbit/s  
    Channel ID i = 0x81  
        Preferred, B1  
    Progress Ind i = 0x8183 - Origination address is non-ISDN  
    Calling Party Number i = 0x0080, '417660107'  
        Plan:Unknown, Type:Unknown  
    Called Party Number i = 0x80, '0797203223'  
        Plan:Unknown, Type:Unknown  
\*Aug 24 11:58:52.184: ISDN BR0/1/0 Q931: RX <- SETUP\_ACK pd = 8 callref = 0xA4  
    Channel ID i = 0x89  
        Exclusive, B1  
\*Aug 24 11:58:57.188: ISDN BR0/1/0 Q931: RX <- CALL\_PROC pd = 8 callref = 0xA4  
\*Aug 24 11:59:03.116: ISDN BR0/1/0 Q931: TX -> DISCONNECT pd = 8 callref = 0x24  
    Cause i = 0x8090 - Normal call clearing

\*Aug 24 11:59:03.140: ISDN BR0/1/0 Q931: RX <- RELEASE pd = 8 callref = 0xA4  
Cause i = 0x8290 - Normal call clearing

\*Aug 24 11:59:03.140: ISDN BR0/1/0 Q931: TX -> RELEASE\_COMP pd = 8  
callvoice register global

\*Aug 24 12:02:59.640: ISDN BR0/0/1 Q931: Applying typeplan for sw-type 0x1 is 0x0 0x0, Calling num 417660108

\*Aug 24 12:02:59.640: ISDN BR0/0/1 Q931: Sending SETUP callref = 0x0025  
callID = 0x8033 switch = basic-net3 interface = User

\*Aug 24 12:02:59.640: ISDN BR0/0/1 Q931: TX -> SETUP pd = 8 callref = 0x25  
Bearer Capability i = 0x8890  
Standard = CCITT  
Transfer Capability = Unrestricted Digital  
Transfer Mode = Circuit  
Transfer Rate = 64 kbit/s  
Channel ID i = 0x81  
Preferred, B1  
Progress Ind i = 0x8183 - Origination address is non-ISDN  
Calling Party Number i = 0x0080, '417660108'  
Plan:Unknown, Type:Unknown  
Called Party Number i = 0x80, '0797203223'  
Plan:Unknown, Type:Unknown

\*Aug 24 12:02:59.680: ISDN BR0/0/1 Q931: RX <- SETUP\_ACK pd = 8 callref = 0xA5  
Channel ID i = 0x89  
Exclusive, B1

\*Aug 24 12:03:04.692: ISDN BR0/0/1 Q931: RX <- CALL\_PROC pd = 8 callref = 0xA5sh ca  
VGW\_Manatrade\_01#sh cal  
VGW\_Manatrade\_01#sh cal

\*Aug 24 12:03:21.792: ISDN BR0/0/1 Q931: RX <- DISCONNECT pd = 8 callref = 0xA5  
Cause i = 0x829F - Normal, unspecified

\*Aug 24 12:03:21.792: ISDN BR0/0/1 Q931: TX -> RELEASE pd = 8 callref = 0x25  
Cause i = 0x809F - Normal, unspecified

\*Aug 24 12:03:21.816: ISDN BR0/0/1 Q931: RX <- RELEASE\_COMP pd = 8  
callref = 0xA5

\*Aug 24 12:03:21.824: ISDN BR0/1/0 Q931: Applying typeplan for sw-type 0x1 is 0x0 0x0, Calling num 417660108

\*Aug 24 12:03:21.824: ISDN BR0/1/0 Q931: Sending SETUP callref = 0x0026  
callID = 0x8034 switch = basic-net3 interface = Use

\*Aug 24 12:03:21.824: ISDN BR0/1/0 Q931: TX -> SETUP pd = 8 callref = 0x26  
Bearer Capability i = 0x8890  
Standard = CCITT  
Transfer Capability = Unrestricted Digital  
Transfer Mode = Circuit  
Transfer Rate = 64 kbit/s  
Channel ID i = 0x81  
Preferred, B1  
Progress Ind i = 0x8183 - Origination address is non-ISDN  
Calling Party Number i = 0x0080, '417660108'  
Plan:Unknown, Type:Unknown  
Called Party Number i = 0x80, '0797203223'  
Plan:Unknown, Type:Unknown

\*Aug 24 12:03:21.864: ISDN BR0/1/0 Q931: RX <- SETUP\_ACK pd = 8 callref  
= 0xA6  
Channel ID i = 0x89  
Exclusive, B1