

```

interface TenGigabitEthernet1/2
description *** Connection to ASR9000 ***
switchport trunk encapsulation dot1q
switchport trunk allowed vlan 100
switchport mode trunk
!
interface Vlan100
ip address 192.168.100.12 255.255.255.0
!

```

SITE A-SW3560X#ping 192.168.100.13

```

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.100.13, timeout is 2 seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/5/9 ms
SITE A-SW3560X#
SITE A-SW3560X#ping 192.168.100.50]

```

```

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.100.70, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)
SITE A-SW3560X#

```

SITE A-SW3560X#ping 192.168.100.70

```

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.100.70, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)
SITE A-SW3560X#

```

```

interface Bundle-Ether1
l2transport
!
interface TenGigE0/0/0/1
cdp
!
interface TenGigE0/0/0/1.100 l2transport
encapsulation dot1q 100
!
interface TenGigE0/0/0/4
description *** Connection to SW3560 ***
cdp
!
interface TenGigE0/0/0/4.100 l2transport
encapsulation dot1q 100
!
interface TenGigE0/0/0/6
description *** Connection to SuperComputo ***
bundle id 1 mode on
!
interface TenGigE0/0/0/7
description *** Connection to SuperComputo ***
bundle id 1 mode on
!
l2vpn
bridge group 1
bridge-domain VLAN100
interface Bundle-Ether1
!
interface TenGigE0/0/0/1.100
!
interface TenGigE0/0/0/4.100
!

```

```

interface Bundle-Ether1
l2transport
!
interface TenGigE0/0/0/0
cdp
!
interface TenGigE0/0/0/0.100 l2transport
encapsulation dot1q 100
!
interface TenGigE0/0/0/4
description *** Connection to SW3560 ***
cdp
!
interface TenGigE0/0/0/4.100 l2transport
encapsulation dot1q 100
!
interface TenGigE0/0/0/6
description *** Connection to SuperComputo ***
bundle id 1 mode on
!
interface TenGigE0/0/0/7
description *** Connection to SuperComputo ***
bundle id 1 mode on
!
l2vpn
bridge group 1
bridge-domain VLAN100
interface Bundle-Ether1
!
interface TenGigE0/0/0/0.100]
!
interface TenGigE0/0/0/4.100
!

```

```

interface TenGigabitEthernet1/1
description *** Connection to ASR9000 ***
switchport trunk encapsulation dot1q
switchport trunk allowed vlan 100
switchport mode trunk
!
interface TenGigabitEthernet1/2
!
interface Vlan100
ip address 192.168.100.13 255.255.255.0
!
SITE B-SW3560X#ping 192.168.100.12

```

```

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.100.12, timeout is 2 seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/9 ms
SITE B-SW3560X#ping 192.168.100.70

```

```

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.100.70, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)
SITE B-SW3560X#
SITE B-SW3560X#ping 192.168.100.50

```

```

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.100.70, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)
SITE B-SW3560X#

```

