

Endpoint

* MAC Address 00:1B:2A:BC:5D:E0

Static Assignment

* Policy Assignment Cisco-AP-Aironet-1130 ▼

Static Group Assignment

* Identity Group Assignment Cisco-Access-Point ▼

Attribute List

AAA-Server	ise1
AllowedProtocolMatchedRule	L2-WIRED-MAB
AuthenticationIdentityStore	Internal Endpoints
AuthenticationMethod	Lookup
AuthorizationPolicyMatchedRule	L2-WIRED-MAB-LAP
BYODRegistration	Unknown
Called-Station-ID	00-18-18-0A-93-84
Calling-Station-ID	00-1B-2A-BC-5D-E0
DestinationIPAddress	192.168.99.11
DestinationPort	1812
Device IP Address	192.168.0.254
Device Port	1645
Device Type	Device Type#All Device Types#Switch
DeviceRegistrationStatus	NotRegistered
EndPointMACAddress	00-1B-2A-BC-5D-E0
EndPointPolicy	Cisco-AP-Aironet-1130
EndPointProfilerServer	ise1.lab2.summerdale.co.uk
EndPointSource	DHCP SPAN Probe
FQDN	hp-nc6400.
Framed-IP-Address	192.168.99.50
IdentityGroup	Cisco-Access-Point
Location	Location#All Locations

MACAddress	00:1B:2A:BC:5D:E0
MatchedPolicy	Cisco-AP-Aironet-1130
MoveFromPort	4
MoveToPort	4
NADAddress	192.168.0.254
NAS-IP-Address	192.168.0.254
NAS-Port	50002
NAS-Port-Id	FastEthernet0/2
NAS-Port-Type	Ethernet
NetworkDeviceGroups	Device Type#All Device Types#Switch, Location#All Locations
NetworkDeviceName	3560-1
OUI	CISCO SYSTEMS, INC.
OriginalUserName	001b2abc5de0
PolicyVersion	11
PostureAssessmentStatus	NotApplicable
RadiusPacketType	AccessRequest
SelectedAccessService	Default Network Access
SelectedAuthenticationIdentityStores	Internal Endpoints
SelectedAuthorizationProfiles	L2-PROF-LAP
Service-Type	Framed
StaticAssignment	false
StaticGroupAssignment	false
Timestamp	1348244698
Total Certainty Factor	70
UpdateTime	1382167167795
UseCase	Host Lookup
User-Name	00-1B-2A-BC-5D-E0
UserType	Host
Vlan	99
VlanName	VLAN0099
cafSessionAuthUserName	00-1B-2A-BC-5D-E0

cafSessionAuthVlan	0
cafSessionAuthorizedBy	Authentication Server
cafSessionDomain	2
cafSessionStatus	6
cdpCacheAddress	192.168.99.50
cdpCacheCapabilities	T;I
cdpCacheDeviceId	ap
cdpCachePlatform	cisco AIR-AP1131AG-E-K9
cdpCacheVersion	Cisco IOS Software, C1130 Software (C1130-K9W7-M), Version 12.4(10b)JDA3, RE 02:59 by prod_rel_team
chaddr	00:1b:2a:bc:5d:e0
ciaddr	0.0.0.0
client-fqdn	ÿÿ
dhcp-class-identifier	MSFT 5.0
dhcp-client-identifier	01:00:1b:2a:bc:5d:e0
dhcp-message-type	DHCPACK
dhcp-parameter-request-list	1, 15, 3, 6, 44, 46, 47, 31, 33, 249, 43
dhcp-requested-address	192.168.99.50
domain-name	lab2.summerdale.co.uk
dot1dBasePort	4
dot1xAuthAuthControlledPortControl	2
dot1xAuthAuthControlledPortStatus	2
flags	0x0000
giaddr	0.0.0.0
hlen	6
host-name	hp-nc6400
htype	Ethernet (10Mb)
ifDescr	FastEthernet0/2
ifIndex	10002
ifOperStatus	1
ifType	6
ip	192.168.99.50
locIfReason	up
op	BOOTREPLY
port	4
sysUpTime	156 days, 0:41:46.58
yiaddr	192.168.99.50