

Primary WLC

High Availability

AP Heartbeat Timeout(1-30)	<input type="text" value="30"/>
Local Mode AP Fast Heartbeat Timer State	<input type="button" value="Disable"/> ▼
FlexConnect Mode AP Fast Heartbeat Timer State	<input type="button" value="Disable"/> ▼
AP Primary Discovery Timeout(30 to 3600)	<input type="text" value="60"/>
AP Primed Join Timeout(120 - 43200 seconds)	<input type="text" value="120"/>
Back-up Primary Controller IP Address(Ipv4/Ipv6)	<input type="text" value="172.16.20.241"/>
Back-up Primary Controller name	<input type="text" value="CFC_WLC_BK"/>
Back-up Secondary Controller IP Address(Ipv4/Ipv6)	<input type="text"/>
Back-up Secondary Controller name	<input type="text"/>

TCF MCG

General

Name	<input type="text" value="CFC_WLC"/>
802.3x Flow Control Mode	<input type="button" value="Disabled"/> ▼
LAG Mode on next reboot	<input type="button" value="Disabled"/> ▼ (LAG Mode is currently disabled)
Broadcast Forwarding	<input type="button" value="Disabled"/> ▼
AP Multicast Mode	<input type="button" value="Multicast"/> ▼ <input type="text" value="239.20.226.197"/> Multicast Group Address
AP IPv6 Multicast Mode	<input type="button" value="Multicast"/> ▼ <input type="text" value="::"/> IPv6 Multicast Group Address
AP Fallback	<input type="button" value="Enabled"/> ▼
CAPWAP Preferred Mode	<input type="button" value="ipv4"/> ▼
Fast SSID change	<input type="button" value="Enabled"/> ▼
Link Local Bridging	<input type="button" value="Disabled"/> ▼
Default Mobility Domain Name	<input type="text" value="corficol"/>
RF Group Name	<input type="text" value="corficol"/>
User Idle Timeout (seconds)	<input type="text" value="300"/>
ARP Timeout (seconds)	<input type="text" value="300"/>
Web Radius Authentication	<input type="button" value="PAP"/> ▼
Operating Environment	Commercial (0 to 40 C)
Internal Temp Alarm Limits	0 to 65 C
WebAuth Proxy Redirection Mode	<input type="button" value="Disabled"/> ▼
WebAuth Proxy Redirection Port	<input type="text" value="0"/>
Captive Network Assistant Bypass	<input type="button" value="Disabled"/> ▼
Global IPv6 Config	<input type="button" value="Disabled"/> ▼
Web Color Theme	<input type="button" value="Red"/> ▼
HA SKU secondary unit	<input type="button" value="Disabled"/> ▼
Nas-Id	<input type="text"/>
HTTP Profiling Port	<input type="text" value="80"/>

Static Mobility Group Members

Local Mobility Group		corficol		
MAC Address	IP Address(Ipv4/Ipv6)	Group Name	Multicast IP	Status
00:42:5a:55:7a:c0	172.16.20.240	corficol	0.0.0.0	Up
c4:b9:cd:b7:d0:e0	172.16.20.241	corficol	0.0.0.0	Up

Licenses ¹

License	Type	Time(expires)	Count	Priority	Status
base	permanent	No Expiry	NA	Medium	Active, Not in Use
data_encryption	permanent	No Expiry	NA	Medium	Active, In Use
base-ao-count	evaluation	12 weeks, 6 days	75	High	Active, In Use

Foot Notes

1. Inherited licenses are shown for active secondary HA SKU controller.

Secondary WLC

High Availability

AP Heartbeat Timeout(1-30)	<input type="text" value="30"/>
Local Mode AP Fast Heartbeat Timer State	<input type="button" value="Disable"/> ▼
FlexConnect Mode AP Fast Heartbeat Timer State	<input type="button" value="Disable"/> ▼
AP Primary Discovery Timeout(30 to 3600)	<input type="text" value="60"/>
AP Primed Join Timeout(120 - 43200 seconds)	<input type="text" value="120"/>
Back-up Primary Controller IP Address(Ipv4/Ipv6)	<input type="text" value="172.16.20.240"/>
Back-up Primary Controller name	<input type="text" value="CFC_WLC"/>
Back-up Secondary Controller IP Address(Ipv4/Ipv6)	<input type="text"/>
Back-up Secondary Controller name	<input type="text"/>

Name	<input type="text" value="CFC_WLC_BK"/>
802.3x Flow Control Mode	<input type="button" value="Disabled"/> ▼
LAG Mode on next reboot	<input type="button" value="Disabled"/> ▼
Broadcast Forwarding	<input type="button" value="Disabled"/> ▼
AP Multicast Mode	<input type="button" value="Multicast"/> ▼ <input type="text" value="239.20.226.197"/> Multicast Group
AP IPv6 Multicast Mode	<input type="button" value="Multicast"/> ▼ <input type="text" value="::"/>
AP Fallback	<input type="button" value="Enabled"/> ▼
CAPWAP Preferred Mode	<input type="button" value="ipv4"/> ▼
Fast SSID change	<input type="button" value="Enabled"/> ▼
Link Local Bridging	<input type="button" value="Disabled"/> ▼
Default Mobility Domain Name	<input type="text" value="corficol"/>
RF Group Name	<input type="text" value="corficol"/>
User Idle Timeout (seconds)	<input type="text" value="300"/>
ARP Timeout (seconds)	<input type="text" value="300"/>
Web Radius Authentication	<input type="button" value="PAP"/> ▼
Operating Environment	Commercial (0 to 40 C)
Internal Temp Alarm Limits	0 to 65 C
WebAuth Proxy Redirection Mode	<input type="button" value="Disabled"/> ▼
WebAuth Proxy Redirection Port	<input type="text" value="0"/>
Captive Network Assistant Bypass	<input type="button" value="Disabled"/> ▼
Global IPv6 Config	<input type="button" value="Disabled"/> ▼
Web Color Theme	<input type="button" value="Red"/> ▼
HA SKU secondary unit	<input type="button" value="Enabled"/> ▼
Nas-Id	<input type="text"/>

Licenses ¹

License	Type	Time(expires)	Count	Priority	Status
base	permanent	No Expiry	NA	Medium	Inactive
base-ap-count	permanent	No Expiry	75	Medium	Active, Not in Use
base	permanent	No Expiry	NA	Medium	Active, Not in Use
data_encryption	permanent	No Expiry	NA	Medium	Active, In Use
base-ap-count	evaluation	12 weeks, 6 days	75	None	Inactive

Foot Notes

1. Inherited licenses are shown for active secondary HA SKU controller.