

```

WLAN Identifier..... XXX
Profile Name..... XXXXXXXXXXXX
Network Name (SSID)..... XXXXXXXXXXXX
Status..... Enabled
MAC Filtering..... Disabled
Broadcast SSID..... Enabled
AAA Policy Override..... Disabled
Network Admission Control
Client Profiling Status
  Radius Profiling ..... Enabled
  DHCP ..... Enabled
  HTTP ..... Enabled
  Local Profiling ..... Enabled
  DHCP ..... Enabled
  HTTP ..... Enabled
  Radius-NAC State..... Disabled
  SNMP-NAC State..... Disabled
  Quarantine VLAN..... 0
Maximum number of Associated Clients..... 0
Maximum number of Clients per AP Radio..... 200

--More-- or (q)uit
ATF Policy..... 0
Number of Active Clients..... 4
Exclusionlist Timeout..... 60 seconds
Session Timeout..... 1800 seconds
User Idle Timeout..... Disabled
Sleep Client..... disable
Sleep Client Timeout..... 720 minutes
User Idle Threshold..... 0 Bytes
NAS-identifier..... none
CHD per WLAN..... Enabled
Webauth DHCP exclusion..... Disabled
Interface..... prod
Multicast Interface..... Not Configured
WLAN IPv4 ACL..... unconfigured
WLAN IPv6 ACL..... unconfigured
WLAN Layer2 ACL..... unconfigured
mDNS Status..... Enabled
mDNS Profile Name..... default-mdns-
profile
DHCP Server..... Default
DHCP Address Assignment Required..... Disabled
Static IP client tunneling..... Disabled
Tunnel Profile..... Unconfigured
PMIPv6 Mobility Type..... none

--More-- or (q)uit
  PMIPv6 MAG Profile..... Unconfigured
  PMIPv6 Default Realm..... Unconfigured
  PMIPv6 NAI Type..... Hexadecimal
  PMIPv6 MAG location..... WLC
Quality of Service..... Silver

```

```

Per-SSID Rate Limits..... Upstream
Downstream
Average Data Rate..... 0 0
Average Realtime Data Rate..... 0 0
Burst Data Rate..... 0 0
Burst Realtime Data Rate..... 0 0
Per-Client Rate Limits..... Upstream
Downstream
Average Data Rate..... 0 0
Average Realtime Data Rate..... 0 0
Burst Data Rate..... 0 0
Burst Realtime Data Rate..... 0 0
Scan Defer Priority..... 4,5,6
Scan Defer Time..... 100 milliseconds
WMM..... Allowed
WMM UAPSD Compliant Client Support..... Disabled
Media Stream Multicast-direct..... Disabled
CCX - AironetIe Support..... Disabled
CCX - Gratuitous ProbeResponse (GPR)..... Disabled
CCX - Diagnostics Channel Capability..... Disabled

```

--More-- or (q)uit

```

Dot11-Phone Mode (7920)..... Disabled
Wired Protocol..... None
Passive Client Feature..... Disabled
Peer-to-Peer Blocking Action..... Disabled
Radio Policy..... All
DTIM period for 802.11a radio..... 1
DTIM period for 802.11b radio..... 1
Radius Servers
  Authentication..... XXXXXXXXXXXX
  Authentication..... XXXXXXXXXXXX
  Accounting..... Disabled
  Dynamic Interface..... Disabled
  Dynamic Interface Priority..... wlan
Local EAP Authentication..... Disabled
Radius NAI-Realm..... Disabled
Mu-Mimo..... Enabled
Security

```

```

  802.11 Authentication:..... Open System
  FT Support..... Disabled
  Static WEP Keys..... Disabled
  802.1X..... Disabled
  Wi-Fi Protected Access (WPA/WPA2)..... Enabled

```

--More-- or (q)uit

```

  WPA (SSN IE)..... Disabled
  WPA2 (RSN IE)..... Enabled
    TKIP Cipher..... Disabled
    AES Cipher..... Enabled
  OSEN IE..... Disabled
  Auth Key Management
    802.1x..... Enabled

```

```

    PSK..... Disabled
    CCKM..... Disabled
    FT-1X(802.11r)..... Disabled
    FT-PSK(802.11r)..... Disabled
    PMF-1X(802.11w)..... Disabled
    PMF-PSK(802.11w)..... Disabled
    OSEN-1X..... Disabled
    FT Reassociation Timeout..... 20
    FT Over-The-DS mode..... Enabled
    GTK Randomization..... Disabled
    SKC Cache Support..... Disabled
    CCKM TSF Tolerance..... 1000
    Wi-Fi Direct policy configured..... Disabled
    EAP-Passthrough..... Disabled
    CKIP ..... Disabled
    Web Based Authentication..... Disabled

```

--More-- or (q)uit

```

    Web Authentication Timeout..... 300
    Web-Passthrough..... Disabled
    Mac-auth-server..... 0.0.0.0
    Web-portal-server..... 0.0.0.0
    Conditional Web Redirect..... Disabled
    Splash-Page Web Redirect..... Disabled
    Auto Anchor..... Disabled
    FlexConnect Local Switching..... Disabled
    FlexConnect Central Association..... Disabled
    flexconnect Central Dhcp Flag..... Disabled
    flexconnect nat-pat Flag..... Disabled
    flexconnect Dns Override Flag..... Disabled
    flexconnect PPPoE pass-through..... Disabled
    flexconnect local-switching IP-source-guar.... Disabled
    FlexConnect Vlan based Central Switching ..... Disabled
    FlexConnect Local Authentication..... Disabled
    FlexConnect Learn IP Address..... Enabled
    Client MFP..... Disabled
    PMF..... Disabled
    PMF Association Comeback Time..... 1
    PMF SA Query RetryTimeout..... 200
    Tkip MIC Countermeasure Hold-down Timer..... 60
    Eap-params..... Disabled

```

--More-- or (q)uit

```

    AVC Visibilty..... Enabled
    AVC Profile Name..... XXXX
    Flow Monitor Name..... None
    Split Tunnel Configuration
        Split Tunnel..... Disabled
    Call Snooping..... Disabled
    Roamed Call Re-Anchor Policy..... Disabled
    SIP CAC Fail Send-486-Busy Policy..... Enabled
    SIP CAC Fail Send Dis-Association Policy..... Disabled
    KTS based CAC Policy..... Disabled
    Assisted Roaming Prediction Optimization..... Enabled

```

```

802.11k Neighbor List..... Enabled
802.11k Neighbor List Dual Band..... Enabled
802.11v Directed Multicast Service..... Disabled
802.11v BSS Max Idle Service..... Enabled
802.11v BSS Transition Service..... Disabled
802.11v BSS Transition Disassoc Imminent..... Disabled
802.11v BSS Transition Disassoc Timer..... 200
802.11v BSS Transition OpRoam Disassoc Timer..... 40
DMS DB is empty
Band Select..... Disabled
Load Balancing..... Disabled
Multicast Buffer..... Disabled

```

```

--More-- or (q)uit
Universal Ap Admin..... Disabled

```

```

Mobility Anchor List
WLAN ID      IP Address          Status
Priority
-----
-----
-----

```

```

802.11u..... Disabled

```

```

MSAP Services..... Disabled

```

Local Policy

```

-----
Priority  Policy Name
-----
-----

```

```

Lync State ..... Disabled
Audio QoS Policy..... Silver
Video QoS Policy..... Silver
App-Share QoS Policy..... Silver
File Transfer QoS Policy..... Silver

```