

Controller -> Interfaces -> deed-staff

Interfaces > Edit

General Information

Interface Name	deed-staff
MAC Address	cc:ef:48:b3:4b:4f

Configuration

Guest Lan	<input type="checkbox"/>
Quarantine	<input type="checkbox"/>
Quarantine Vlan Id	<input type="text" value="0"/>

Physical Information

The interface is attached to a LAG.

Enable Dynamic AP Management

Interface Address

VLAN Identifier	<input type="text" value="198"/>
IP Address	<input type="text" value="172.19.198.5"/>
Netmask	<input type="text" value="255.255.254.0"/>
Gateway	<input type="text" value="172.19.198.1"/>

DHCP Information

Primary DHCP Server	<input type="text" value="172.19.41.226"/>
Secondary DHCP Server	<input type="text"/>

Controller -> Interfaces -> management

Interfaces > Edit

General Information

Interface Name	management
MAC Address	cc:ef:48:b3:4b:4f

Configuration

Quarantine

Quarantine Vlan Id

NAT Address

Enable NAT Address

Interface Address

VLAN Identifier

IP Address

Netmask

Gateway

Physical Information

The interface is attached to a LAG.

Enable Dynamic AP Management

DHCP Information

Primary DHCP Server

Secondary DHCP Server

Wireless -> All APs -> FNB-LY-CONF

All APs > Details for FNB-LY-CONF

General	Credentials	Interfaces	High Availability	Inventory	FlexConnect	Advanced
General		Versions				
AP Name	FNB-LY-CONF		Primary Software Version	7.2.111.3		
Location	FNB Conferencce Rooms		Backup Software Version	7.0.116.0		
AP MAC Address	70:81:05:96:7d:42		Predownload Status	None		
Base Radio MAC	68:bc:0c:a0:ac:e0		Predownloaded Version	None		
Admin Status	Enable ▾		Predownload Next Retry Time	NA		
AP Mode	FlexConnect ▾		Predownload Retry Count	NA		
AP Sub Mode	None ▾		Boot Version	12.4.2.4		
Operational Status	REG		IOS Version	12.4(25e)JA2\$		
Port Number	LAG		Mini IOS Version	7.0.112.74		
Venue Group	Unspecified ▾		IP Config			
Venue Type	Unspecified ▾		IP Address	172.19.105.215		
Venue Name			Static IP	<input checked="" type="checkbox"/>		
Language			Static IP	172.19.105.215		
Network Spectrum			Netmask	255.255.255.0		
Interface Key			Gateway	172.19.105.1		
			¹ DNS IP Address	172.19.41.221		
			Domain Name	mndeedom.deed.state.mn.us		
			Time Statistics			
			UP Time	81 d, 10 h 25 m 06 s		
			Controller Associated Time	0 d, 08 h 34 m 50 s		
			Controller Association Latency	0 d, 00 h 00 m 12 s		

All APs > Details for FNB-LY-CONF

General	Credentials	Interfaces	High Availability	Inventory	FlexConnect	Advanced
VLAN Support <input checked="" type="checkbox"/>						
Native VLAN ID		<input type="text" value="105"/>	VLAN Mappings			
FlexConnect Group Name		FNB				
PreAuthentication Access Control Lists						
External WebAuthentication ACLs						
OfficeExtend AP						
Enable OfficeExtend AP		<input type="checkbox"/>				
Enable Least Latency Controller Join		<input type="checkbox"/>				
Reset Personal SSID						

All APs > FNB-LY-CONF > VLAN Mappings

AP Name	FNB-LY-CONF
Base Radio MAC	68:bc:0c:a0:ac:e0

WLAN Id	SSID	VLAN ID
1	DEED-Staff	198

Centrally switched Wlans

WLAN Id	SSID	VLAN ID
2	DEED-Guest	N/A

AP level VLAN ACL Mapping

Vlan Id	Ingress ACL	Egress ACL
198	none ▾	none ▾

Group level VLAN ACL Mapping

Vlan Id	Ingress ACL	Egress ACL
----------------	--------------------	-------------------

WANs -> DEED-Staff

WLANs > Edit 'DEED-Staff'

General	Security	QoS	Advanced
Profile Name	DEED-Staff		
Type	WLAN		
SSID	DEED-Staff		
Status	<input checked="" type="checkbox"/> Enabled		
Security Policies	[WPA2][Auth(802.1X)] (Modifications done under security tab will appear after applying the changes.)		
Radio Policy	<input type="text" value="All"/> ▼		
Interface/Interface Group(G)	<input type="text" value="deed-staff"/> ▼		
Multicast Vlan Feature	<input type="checkbox"/> Enabled		
Broadcast SSID	<input checked="" type="checkbox"/> Enabled		

WLANs > Edit 'DEED-Staff'

General **Security** **QoS** **Advanced**

Layer 2 **Layer 3** **AAA Servers**

Layer 2 Security ^g
MAC Filtering^g

Fast Transition

Fast Transition

WPA+WPA2 Parameters

WPA Policy
WPA2 Policy
WPA2 Encryption AES TKIP

Authentication Key Management

802.1X Enable
CCKM Enable
PSK Enable
FT 802.1X Enable
FT PSK Enable
WPA gtk-randomize State

WLANs > Edit 'DEED-Staff'

General **Security** **QoS** **Advanced**

Layer 2 **Layer 3** **AAA Servers**

Layer 3 Security ▼

Web Policy [1](#)

Allow AAA Override Enabled

Coverage Hole Detection Enabled

Enable Session Timeout
 Session Timeout (secs)

Aironet IE Enabled

Diagnostic Channel Enabled

Override Interface ACL IPv4 IPv6

P2P Blocking Action

Client Exclusion ³ Enabled
 Timeout Value (secs)

Maximum Allowed Clients ⁸

Static IP Tunneling ¹¹ Enabled

Wi-Fi Direct Clients Policy

Maximum Allowed Clients Per AP Radio

Off Channel Scanning Defer

Scan Defer Priority **0 1 2 3 4 5 6 7**

Scan Defer Time(msecs)

FlexConnect

FlexConnect Local Switching ² Enabled

FlexConnect Local Auth ¹² Enabled

Learn Client IP Address ⁵ Enabled

DHCP

DHCP Server Override

DHCP Addr. Assignment Required

Management Frame Protection (MFP)

MFP Client Protection ⁴

DTIM Period (in beacon intervals)

802.11a/n (1 - 255)

802.11b/g/n (1 - 255)

NAC

NAC State

Load Balancing and Band Select

Client Load Balancing

Client Band Select ²

Passive Client

Passive Client

Voice

Media Session Snooping Enabled

Re-anchor Roamed Voice Clients Enabled

KTS based CAC Policy Enabled

Client Profiling

DHCP Profiling Enabled